



- > Base G13 Bi-Pin
- > Daylight 5000k CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty

# 4' T8 Direct Replacement Tube

2200 lms | Ballast Driven | Model 64101461 | Part T8BC-4-15-850-MV



## SPECIFICATIONS

Model	64101461
Part	T8BC-4-15-850-MV
Description	4' T8 Direct Replacement Tube - Non-Dimmable
Input Voltage (VAC)	Ballast Driven
Wattage	15
Dimmability	Non
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	2200
CCT <sup>3</sup>	5000k
Location Rating	UL Damp
CRI <sup>4</sup>	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	8
DUV	0.0020
Operating Frequency (Hz)	50/60

<sup>1</sup> Hours lifetime with 70% lumen maintenance

<sup>2</sup> Thermally stable typical lumens (±10%)

<sup>3</sup> Thermally stable CCT (±10%)

<sup>4</sup> Color rendering index/Ra

## TO ORDER:

[www.ETiSSL.com](http://www.ETiSSL.com)

Call: 1.855.ETi.SSLI

1.855.384.7754





# 4' T8 Direct Replacement Tube

2200 lms | Ballast Driven | Model 64101461 | Part T8BC-4-15-850-MV

## SHIPPING INFORMATION

Model	64101461
Part	T8BC-4-15-850-MV
UPC	849489060019
Product Dimensions (L x W x H in.)	47.2 x 1.02 x 1.02
Product Dimensions (L x W x H cm.)	121 x 2.6 x 2.6
Product Weight (lbs.)	0.2
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	25
Master Carton Bar Code	50849489060014
Master Carton Dimensions (L x W x H in.)	48.8 x 5.9x 5.9
Master Carton Dimensions (L x W x H cm.)	124 x 15 x 15
Master Carton Weight (lbs)	12.98
Pallet Quantity	2400

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.ETiSSL.com/fcc15b](http://www.ETiSSL.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

ETi Solid State Lighting, Inc.  
720 Northgate Parkway  
Wheeling, IL 60090  
Phone: 855.384.7754