



# Recessed

HALO

Recessed Downlighting

# HLB LED Direct Mount Downlight

## HALO

The HLB ultra-thin LED lens downlight series (4-inch and 6-inch sizes) features a remote driver/junction box suitable for new construction and remodel applications. The products simply install in drywall or a suspended ceiling, eliminating the need for a recessed can. The products install from below the ceiling in as little as 3-1/2-inch plenum height and can be used in direct contact with insulation. The modules are available in a choice of 3000K or 4000K, or choose a model with CCT selectable technology, allowing the user to choose from a range of five color temperatures from 2700K to 5000K via a switch.



| Catalog Number  | Product Description                   | Finish | Replaces Up To | CCT                    | Voltage | Lumens (up to) | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|-----------------|---------------------------------------|--------|----------------|------------------------|---------|----------------|-------|-----------------|--------------|-----------------------|
| HLB4069301EMWR  | 4" Module, Round Remote Driver J-Box  | White  | 65W INC        | 3000K                  | 120V    | 697            | 12    | 720             | 080083863242 | 233167                |
| HLB4069401EMWR  | 4" Module, Round Remote Driver J-Box  | White  | 65W INC        | 4000K                  | 120V    | 773            | 12    | 720             | 080083863266 | 2331658               |
| HLB4069FS1EMWR  | 4" Module, Round Remote Driver J-Box  | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 752            | 12    | 864             | 080083848140 | 2322243               |
| HLB6099301EMWR  | 6" Module, Round Remote Driver J-Box  | White  | 65W INC        | 3000K                  | 120V    | 992            | 12    | 432             | 080083863327 | 2331660               |
| HLB6099401EMWR  | 6" Module, Round Remote Driver J-Box  | White  | 65W INC        | 4000K                  | 120V    | 1,057          | 12    | 432             | 080083863341 | 2331661               |
| HLB6099FS1EMWR  | 6" Module, Round Remote Driver J-Box  | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 1,103          | 16    | 450             | 080083848164 | 2322242               |
| HLB4S069301EMWR | 4" Module, Square Remote Driver J-Box | White  | 65W INC        | 3000K                  | 120V    | 734            | 12    | 720             | 080083863280 | 2331665               |
| HLB4S069401EMWR | 4" Module, Square Remote Driver J-Box | White  | 65W INC        | 4000K                  | 120V    | 721            | 12    | 720             | 080083873463 | 2331666               |
| HLB4S069FS1EMWR | 4" Module, Square Remote Driver J-Box | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 752            | 12    | 720             | 080083863303 | 2331662               |
| HLB6S099301EMWR | 6" Module, Square Remote Driver J-Box | White  | 65W INC        | 3000K                  | 120V    | 949            | 12    | 432             | 080083863365 | 2331667               |
| HLB6S099401EMWR | 6" Module, Square Remote Driver J-Box | White  | 65W INC        | 4000K                  | 120V    | 987            | 12    | 432             | 080083873487 | 2331668               |
| HLB6S099FS1EMWR | 6" Module, Square Remote Driver J-Box | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 1,103          | 12    | 432             | 080083863389 | 2331663               |

# RL LED Baffle Trim Direct Mount

## HALO

The RL-DM is a 4-inch or 6-inch regressed LED lens downlight with remote driver/junction box suitable for new construction and remodel applications. Field selectable color temperature and high color rendering provide excellent color performance. Simplified installation in drywall or suspended ceilings eliminates recessed cans saving time and money. Installs from below the ceiling in shallow plenum height, can be used in direct contact with insulation and is airtight.



| Catalog Number | Product Description                          | Finish | Replaces Up To | Selectable CCT | Voltage | Lumens (up to) | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|----------------------------------------------|--------|----------------|----------------|---------|----------------|-------|-----------------|--------------|-----------------------|
| RL4069S1EWHDM  | 4" Retrofit Baffle-Trim, Remote Driver J-Box | White  | 65W INC        | 2700K-5000K    | 120V    | 652            | 9     | 300             | 080083858101 | 2325604               |
| RL6069S1EWHDM  | 6" Retrofit Baffle-Trim, Remote Driver J-Box | White  | 65W INC        | 2700K-5000K    | 120V    | 719            | 9     | 240             | 080083858125 | 2325603               |

# SMD LED Direct Mount Module

## HALO

The HALO Surface Mount LED Downlight (SMD-DM) is a low profile surface luminaire with a larger look and high performance. SMD-DM (Direct Mount with spring clips) is designed for new installation into drywall, without any additional housing or junction box needed. Suitable for residential or commercial installations. Ideal for general areas, closets, storage areas, attics and basements.



SMD4R6930VHDM



SMD6R6930VHDM



| Catalog Number | Product Description | Finish | Replaces Up To | CCT   | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|---------------------|--------|----------------|-------|---------|--------|-------|-----------------|--------------|-----------------------|
| SMD4R6930VHDM  | 4" RD Surface       | White  | 65W INC        | 3000K | 120V    | 700    | 10    | 240             | 080083766390 | 2281593               |
| SMD6R6930VHDM  | 6" RD Surface       | White  | 65W INC        | 3000K | 120V    | 750    | 10    | 240             | 080083767090 | 2281592               |

## Direct Mount Product Selection Guide



|             |                           | SMD-DM | RL-DM | HLB |
|-------------|---------------------------|--------|-------|-----|
| APPLICATION | Ultra-shallow Lens        | ✓      |       | ✓   |
|             | General Area Illumination | ✓      | ✓     | ✓   |
|             | Wet Location              | ✓      | ✓     | ✓   |
|             | New Construction          | ✓      | ✓     | ✓   |
|             | Remodel                   | ✓      | ✓     | ✓   |

|                        |                  |                       |             |                       |
|------------------------|------------------|-----------------------|-------------|-----------------------|
| FEATURES / PERFORMANCE | Size / Shape     | 4 & 6" Round & Square | 6" Round    | 4 & 6" Round & Square |
|                        | Lumens (Max)     | 800                   | 600         | 1000                  |
|                        | Life (L70B50)    | 50K hours             | 50K hours   | 50K hours             |
|                        | CRI              | 90 (min)              | 90 (min)    | 90 (min)              |
|                        | CCT (K)          | 27/30/35/40/50        | 27/30/35/40 | 27/30/35/40/50        |
|                        | Spacing Criteria | 1.4                   | 1.2         | 1.4                   |
|                        | Input Voltage    | 120                   | 120         | 120                   |

|         |                      |   |   |   |
|---------|----------------------|---|---|---|
| CONTROL | Field Select (5) CCT |   | ✓ | ✓ |
|         | LE/TE Phase Cut      | ✓ | ✓ | ✓ |

Visit [eaton.com/MarketPro](http://eaton.com/MarketPro) to download this guide.

# RL LED Baffle Trim Downlight

## HALO

The HALO RL Series is a complete LED baffle-trim module for 4-inch or 5/6-inch aperture recessed downlights. Ideal for new construction, remodel and retrofit installation, the integral LED driver offers 120V dimming capability and the lens provides uniform illumination and a wet location listing. The modules are available in a choice of 2700K or 3000K or choose the baffle-trim modules with CCT selectable technology that allows the user to choose from a range of five color temperatures from 2700K to 5000K via a switch.



| Catalog Number | Product Description       | Finish | Replaces Up To | CCT                    | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID     |
|----------------|---------------------------|--------|----------------|------------------------|---------|--------|-------|-----------------|--------------|---------------------------|
| RL4069S1EWH    | 4" Retrofit Baffle-Trim   | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 621    | 9     | 300             | 080083816712 | 2326218                   |
| RL4099S1EWH    | 4" Retrofit Baffle-Trim   | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 1006   | 12    | 504             | 080083816736 | 2321466                   |
| RL56069S1EWH   | 5/6" Retrofit Baffle-Trim | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 712    | 8     | 240             | 080083816750 | 2326217                   |
| RL56099S1EWH   | 5/6" Retrofit Baffle-Trim | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 1,006  | 12    | 240             | 080083818679 | 2326219                   |
| RL56129S1EWH   | 5/6" Retrofit Baffle-Trim | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 1,272  | 14    | 240             | 080083818693 | 2321465                   |
| RL460WH927PK   | 4" Retrofit Baffle-Trim   | White  | 60W INC        | 2700K                  | 120V    | 530    | 8     | 630             | 080083699445 | 2286441, 2286440          |
| RL460WH930PK   | 4" Retrofit Baffle-Trim   | White  | 60W INC        | 3000K                  | 120V    | 570    | 8     | 1,008           | 080083690770 | 2286445, 2286444          |
| RL560WH6927    | 5/6" Retrofit Baffle-Trim | White  | 65W INC        | 2700K                  | 120V    | 633    | 10    | 288             | 080083699384 | 2269156, 2286436, 2286422 |
| RL560WH6930    | 5/6" Retrofit Baffle-Trim | White  | 65W INC        | 3000K                  | 120V    | 610    | 8     | 288             | 080083690602 | 2269160, 2286425, 2286424 |

# RLD LED Deep Baffle Downlight

## HALO

The RLD Deep Baffle series is a complete LED baffle-trim module for 4-inch (RLD4) or 6-inch (RLD6) aperture recessed downlights suitable for new construction, remodel and retrofit installation. The regressed lens provides uniform illumination and 50° optical cutoff. The Deep Baffle comes standard with both white and black Coilex baffle included and is wet location. Precision construction makes any housing airtight for added savings and code compliance.



| Catalog Number | Product Description          | Finish | Replaces Up To | CCT   | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|------------------------------|--------|----------------|-------|---------|--------|-------|-----------------|--------------|-----------------------|
| RLD4069301EWH  | 4" Retrofit Deep Baffle-Trim | White  | 40W INC        | 3000K | 120V    | 681    | 9     | 420             | 080083823604 | 2320421               |
| RLD6069301EWH  | 6" Retrofit Deep Baffle-Trim | White  | 40W INC        | 3000K | 120V    | 668    | 9     | 120             | 080083823642 | 2320420               |

# RSQ All-Purpose Square LED Downlights

## HALO

The RSQ all-purpose square lens LED modules are available in three sizes for use in HALO or compatible 4, 5 or 6-inch recessed housings. Designed for both new construction or to update an existing installation, the wide distribution patterns work well in low to high ceilings, providing general area illumination. The regressed flat lens with step baffle provides visual comfort and glare control.



RSQ4089301EMWWB



RSQ5089301EMWWB



RSQ6089301EMWWB



| Catalog Number  | Product Description            | Finish        | Replaces Up To | CCT   | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|-----------------|--------------------------------|---------------|----------------|-------|---------|--------|-------|-----------------|--------------|-----------------------|
| RSQ4089271EMWWB | 4" Retrofit Square Baffle-trim | White         | 60W INC        | 2700K | 120V    | 807    | 9     | 672             | 080083824410 | 2323426               |
| RSQ4089301EMWWB | 4" Retrofit Square Baffle-trim | White         | 60W INC        | 3000K | 120V    | 814    | 9     | 672             | 080083824434 | 2323427               |
| RSQ4089351EMWWB | 4" Retrofit Square Baffle-trim | White         | 60W INC        | 3500K | 120V    | 825    | 9     | 672             | 080083824458 | 2323428               |
| RSQ4089401EMWWB | 4" Retrofit Square Baffle-trim | White         | 60W INC        | 4000K | 120V    | 835    | 9     | 672             | 080083824472 | 2323429               |
| RSQ5089271EMWWB | 5" Retrofit Square Baffle-trim | White         | 60W INC        | 2700K | 120V    | 813    | 9     | 360             | 080083824519 | 2323485               |
| RSQ5089301EMWWB | 5" Retrofit Square Baffle-trim | White         | 60W INC        | 3000K | 120V    | 837    | 9     | 360             | 080083824533 | 2323486               |
| RSQ5089351EMWWB | 5" Retrofit Square Baffle-trim | White         | 60W INC        | 3500K | 120V    | 828    | 9     | 360             | 080083824557 | 2323487               |
| RSQ5089401EMWWB | 5" Retrofit Square Baffle-trim | White         | 60W INC        | 4000K | 120V    | 840    | 9     | 360             | 080083824571 | 2323488               |
| RSQ6089271EMWWB | 6" Retrofit Square Baffle-trim | White         | 60W INC        | 2700K | 120V    | 835    | 9     | 240             | 080083824618 | 2323481               |
| RSQ6089301EMWWB | 6" Retrofit Square Baffle-trim | White         | 60W INC        | 3000K | 120V    | 844    | 9     | 240             | 080083824632 | 2323482               |
| RSQ6089351EMWWB | 6" Retrofit Square Baffle-trim | White         | 60W INC        | 3500K | 120V    | 835    | 9     | 240             | 080083824656 | 2323483               |
| RSQ6089401EMWWB | 6" Retrofit Square Baffle-trim | White         | 60W INC        | 4000K | 120V    | 845    | 9     | 240             | 080083824670 | 2323484               |
| RSQ4TRMMW       | 4" Splay trim                  | Paintable     |                |       |         |        |       | 3780            | 080083840984 |                       |
| RSQ4TRMSNB      | 4" Baffle MW, trim             | Satin Nickel  |                |       |         |        |       | 3780            | 080083841004 |                       |
| RSQ4TRMTBZB     | 4" Baffle trim                 | Tuscan Bronze |                |       |         |        |       | 3780            | 080083841028 |                       |
| RSQ5TRMMW       | 5" Splay trim                  | Paintable     |                |       |         |        |       | 2520            | 080083841042 |                       |
| RSQ5TRMSNB      | 5" Baffle MW, trim             | Satin Nickel  |                |       |         |        |       | 2520            | 080083841066 |                       |
| RSQ5TRMTBZB     | 5" Baffle trim                 | Tuscan Bronze |                |       |         |        |       | 2520            | 080083841080 |                       |
| RSQ6TRMMW       | 6" Splay trim                  | Paintable     |                |       |         |        |       | 1800            | 080083841103 |                       |
| RSQ6TRMSNB      | 6" Baffle MW, trim             | Satin Nickel  |                |       |         |        |       | 1800            | 080083841127 |                       |
| RSQ6TRMTBZB     | 6" Baffle trim                 | Tuscan Bronze |                |       |         |        |       | 1800            | 080083841141 |                       |

# LT LED Retrofit Baffle Trim Downlight

## HALO

The LT Series combines the energy savings, long life and sustainability of LED in an easy-to-install retrofit baffle trim kit. The modules are available in 4-inch and 5/6-inch sizes and supplied with torsion springs or friction blades to secure the trim tight to ceiling. The diffuse lens provides shielding to the source and a wet location listing; suitable for use in showers or in outdoor covered ceiling applications. The series is ideal for new construction or remodel applications.



LT460WH6927



LT560WH6927

| Catalog Number | Product Description       | Finish | Replaces Up To | CCT   | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|---------------------------|--------|----------------|-------|---------|--------|-------|-----------------|--------------|-----------------------|
| LT460WH6927    | 4" Retrofit Baffle-Trim   | White  | 60W INC        | 2700K | 120V    | 544    | 8     | 420             | 080083762033 | 2277226               |
| LT460WH6930    | 4" Retrofit Baffle-Trim   | White  | 60W INC        | 3000K | 120V    | 554    | 8     | 504             | 080083742394 | 2257770, 2277227      |
| LT560WH6927    | 5/6" Retrofit Baffle-Trim | White  | 60W INC        | 2700K | 120V    | 700    | 10    | 288             | 080083762897 | 2277231               |
| LT560WH6930    | 5/6" Retrofit Baffle-Trim | White  | 60W INC        | 3000K | 120V    | 683    | 10    | 240             | 080083742417 | 2252183, 2277232      |
| LT560WH6935    | 5/6" Retrofit Baffle-Trim | White  | 60W INC        | 3500K | 120V    | 697    | 10    | 288             | 080083762910 | 2277233               |
| LT560WH6940    | 5/6" Retrofit Baffle-Trim | White  | 60W INC        | 4000K | 120V    | 737    | 10    | 288             | 080083762934 | 2277234               |
| LT560WH12927   | 5/6" Retrofit Baffle-Trim | White  | 90W INC        | 2700K | 120V    | 1,100  | 12    | 240             | 080083798667 |                       |
| LT560WH12930   | 5/6" Retrofit Baffle-Trim | White  | 90W INC        | 3000K | 120V    | 1,140  | 12    | 240             | 080083798681 |                       |

# SLD LED Surface Mount Module

## HALO

The HALO Surface LED Downlight (SLD) incorporates WaveStream™ technology to create an ultra-low profile surface-mounting luminaire with the performance and look of a traditional downlight. Available in 4-inch and 6-inch sizes, the SLD is designed for installation in many standard and fire-rated junction boxes. A supply wire adapter with LED quick wiring connector is included. Suitable for residential or commercial installations, the SLD is ideal for closets, storage areas, attics and basements.



SLD405830WH



SLD606830WH

| Catalog Number | Product Description         | Finish | Replaces Up To | CCT   | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|-----------------------------|--------|----------------|-------|---------|--------|-------|-----------------|--------------|-----------------------|
| SLD405830WH*   | 4" Surface Downlight        | White  | 60W INC        | 3000K | 120V    | 750    | 12    | 540             | 080083697564 | 2275534               |
| SLD405830WHJB  | 4" Surface Downlight, J-Box | White  | 60W INC        | 3000K | 120V    | 750    | 12    | 540             | 080083705979 | 2275534               |
| SLD606830WH*   | 6" Surface Downlight        | White  | 65W INC        | 3000K | 120V    | 760    | 12    | 300             | 080083697588 | 2271848               |
| SLD606830WHJB  | 6" Surface Downlight, J-Box | White  | 65W INC        | 3000K | 120V    | 760    | 12    | 300             | 080083705993 | 2271848               |
| SLD606930WH*   | 6" Surface Downlight        | White  | 65W INC        | 3000K | 120V    | 735    | 13    | 300             | 080083697625 | 2271068               |
| SLD606930WHJB  | 6" Surface Downlight, J-Box | White  | 65W INC        | 3000K | 120V    | 735    | 13    | 300             | 080083706037 | 2271068               |

\*Not for sale in California. For California, apply "CA" to the model number (i.e. SLD405830WH-CA)

# SMD LED Surface Mount Module

## HALO

The Surface Mount LED Downlight (SMD) is a low-profile, surface-mounting luminaire with a modern look that provides high performance. The SMD is designed for installation with many square, octagon, or round junction boxes and a supply wire adapter with LED quick wiring connector is included. The SMD-DM model is designed for new installation into drywall, without the need for a housing or junction box.



SMD4R6930WH



SMD6R12927WH



SMD6S12927WH



| Catalog Number | Product Description | Finish | Replaces Up To | CCT   | Voltage  | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|---------------------|--------|----------------|-------|----------|--------|-------|-----------------|--------------|-----------------------|
| SMD4R6930WH    | 4" RD Surface Mount | White  | 60W INC        | 3000K | 120V     | 700    | 10    | 504             | 080083766352 | 2281593               |
| SMD6R6930WH    | 6" RD Surface Mount | White  | 65W INC        | 3000K | 120V     | 758    | 10    | 300             | 080083767052 | 2281592               |
| SMD6R12927WH   | 6" RD Surface Mount | White  | 80W INC        | 2700K | 120V     | 1,244  | 16    | 360             | 080083825400 | 2308976               |
| SMD6R12927WHE  | 6" RD Surface Mount | White  | 80W INC        | 2700K | 120-277V | 1,210  | 15    | 450             | 080083817603 | 2322244               |
| SMD6R12930WH   | 6" RD Surface Mount | White  | 80W INC        | 3000K | 120V     | 1,242  | 15    | 360             | 080083825424 | 2308976               |
| SMD6R12930WHE  | 6" RD Surface Mount | White  | 80W INC        | 3000K | 120-277V | 1,203  | 15    | 450             | 080083817627 | 2322245               |
| SMD6R12935WH   | 6" RD Surface Mount | White  | 80W INC        | 3500K | 120V     | 1,264  | 15    | 360             | 080083825448 | 2308976               |
| SMD6R12935WHE  | 6" RD Surface Mount | White  | 80W INC        | 3500K | 120-277V | 1,200  | 15    | 450             | 080083817641 | 2322246               |
| SMD6R12940WH   | 6" RD Surface Mount | White  | 80W INC        | 4000K | 120V     | 1,223  | 15    | 360             | 080083825462 | 2308976               |
| SMD6R12940WHE  | 6" RD Surface Mount | White  | 80W INC        | 4000K | 120-277V | 1,260  | 15    | 450             | 080083817665 | 2322247               |
| SMD6R12950WH   | 6" RD Surface Mount | White  | 80W INC        | 5000K | 120V     | 1,252  | 15    | 360             | 080083825486 | 2308976               |
| SMD6R12950WHE  | 6" RD Surface Mount | White  | 80W INC        | 5000K | 120-277V | 1,200  | 15    | 450             | 080083817689 | 2322248               |
| SMD6S12927WH   | 6" RD Surface Mount | White  | 76W INC        | 2700K | 120V     | 1,190  | 16    | 360             | 080083825509 | 2308976               |
| SMD6S12927WHE  | 6" RD Surface Mount | White  | 76W INC        | 2700K | 120-277V | 1,167  | 16    | 450             | 080083817702 | 2322250               |
| SMD6S12930WH   | 6" RD Surface Mount | White  | 76W INC        | 3000K | 120V     | 1,180  | 16    | 360             | 080083825523 | 2308976               |
| SMD6S12930WHE  | 6" RD Surface Mount | White  | 76W INC        | 3000K | 120-277V | 1,135  | 16    | 450             | 080083817726 | 2322251               |
| SMD6S12935WH   | 6" RD Surface Mount | White  | 80W INC        | 3500K | 120V     | 1,237  | 16    | 360             | 080083825547 | 2308976               |
| SMD6S12935WHE  | 6" RD Surface Mount | White  | 76W INC        | 3500K | 120-277V | 1,140  | 16    | 450             | 080083817740 | 2322252               |
| SMD6S12940WH   | 6" RD Surface Mount | White  | 80W INC        | 4000K | 120V     | 1,215  | 16    | 360             | 080083825561 | 2308976               |
| SMD6S12940WHE  | 6" RD Surface Mount | White  | 76W INC        | 4000K | 120-277V | 1,155  | 16    | 450             | 080083817764 | 2322253               |
| SMD6S12950WH   | 6" RD Surface Mount | White  | 80W INC        | 5000K | 120V     | 1,235  | 16    | 360             | 080083825585 | 2308976               |
| SMD6S12950WHE  | 6" RD Surface Mount | White  | 76W INC        | 5000K | 120-277V | 1,180  | 16    | 450             | 080083817788 | 2322254               |

# BLD LED Surface Mount Module

## HALO

The Backlit downlight is a low-profile, high-performance surface mount luminaire that offers the added flexibility of seleCCTable color temperatures at time of installation. BLD4 (4-inch) and BLD6 (6-inch) are designed for installation in many 3-1/2-inch and 4-inch square, octagon, or round junction boxes. The BLD4/BLD6 may also retrofit in 4-inch, 5-inch and 6-inch aperture IC and Non-IC recessed housings. The user can choose from a range of five color temperatures from 2700K to 5000K via a switch.



BLD406930WH



BLD606930WH

| Catalog Number | Product Description         | Finish | Replaces Up To | CCT                    | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|-----------------------------|--------|----------------|------------------------|---------|--------|-------|-----------------|--------------|-----------------------|
| BLD406930WH    | 4" RD Surface, Direct Mount | White  | 65W INC        | 3000K                  | 120V    | 690    | 8     | 648             | 080083826667 | 2319363               |
| BLD4089SWH     | 4" RD Surface, Direct Mount | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 802    | 10    | 432             | 080083826681 | 2319361               |
| BLD606930WH    | 6" RD Surface, Direct Mount | White  | 65W INC        | 3000K                  | 120V    | 700    | 8     | 450             | 080083826704 | 2319362               |
| BLD6089SWH     | 6" RD Surface, Direct Mount | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 812    | 10    | 300             | 080083826728 | 2319364               |

# RA LED Adjustable Gimbal

## HALO

The RA LED is a complete adjustable gimbal LED module for 4-inch and 5/6-inch aperture recessed downlights; suitable for new construction, remodel and retrofit installation. The RA adjustable gimbal offers 35° tilt and up to 360° rotation and is compatible with Leading Edge and Trailing Edge phase control dimmers. The modules are offered in Very Wide Flood (VWFL) and Narrow Flood (NFL) models. The modules are available in a choice of 2700K or 3000K or choose the gimbal with CCT selectable technology that allows the user to choose from a range of five color temperatures from 2700K to 5000K via a switch.



RA406927WH



RA5606927WH

| Catalog Number | Product Description            | Finish | Replaces Up To | CCT                    | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|--------------------------------|--------|----------------|------------------------|---------|--------|-------|-----------------|--------------|-----------------------|
| RA4069S1EWH    | 4" Retrofit Adjustable, Wide   | White  | 65W INC        | 2700K-5000K            | 120V    | 615    | 7     | 504             | 080083817887 | 2319905               |
| RA406927WH     | 4" Retrofit Adjustable, Wide   | White  | 65W INC        | 2700K                  | 120V    | 600    | 10    | 384             | 080083693184 | 2284607, 2319592      |
| RA406930WH     | 4" Retrofit Adjustable, Wide   | White  | 65W INC        | 3000K                  | 120V    | 615    | 10    | 288             | 080083693207 | 2281535, 2319593      |
| RA406930NFLWH  | 4" Retrofit Adjustable, Narrow | White  | 65W INC        | 3000K                  | 120V    | 640    | 10    | 384             | 080083693283 | 2319591               |
| RA56069S1EWH   | 5/6" Retrofit Adjustable, Wide | White  | 65W INC        | Selectable 2700K-5000K | 120V    | 630    | 7     | 270             | 080083817900 | 2319904               |
| RA5606927WH    | 5/6" Retrofit Adjustable, Wide | White  | 65W INC        | 2700K                  | 120V    | 645    | 10    | 240             | 080083693221 | 2272165, 2319596      |
| RA5606930WH    | 5/6" Retrofit Adjustable, Wide | White  | 65W INC        | 3000K                  | 120V    | 670    | 10    | 240             | 080083693245 | 2271987, 2319597      |
| RA5606930NFLWH | 5/6" Retrofit Adjustable, Wide | White  | 65W INC        | 2700K                  | 120V    | 645    | 10    | 192             | 080083693320 | 2272166, 2319595      |

# LA LED Adjustable Gimbal

## HALO

The HALO LA LED Adjustable Downlight series is an adjustable LED module for 4-inch and 5/6-inch aperture recessed downlights. The LA gimbals feature adjustment of 35° tilt and up to 360° rotation. The lens provides uniform illumination and wet location listing and precision construction makes any housing AIR-TITE for added savings and code compliance. The series is offered in five color temperatures and 90 CRI.



LA56069271EWH



LA56069271EWH



| Catalog Number | Product Description                     | Finish | Replaces Up To | CCT   | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|-----------------------------------------|--------|----------------|-------|---------|--------|-------|-----------------|--------------|-----------------------|
| LA4069271EWH   | 4" Retrofit Adjustable, Plastic, Wide   | White  | 40W INC        | 2700K | 120V    | 611    | 9     | 576             | 080083818129 | 2325615               |
| LA4069301EWH   | 4" Retrofit Adjustable, Plastic, Wide   | White  | 40W INC        | 3000K | 120V    | 613    | 9     | 576             | 080083818143 | 2325616               |
| LA4069351EWH   | 4" Retrofit Adjustable, Plastic, Wide   | White  | 40W INC        | 3500K | 120V    | 630    | 9     | 576             | 080083818167 | 2325617               |
| LA4069401EWH   | 4" Retrofit Adjustable, Plastic, Wide   | White  | 40W INC        | 4000K | 120V    | 640    | 9     | 576             | 080083818181 | 2325618               |
| LA4069501EWH   | 4" Retrofit Adjustable, Plastic, Wide   | White  | 40W INC        | 5000K | 120V    | 630    | 9     | 576             | 080083818204 | 2325619               |
| LA56069271EWH  | 5/6" Retrofit Adjustable, Plastic, Wide | White  | 40W INC        | 2700K | 120V    | 614    | 9     | 270             | 080083818228 | 2325605               |
| LA56069301EWH  | 5/6" Retrofit Adjustable, Plastic, Wide | White  | 40W INC        | 3000K | 120V    | 637    | 9     | 270             | 080083818242 | 2325606               |
| LA56069351EWH  | 5/6" Retrofit Adjustable, Plastic, Wide | White  | 40W INC        | 3500K | 120V    | 640    | 9     | 270             | 080083818266 | 2325607               |
| LA56069401EWH  | 5/6" Retrofit Adjustable, Plastic, Wide | White  | 40W INC        | 4000K | 120V    | 640    | 9     | 270             | 080083818280 | 2325608               |
| LA56069501EWH  | 5/6" Retrofit Adjustable, Plastic, Wide | White  | 40W INC        | 5000K | 120V    | 630    | 9     | 270             | 080083818303 | 2325609               |

# HU10 LED Undercabinet

## HALO

The HU10 undercabinet low-profile design delivers maximum energy savings and life with easy installation. The integrated driver allowing 120V direct to the fixture for easy installation. Available in multiple lengths, the HALO system can be configured to fit almost anywhere. Smooth dimming down to 5% using a standard dimmer and connector cables in a variety of different lengths make it easy to link one unit to another. Each unit has an integrated on-off switch.



HU1018D930PR



HU1018D930MBR



| Catalog Number | Product Description               | Finish | Length | Replaces Up To | CCT   | Voltage | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|-----------------------------------|--------|--------|----------------|-------|---------|--------|-------|-----------------|--------------|-----------------------|
| HU1009D930MBR  | Dimming, Cord/Plug or Direct Wire | Black  | 9"     | 17W INC        | 3000K | 120V    | 248    | 4     | 576             | 080083748310 | 2271988               |
| HU1009D930PR   | Dimming, Cord/Plug or Direct Wire | White  | 9"     | 17W INC        | 3000K | 120V    | 248    | 4     | 576             | 080083747436 | 2271988               |
| HU1018D930PR   | Dimming, Cord/Plug or Direct Wire | White  | 18"    | 33W INC        | 3000K | 120V    | 495    | 7     | 336             | 080083747450 | 2272162               |
| HU1018D930MBR  | Dimming, Cord/Plug or Direct Wire | Black  | 18"    | 33W INC        | 3000K | 120V    | 495    | 7     | 336             | 080083748334 | 2272162               |
| HU1024D930MBR  | Dimming, Cord/Plug or Direct Wire | Black  | 24"    | 44W INC        | 3000K | 120V    | 660    | 7     | 224             | 080083748358 | 2289580               |
| HU1024D930PR   | Dimming, Cord/Plug or Direct Wire | White  | 24"    | 44W INC        | 3000K | 120V    | 660    | 7     | 224             | 080083748280 | 2289580               |

# HU30 LED Undercabinet

## HALO

The HU30 undercabinet maintains HALO's signature low-profile design and offers users selectable color temperature options (2700K, 3000K, 3500K and 4000K) via a switch. The integrated driver allows operation at 120V and 277V with various back and side wiring options. Available in multiple lengths, the HALO system can be configured to fit almost any space. With a motion sensor or USB port as standard options, customers can maximize utility and efficiency from their undercabinet fixture.



HU30BSC18P



HU30ADV18MB

Recessed

HALO Recessed Downlighting

| Catalog Number | Product Description                 | Finish | Length | Replaces Up To | Selectable CCT | Voltage  | Lumens | Watts | Pallet Quantity | UPC          | ENERGY STAR Unique ID |
|----------------|-------------------------------------|--------|--------|----------------|----------------|----------|--------|-------|-----------------|--------------|-----------------------|
| HU30SCT09P     | Low Profile, Dimming                | White  | 9"     | 15W INC        | 2700K-4000K    | 120-277V | 222    | 4     | 1008            | 080083797868 | 2308975               |
| HU30SCT09MB    | Low Profile, Dimming                | Black  | 9"     | 15W INC        | 2700K-4000K    | 120-277V | 222    | 4     | 1008            | 080083797882 | 2308975               |
| HU30BSC18P     | Low Profile, Dimming, USB Port      | White  | 18"    | 29W INC        | 2700K-4000K    | 120-277V | 440    | 8     | 648             | 080083797905 |                       |
| HU30BSC18MB    | Low Profile, Dimming, USB Port      | Black  | 18"    | 29W INC        | 2700K-4000K    | 120-277V | 440    | 8     | 648             | 080083797943 |                       |
| HU30ADV18P     | Low Profile, Dimming, Motion Sensor | White  | 18"    | 29W INC        | 2700K-4000K    | 120-277V | 440    | 8     | 648             | 080083797929 | 2310291               |
| HU30ADV18MB    | Low Profile, Dimming, Motion Sensor | Black  | 18"    | 29W INC        | 2700K-4000K    | 120-277V | 440    | 8     | 648             | 080083797967 | 2310291               |
| HU30ADV24P     | Low Profile, Dimming, USB Port      | White  | 24"    | 42W INC        | 2700K-4000K    | 120-277V | 627    | 11    | 648             | 080083798001 | 2310169               |
| HU30ADV24MB    | Low Profile, Dimming, USB Port      | Black  | 24"    | 42W INC        | 2700K-4000K    | 120-277V | 627    | 11    | 648             | 080083798049 | 2310169               |
| HU30BSC24P     | Low Profile, Dimming, Motion Sensor | White  | 24"    | 42W INC        | 2700K-4000K    | 120-277V | 627    | 11    | 648             | 080083797981 |                       |
| HU30BSC24MB    | Low Profile, Dimming, Motion Sensor | Black  | 24"    | 42W INC        | 2700K-4000K    | 120-277V | 627    | 11    | 648             | 080083798025 |                       |
| HU30BSC36P     | Low Profile, Dimming, USB Port      | White  | 36"    | 56W INC        | 2700K-4000K    | 120-277V | 844    | 14    | 272             | 080083798063 |                       |
| HU30BSC36MB    | Low Profile, Dimming, USB Port      | Black  | 36"    | 56W INC        | 2700K-4000K    | 120-277V | 844    | 14    | 272             | 080083798100 |                       |
| HU30ADV36P     | Low Profile, Dimming, Motion Sensor | White  | 36"    | 56W INC        | 2700K-4000K    | 120-277V | 844    | 14    | 272             | 080083798087 | 2310168               |
| HU30ADV36MB    | Low Profile, Dimming, Motion Sensor | Black  | 36"    | 56W INC        | 2700K-4000K    | 120-277V | 844    | 14    | 272             | 080083798124 | 2310168               |
| HU30BSC48P     | Low Profile, Dimming, USB Port      | White  | 48"    | 84W INC        | 2700K-4000K    | 120-277V | 1,253  | 21    | 272             | 080083798148 |                       |
| HU30BSC48MB    | Low Profile, Dimming, USB Port      | Black  | 48"    | 84W INC        | 2700K-4000K    | 120-277V | 1,253  | 21    | 272             | 080083798186 |                       |
| HU30ADV48P     | Low Profile, Dimming, Motion Sensor | White  | 48"    | 84W INC        | 2700K-4000K    | 120-277V | 1,253  | 21    | 272             | 080083798162 | 2310292               |
| HU30ADV48MB    | Low Profile, Dimming, Motion Sensor | Black  | 48"    | 84W INC        | 2700K-4000K    | 120-277V | 1,253  | 21    | 272             | 080083798209 | 2310292               |

# E Series Housings

## HALO

The E Series is a compact and efficient recessed housing family optimized and listed for EISA compliant tungsten-Halogen lamps, as well as INC, CFL and LED lamps. The housings are suitable for new or retrofit residential or light commercial construction. The housings are designed for installation in insulated ceilings or non-insulated ceilings with airtight code compliant construction and can be used with a variety of trims and finishes to create different lighting effects or to match any decor. The family includes ultra-shallow housings for application with limited plenum space.



E27ICAT



E27RICAT



| Catalog Number | Product Description                                    | Socket                    | Lamp Source*         | Voltage  | Pallet Quantity | UPC          |
|----------------|--------------------------------------------------------|---------------------------|----------------------|----------|-----------------|--------------|
| E27ICAT        | 6", IC, Shallow, New Construction                      | E26                       | HAL., INC., LED, CFL | 120V     | 192             | 080083737604 |
| E27RICAT       | 6", IC, Shallow, Remodel                               | E26                       | HAL., INC., LED, CFL | 120V     | 192             | 080083737482 |
| E4ICATSB       | 4", IC, Shallow, New Construction                      | E26                       | HAL., INC., LED, CFL | 120V     | 108             | 080083751525 |
| E4RTATSB       | 4" NON-IC Air-Tite, Remodel, w/Socket Bracket          | E26                       | HAL., INC., LED, CFL | 120V     | 168             | 080083751501 |
| E4TATSB        | 4" NON-IC, Air-Tite, New Construction w/Socket Bracket | E26                       | HAL., INC., LED, CFL | 120V     | 168             | 080083751488 |
| E5ICAT         | 5" IC, Air-Tite, New Construction                      | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 080083737420 |
| E5ICATNB       | 5" IC, Air-Tite, New Construction, No Socket Bracket   | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 080083737390 |
| E5RICAT        | 5" IC, Air-Tite, Remodel                               | E26                       | HAL., INC., LED, CFL | 120V     | 180             | 080083737307 |
| E750ICAT       | 6" IC, Air-Tite, LED New Construction                  | Quick Connect (No Socket) | LED Modules          | 120-277V | 144             | 080083775040 |
| E750RICAT      | 6" IC, Air-Tite, LED Remodel                           | Quick Connect (No Socket) | LED Modules          | 120-277V | 144             | 080083778584 |
| E7ICAT         | 6" IC, Air-Tite, New Construction Housing              | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 080083737727 |
| E7ICATNB       | 6" IC, AIRTITE, New Construction, No Socket Bracket    | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 080083737697 |
| E7RICAT        | 6" IC, Air-Tite, Remodel                               | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 080083737543 |

Note: Lamps not included.

## 4", 5" and 6" Trims

### HALO

Baffle, Gimbal, Coilex, Splay, Cone, Slope and Open Socket baffle trims are an ideal solution to shape light to minimize aperture glare and reduce ceiling brightness. Open trims focus the downlighting beam to provide uniform distribution. The trims can be used in new construction and remodel housings. The lensed shower trims are wet location listed.



| Catalog Number | Product Description                            | Finish | Lamp Source*           | Pallet Quantity | UPC          |
|----------------|------------------------------------------------|--------|------------------------|-----------------|--------------|
| 4001WB         | 4" Step Baffle - Plastic                       | White  | Halogen, INC, LED, CFL | 960             | 080083745869 |
| 993W           | 4" Coilex Baffle                               | White  | Halogen, INC, LED, CFL | 840             | 080083628483 |
| 5001P          | 5" Metal Splay Baffle                          | White  | Halogen, INC, LED, CFL | 360             | 662400602729 |
| 5125WB         | 5" Full Cone Baffle                            | White  | Halogen, INC, LED, CFL | 288             | 080083743162 |
| 300P           | 6" Open - Socket Supporting                    | White  | Halogen, INC, LED, CFL | 450             | 662400302421 |
| 30WAT          | 6" Air-Tite Baffle                             | White  | Halogen, INC, LED, CFL | 540             | 662400603320 |
| 310W           | 6" Coilex Baffle                               | White  | Halogen, INC, LED, CFL | 540             | 080083515882 |
| 456W           | 6" Baffle for Slope Ceiling                    | White  | Halogen, INC, LED, CFL | 360             | 662400676287 |
| 6100WB         | 6" Tapered Metal Baffle, 2-Rings Narrow & Wide | White  | Halogen, INC, LED, CFL | 1,080           | 080083743452 |
| 6125WB         | 6" Full Cone Baffle                            | White  | Halogen, INC, LED, CFL | 432             | 080083742912 |

Note: Lamps not included.

# H Series Housings

## HALO

The H Series is the standard in the industry for both commercial and residential applications. Optimized and listed for EISA compliant tungsten-Halogen lamps, as well as Incandescent, CFL and LED lamps. For installation in insulated ceilings and non-insulated ceilings with airtight code compliant construction. Use with a variety of trims and finishes to create different lighting effects or to match any decor. The wide variety of trims available allows a number of different lighting effects to be created.



H271CAT



H271CAT


| Catalog Number | Product Description                                 | Socket                    | Lamp Source*         | Voltage  | Pallet Quantity | UPC          |
|----------------|-----------------------------------------------------|---------------------------|----------------------|----------|-----------------|--------------|
| H1499ICAT      | 4" IC Air-Tite, 12V Low Voltage                     | GU5.3                     | HAL., INC., LED, CFL | 120V     | 40              | 080083584079 |
| H245ICAT       | 4" New Construction Ultra Shallow                   | Quick Connect (No Socket) | LED Modules          | 120/277V | 180             | 080083770717 |
| H245RICAT      | 4" Remodel Ultra Shallow                            | Quick Connect (No Socket) | LED Modules          | 120-277V | 540             | 080083756520 |
| H2750ICAT      | 6" New Construction, Shallow, IC Air-Tite           | Quick Connect (No Socket) | LED Modules          | 120/277V | 144             | 080083618163 |
| H271CAT        | 6" New Construction, Shallow Ceiling, IC Air-Tite   | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 662400605898 |
| H271RICAT      | 6" Remodel, Shallow Ceiling, IC Air-Tite            | E26                       | HAL., INC., LED, CFL | 120V     | 180             | 080083609253 |
| H550ICAT       | 5" New Construction, IC Air-Tite                    | Quick Connect (No Socket) | LED Modules          | 120/277V | 120             | 080083626533 |
| H550RICAT      | 5" Remodel, IC Air-Tite                             | Quick Connect (No Socket) | LED Modules          | 120/277V | 144             | 080083626557 |
| H51CAT         | 5" New Construction, IC Air-Tite                    | E26                       | HAL., INC., LED, CFL | 120V     | 120             | 080083609413 |
| H51CATNB       | 5" New Construction, IC Air-Tite, No Socket Bracket | E26                       | HAL., INC., LED, CFL | 120V     | 120             | 080083756063 |
| H51RICAT       | 5" Remodel, IC Air-Tite                             | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 080083609444 |
| H750ICAT       | 6" New Construction, IC Air-Tite                    | Quick Connect (No Socket) | LED Modules          | 120/277V | 120             | 623961872655 |
| H750RICAT      | 6" Remodel, IC Air-Tite                             | Quick Connect (No Socket) | LED Modules          | 120/277V | 144             | 623961052248 |
| H71CAT         | 6" New Construction, IC Air-Tite                    | E26                       | HAL., INC., LED, CFL | 120V     | 120             | 080083609628 |
| H71CATNB       | 6" New Construction, IC Air-Tite, No Socket Bracket | E26                       | HAL., INC., LED, CFL | 120V     | 120             | 662400612032 |
| H71CT          | 6" New Construction, IC                             | E26                       | HAL., INC., LED, CFL | 120V     | 120             | 080083609680 |
| H71CTNB        | 6" New Construction, IC, No Socket Bracket          | E26                       | HAL., INC., LED, CFL | 120V     | 120             | 662400608523 |
| H71RICAT       | 6" Remodel, IC Air-Tite                             | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 662400610588 |
| H71RICT        | 6" Remodel, IC                                      | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 662400600718 |
| H995ICAT       | 4" New Construction, IC Air-Tite, Shallow           | Quick Connect (No Socket) | LED Modules          | 120/277V | 144             | 080083616930 |
| H995RICAT      | 4" Remodel, IC Air-Tite, Shallow                    | Quick Connect (No Socket) | LED Modules          | 120/277V | 162             | 080083616947 |
| H991CAT        | 4" New Construction, IC Air-Tite, Shallow           | E26                       | HAL., INC., LED, CFL | 120V     | 144             | 080083582259 |
| H99RTAT        | 4" Remodel, Non-IC, Air-Tite, Shallow               | E26                       | HAL., INC., LED, CFL | 120V     | 252             | 080083584369 |
| H99TAT         | 4" New Construction, Non-IC, Air-Tite, Shallow      | E26                       | HAL., INC., LED, CFL | 120V     | 168             | 080083584260 |

Note: Lamps not included.

# E44 Housings

## HALO

The E44 Series is a compact and efficient recessed housing family optimized for use with LED, MR16 and PAR16 lamps (not included). The housings are suitable for new or retrofit residential or light commercial construction. The housings are designed for installation in insulated ceilings or non-insulated ceilings with airtight code compliant construction and can be used with a variety of trims and finishes to create different lighting effects or to match any decor.



E44MR16ICAT



E44MR16RICAT

| Catalog Number | Product Description         | Socket                    | Lamp Source* | Pallet Quantity | UPC          |
|----------------|-----------------------------|---------------------------|--------------|-----------------|--------------|
| E44MR16ICAT    | 4" Ultra Shal, ICAT         | Gx5.3/bi-pin 12V LED MR16 | LED          | 192             | 080083818327 |
| E44MR16RICAT   | 4" Ultra Shal Remodel, ICAT | Gx5.3/bi-pin 12V LED MR16 | LED          | 630             | 080083818341 |
| E44PAR16ICAT   | 4" Ultra Shal, ICAT         | GU10/120V LED PAR16       | LED, HAL     | 192             | 080083818785 |
| E44PAR16RICAT  | 4" Ultra Shal Remodel, ICAT | GU10/120V LED PAR16       | LED, HAL     | 630             | 080083818822 |

Note: Lamps not included.

# 4" Trims for MR/PAR16 Lamps

## HALO

The E44 series of round and square aperture trims are designed for use with HALO E44 series housings and optimized for use with LED, MR16 and PAR16 lamps (not included). An ideal solution to shape light to minimize aperture glare and reduce ceiling brightness, the family includes many trim types and finishes including Open, Lens and Lens Wall Wash available in White, Black with some models offered in Brushed Nickel and German Bronze. The lensed trims are wet location listed.



1440H



1441WBWF



1442H



1444MW

| Catalog Number | Product Description                    | Finish                     | Lamp Source        | Pallet Quantity | UPC          |
|----------------|----------------------------------------|----------------------------|--------------------|-----------------|--------------|
| 1440H          | 4" Conical Ref, Open                   | Haze                       | LED; Halogen PAR16 | 168             | 080083820726 |
| 1440HWF        | 4" Conical Ref, Open                   | Haze, White Flange         | LED; Halogen PAR16 | 168             | 080083820740 |
| 1440MWWF       | 4" Conical Ref, Open                   | Matte White, White Flange  | LED; Halogen PAR16 | 168             | 080083820702 |
| 1441WBWF       | 4" Conical Baf, Open                   | White Baffle, White Flange | LED; Halogen PAR16 | 168             | 080083820900 |
| 1442H          | 4" Conical Lens Wall Wash              | Haze                       | LED; Halogen PAR16 | 168             | 080083821006 |
| 1442HWF        | 4" Conical Lens Wall Wash              | Haze, White Flange         | LED; Halogen PAR16 | 168             | 080083821020 |
| 1442MWWF       | 4" Conical Lens Wall Wash              | Matte White, White Flange  | LED; Halogen PAR16 | 168             | 080083820986 |
| 1443H          | 4" Conical Ref, Diffuse Lens           | Haze                       | LED; Halogen PAR16 | 168             | 080083821068 |
| 1443HWF        | 4" Conical Ref, Diffuse Lens           | Haze, White Flange         | LED; Halogen PAR16 | 168             | 080083821082 |
| 1443MWWF       | 4" Conical Ref, Diffuse Lens           | Matte White, White Flange  | LED; Halogen PAR16 | 168             | 080083821044 |
| 1444MW         | 4" Rnd Pinhole, Open                   | Matte White                | LED; Halogen PAR16 | 168             | 080083821143 |
| 1445MWWB       | 4" Rnd Pinhole w/Oculus                | White Baffle, White Flange | LED; Halogen PAR16 | 168             | 080083821228 |
| 1446MWWB       | 4" Rnd Pinhole, Lens Wall Wash         | White Baffle, White Flange | LED; Halogen PAR16 | 168             | 080083821303 |
| 1447MWWB       | 4" Rnd Pinhole, Diffuse Lens           | White Baffle, White Flange | LED; Halogen PAR16 | 168             | 080083821341 |
| 1449AAG        | 4" Rnd All Acrylic Glass, Diffuse Lens | Acrylic Glass              | LED; Halogen PAR16 | 360             | 080083821426 |
| 1484MW         | 4" Sq Pinhole, Open                    | Matte White                | LED; Halogen PAR16 | 168             | 080083821440 |
| 1485MWWB       | 4" Sq Pinhole w/Oculus                 | Matte White, White Baffle  | LED; Halogen PAR16 | 168             | 080083821525 |
| 1486MWWB       | 4" Sq Pinhole, Lens Wall Wash          | Matte White, White Baffle  | LED; Halogen PAR16 | 168             | 080083821600 |
| 1487MWWB       | 4" Sq Pinhole, Diffuse Lens            | Matte White, White Baffle  | LED; Halogen PAR16 | 168             | 080083821648 |
| 1489AAG        | 4" Sq All Acrylic Glass, Diffuse Lens  | Acrylic Glass              | LED; Halogen PAR16 | 360             | 080083821723 |

Note: Lamps not included.

