



Powering Business Worldwide

5132A

Wallplate 1G Duplex Recp Nylon Std AL

UPC: 032664555114

Brand Name: Eaton

Sub Brand: ARROW HART

Type: (1) Duplex Receptacle

Special Features: Standard Grade, Flush Fitting

Application: Residential

Size: Standard, 2.75 In Width X 4.50 In Height

Gang: 1

Cutout: 1.34 In Width X 1.53 In Height X 1.13 Recp

Material: Thermoset

Thickness: 0.080 In

Color: Almond

Mounting: Screw

Construction: Warp Resistant

5132B-BOX

Wallplate 1G Duplex Recp Nylon Std BR

UPC: 032664151606

Brand Name: Eaton

Sub Brand: ARROW HART

Type: (2) Duplex Receptacle

Special Features: Standard Grade, Flush Fitting

Application: Residential

Size: Standard, 4.56 In Width X 4.50 In Height

Gang: 2

Cutout: 0.40 In Width X 0.93 In Height

Material: Thermoset

Thickness: 0.080 In

Color: Almond

Mounting: Screw

Construction: Warp Resistant

5132BK-SP

Wallplate 1G Duplex Recp Nylon Std BK

UPC: 032664555121

Brand Name: Cooper Wiring Devices

Type: (1) Duplex Receptacle, (1) Decorator

Special Features: Standard Grade, Flush Fitting, Opening Configuration 1.31 In Width X 0.76 In Height, 1.31 In Width X 2.64 In Height

Application: Residential

Size: Standard, 4.56 In Width X 4.50 In Height

Gang: 2

Material: Thermoset

Thickness: 0.080 In

Color: Almond

Mounting: Screw

Construction: Warp Resistant



Powering Business Worldwide

5132GY-BOX

Wallplate 1G Duplex Recp Nylon Std GY

UPC: 032664433306

Brand Name: Eaton

Sub Brand: EATON

Type: Duplex, Straight Blade

Special Features: Standard Grade, Wiring Type Side Wire and Push Wire

Application: Standard grade

Standard: UL

Number Of Poles: 2

Number Of Wires: 3

Wire Size: 14 To 10 AWG

Amperage Rating: 15 Amp

Voltage Rating: 125 Vac

Material: Impact Resistant Thermoplastic

Color: Brown

NEMA Rating: 5-15R

Mounting: Flush

Connection: Screw

Size: 1.31 In Width X 0.69 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 125 Vac

Insulation: Receptacles

Temperature Rating: '-20C to 60C



Powering Business Worldwide

5132LA

Wallplate 1G Duplex Recp Nylon Std LA

UPC: 032664582981

Brand Name: Eaton

Sub Brand: EATON

Type: Duplex, Straight Blade

Special Features: Standard Grade, Wiring Type Side Wire and Push Wire

Application: Standard grade

Standard: UL

Number Of Poles: 2

Number Of Wires: 3

Wire Size: 14 To 10 AWG

Amperage Rating: 15 Amp

Voltage Rating: 125 Vac

Material: Impact Resistant Thermoplastic

Color: Ivory

NEMA Rating: 5-15R

Mounting: Flush

Connection: Screw

Size: 1.31 In Width X 0.69 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 125 Vac

Insulation: Receptacles

Temperature Rating: '-20C to 60C



Powering Business Worldwide

5132RD-BOX

Wallplate 1G Duplex Recp Nylon Std RD

UPC: 032664461101

Brand Name: Eaton

Sub Brand: EATON

Type: Duplex, Straight Blade

Special Features: Standard Grade, Wiring Type Side Wire and Push Wire

Application: Standard grade

Standard: UL

Number Of Poles: 2

Number Of Wires: 3

Wire Size: 14 To 10 AWG

Amperage Rating: 15 Amp

Voltage Rating: 125 Vac

Material: Impact Resistant Thermoplastic

Color: White

NEMA Rating: 5-15R

Mounting: Flush

Connection: Screw

Size: 1.31 In Width X 0.69 In Depth X 4.19 In Height

Environmental Conditions: See Spec Sheet

Dielectric Strength: 125 Vac

Insulation: Receptacles

Temperature Rating: '-20C to 60C

5132V

Wallplate 1G Duplex Recp Nylon Std IV

UPC: 032664560767

Brand Name: Eaton

Sub Brand: ARROW HART

Special Features: Standard Grade, Wiring Type Side and Push Wire, Non-Grounding

Application: Industrial

Voltage Rating: 120 Vac

Amperage Rating: 15 Amp

Number Of Poles: 1

Connection: Screw

Actuator: Framed Toggle

Color: Brown

Contact Configuration: Switches

Size: 0.75 In Width X .88 In Depth X 2.13 Back Length X 3.28
Screw to Screw

Mounting: Wall

Operating Temperature: -20 To 60 Deg C



Powering Business Worldwide

5132W

Wallplate 1G Duplex Recp Nylon Std WH

UPC: 032664560774

Brand Name: Eaton

Sub Brand: ARROW HART

Special Features: Standard Grade, Wiring Type Side and Push Wire, Non-Grounding

Application: Industrial

Voltage Rating: 120 Vac

Amperage Rating: 15 Amp

Number Of Poles: 1

Connection: Screw

Actuator: Framed Toggle

Color: Ivory

Contact Configuration: Switches

Size: 0.75 In Width X .88 In DepthX 2.13 Back Length X 3.28 Screw to Screw

Mounting: Wall

Operating Temperature: -20 To 60 Deg C

BP5132V

Wallplate 1G Duplex Recp Nylon Std IV

UPC: 032664547805

Brand Name: Eaton

Sub Brand: Eaton

Type: 1 Pole, 3-Way, 180 Deg Dual Switch

Special Features: Interchangeable colors

Application: Dimming 0-10V ballasts

BP5132W

Wallplate 1G Duplex Recp Nylon Std WH

UPC: 032664547812

Brand Name: Eaton

Sub Brand: Eaton

Type: 1 Pole, 180 Deg

Special Features: Interchangeable colors

Application: Dimming 0-10V ballasts