



Galvanized Ground Rod, Pointed – 811280UPC



- Meets ANSI®/NEMA® GR1
- Zinc-coated exteriors are hot-dip galvanized for solid protection against corrosion, in accordance with ASTM® specification A123
- Surfaces are rigidly inspected to eliminate seams, slivers and other defects



Part Number	811280UPC
Material	Steel
Finish	Hot-Dip Galvanized
Tensile Strength	80,000 psi Min
Ground Rod Diameter, Nominal	1/2"
Ground Rod Diameter, Actual (Ø)	0.507"
Length (L)	8'
Unit Weight	5.4 lb
UPC Label	Yes
Standard Packaging Quantity	10 pc
UPC	78285633151

ANSI is a registered trademark of American National Standards Institute. ASTM is a registered trademark of American Society for Testing and Materials. NEMA is a registered service mark of National Electrical Manufacturers Association.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.