



FEIN



MULTIMASTER MM 700 Max Top

Oscillating MultiTools - MM 700

Our best MultiTool for ultra-rapid work progress for interior construction and renovation with 12 accessories – for sawing in wood, metal, plastics, for removing tiles, cutting silicone caulking and carpeting, removing residual adhesive and tile adhesive.

Product number: 7 229 68 61 09 0

Details

- > Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- > StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- > With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- > 450 W FEIN high-performance motor: Durable, overload-proof, high-performance motor with high proportion of copper for higher cutting speed and ultra-rapid work progress.
- > Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- > Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- > Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- > Industrial cable: Large operating radius thanks to the 5 m, fine-stranded rubber-clad cable in industrial quality.
- > Electronic safety cut-off – protection for users if the saw blade blocks, for example.

Price includes

- | | |
|---|---|
| ✓ 2 E-Cut standard saw blades, curved (1-3/8 [35] in[mm]) | ✓ 2 E-Cut standard saw blades, curved (2-1/2 [65] in[mm]) |
| ✓ 1 E-Cut Precision BIM saw blade (1-3/8 [35] in[mm]) | ✓ 1 E-Cut Precision BIM saw blade (2-1/4 [65] in[mm]) |
| ✓ 1 E-Cut Long Life saw blade (10 mm) | ✓ 2 E-Cut Long Life saw blades (1-3/8 [35] in[mm]) |
| ✓ 1 E-Cut Long Life saw blade (1-1/4 [32] in[mm]) | ✓ 1 E-Cut Long Life saw blade (1-5/8 [42] in[mm]) |
| ✓ 1 E-Cut Carbide Pro saw blade (1-1/4 [32] in[mm]) | ✓ 1 segmented saw blade (Ø 3-3/8 [85] in[mm]) |
| ✓ 1 HM saw blade (Ø 3 [75] in[mm]) | ✓ 1 carbide rasp (triangular) |
| ✓ 1 rigid scraper blade | ✓ 1 mushroom-shaped cutting blade |
| ✓ 1 Multi-knife | ✓ 1 perforated sanding pad |
| ✓ 10 sanding sheets, perforated each (grits 60, 80, 120, 180) | ✓ 1 dust extraction device |
| ✓ 1 tool case | |

Product feature

- ✓ Mechanical interconnection

Technical data

TECHNICAL DATA

Power consumption	450 W
Power output	250 W
Oscillations	10,000 - 19,500 opm
Tool mount	StarlockMax
Tool change	QuickIN
Range	2 x 2,0°
Cable with plug	16.4 [5] ft[m]
Weight	3.53 [1.60] lbs[kg]
Weight	3.53 lbs

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	85 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	96 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	97 dB 3 dB

Application examples

