



GuardDog®

EXTERIOR WOOD SCREW

FEATURES

- Versatile head style can be used with the PoziSquare™ drive, #2 square drive and Phillips drive
- Guaranteed corrosion resistance
- Color matched to blend in with pressure treated decking
- Approved in pressure treated decking
- Sharp threads quickly penetrate lumber
- Free PoziSquare bit included

LENGTHS: 1 5/8", 2", 2 1/2", 3", 3 1/2"

DESCRIPTION

GuardDog is a versatile exterior wood screw used for a variety of applications. The PoziSquare drive eliminates stripping. Fully tested, fully guaranteed in ACQ, Cedar, Redwood and Copper Azole.

PACKAGING QUANTITIES

75 pc box, 350 pc box, 1,750 pc bucket, 1,350 pc bucket (3 1/2" only)



INSTALLATION PROCEDURE

Use a 0-1800 RPM variable speed drill (at least 14.4V if cordless). Install fastener perpendicular to deck, increasing drill speed as the screw threads into the deck. Slightly countersink. Do not overdrive. If cam-out occurs, remove and replace screw.

Predrilling is recommended at all seam joints, when fastening within 1 1/2" of end of board, and when using hardwoods.



GuardDog SKU Selection Guide			
SCREW LENGTH	PACKAGING QTY	COVERAGE	SKU
1 5/8"	75 pc box	20 sq ft	FMGD158-75
	350 pc box	100 sq ft	FMGD158-350
	1,750 pc bucket	500 sq ft	FMGD158-1750
2"	75 pc box	20 sq ft	FMGD002-75
	350 pc box	100 sq ft	FMGD002-350
	1,750 pc bucket	500 sq ft	FMGD002-1750
2 1/2"	75 pc box	20 sq ft	FMGD212-75
	350 pc box	100 sq ft	FMGD212-350
	1,750 pc bucket	500 sq ft	FMGD212-1750
3"	75 pc box	20 sq ft	FMGD003-75
	350 pc box	100 sq ft	FMGD003-350
	1,750 pc bucket	500 sq ft	FMGD003-1750
3 1/2"	75 pc box	20 sq ft	FMGD312-75
	350 pc box	100 sq ft	FMGD312-350
	1,350 pc bucket	350 sq ft	FMGD312-1350
Driver bit for GuardDog w/ PoziSquare drive (2 included)			FMPOZ12BIT-2PK

GUARANTEED CORROSION RESISTANCE

The GuardDog coating has been tested and approved for use in ACQ, Copper Azole pressure treated wood, cedar, and redwood applications. This fastener is guaranteed to protect against rust for the life of the project. Corrosion guarantee does not apply when the fastener is used within 1,000 ft. of saltwater or when de-icing salts will be in contact with decking. Use FastenMaster TrimTop for these applications.

For technical support or to place an order: 800.518.3569 or www.FastenMaster.com