



Acrylic Product Guide

Max* Flex Kitchen/Bath

Max Flex Kitchen/Bath by GE is a premium quality caulk that is mold and mildew resistant. Max Flex, unlike some acrylic caulks, is paint-friendly so it won't cause paint to crack, fade or change sheen.

- Mold & mildew resistant
- Paint-friendly; won't cause paint to crack, fade or change sheen
- Exceeds ASTM C920, TTS-230 for better crack resistance
- Indoor/outdoor
- Easy soap & water clean-up
- Premium acrylic urethane



SKU	Color	Contents	Pack Qty	UPC
GE23895	White	10.1 FL OZ	12	077027238952
GE23911	Clear	10.1 FL OZ	12	077027239119
GE21840	Almond	10.1 FL OZ	12	077027218404
GE23978	White	5.5 FL OZ	12	077027239782
GE23994	Clear	5.5 FL OZ	12	077027239942
GE21865	Almond	5.5 FL OZ	12	077027218657



Max* Flex Window/Door/Trim

Max Flex Window/Door/Trim by GE is a premium quality caulk that is paint-friendly, so it won't cause paint to crack fade or change sheen, unlike some acrylic caulks. Max Flex is mold and mildew resistant.

- Paint-friendly; won't cause paint to crack, fade or change sheen
- Mold & mildew resistant
- Exceeds ASTM C920, TTS-230 for better weather resistance
- Indoor/outdoor
- Premium acrylic urethane



SKU	Color	Contents	Pack Qty	UPC
GE22764	White	10.1 FL OZ	12	077027227642
GE22780	Clear	10.1 FL OZ	12	077027227802



Max* Extra

Max Extra by GE is a general-purpose paintable caulk that provides better flexibility in most temperatures and is mold and mildew resistant.

- Exceeds ASTM C834 for better flexibility in most temperatures
- Mold & mildew resistant
- Paintable
- Indoor/outdoor
- Window & door
- Siliconized acrylic



SKU	Color	Contents	Pack Qty	UPC
GE22582	White	10.1 FL OZ	12	077027225822
GE22608	Crystal Clear	10.1 FL OZ	12	077027226089
GE22624	Brown	10.1 FL OZ	12	077027226249
GE22640	Woodtone	10.1 FL OZ	12	077027226409
GE22665	Gray	10.1 FL OZ	12	077027226652
GE22681	Almond	10.1 FL OZ	12	077027226812
GE24356	Black	10.1 FL OZ	12	077027243567
GE24331	Redwood	10.1 FL OZ	12	077027243314
GE22723	White	5.5 FL OZ	12	077027227239
GE22749	Crystal Clear	5.5 FL OZ	12	077027227499



Max*

Max by GE is a general-purpose caulk that is paintable in 1 hour.

- Paintable in 1 hour
- Flexible
- Easy soap & water clean-up
- Window & door
- Indoor/outdoor
- Siliconized acrylic



SKU	Color	Contents	Pack Qty	UPC
GE22566	White	10.1 FL OZ	12	077027225662



Painters

Painters by GE is a general-purpose caulk for use in paint preparation.

- Paintable
- Easy soap & water clean-up
- Indoor/outdoor
- Siliconized acrylic

SKU	Color	Contents	Pack Qty	UPC
GE14449	White	10.1 FL OZ	12	077027144499



Max* Stretch

Max Stretch by GE is a premium quality general-purpose caulk that offers maximum stretch with 2x the strength in applications with large joint movement (+/- 35%). Max Stretch typically has over 800% elongation (stretch), providing good adhesion in expansion applications. Spans up to a 2" gap.

- Maximum stretch with 2x the strength – 800% elongation
- Paint-friendly; won't cause paint to crack, fade or change sheen
- Exceeds ASTM C920 class 35; +/-35% joint movement
- Exceeds ASTM C834 -18°C for better flexibility in most temperatures
- Indoor/outdoor
- Siliconized acrylic



SKU	Color	Contents	Pack Qty	UPC
M90044	White	10.1 FL OZ	12	077027900446



Max* Speedpaint

Max Speedpaint by GE is a premium quality, general-purpose caulk that is paintable in 30 minutes, or can be spray painted immediately. Unlike some acrylic caulks, Max Speedpaint is paint friendly, so it won't cause paint to crack, fade or change sheen.

- Paintable in 30 minutes – spray paint immediately
- Paint-friendly; won't cause paint to crack, fade or change sheen
- Exceeds ASTM C834 -18°C for better flexibility in most temperatures
- Mold & mildew resistant
- Indoor/outdoor
- Siliconized acrylic



SKU	Color	Contents	Pack Qty	UPC
GE55749	White	10.1 FL OZ	12	077027557497



To order call Momentive Customer Service toll-free at 866-275-4372. Fax orders to Customer Service at 614-986-2489
For additional information visit www.gesealants.com

Copyright 2013 Momentive Performance Materials Inc., GE is a Trademark of General Electric Company and is under license by Momentive Performance Materials Inc., Huntersville, NC 28078
*Trademark of Momentive Performance Materials Inc.

See individual product labels for additional information, including specific warranty terms and product application conditions, including temperature and humidity, and/or other use requirements or specifications with respect to our claims.