

26439 - GE HID 175 watt ED28 1-pack

HR175DX39/CP

- ☞ Count on GE quality lighting for residential and commercial lighting applications. GE light bulbs are built to last, so you can replace them and forget about them
- ☞ Uses 175 watts
- ☞ 3900K light appearance
- ☞ Lasts 20000 hours
- ☞ ED28 shape with Mogul Screw (E39) base
- ☞ Provides 7800 lumens

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	Mogul Screw
Base Type	Screw-In
Lamp Enclosure Type (LET)	Open or enclosed fixtures
Mercury-Picogram per mean lm hr	228.5
Rated Life Hours-nominal	20000 h
Bulb Finishes and Colors	Delux white
Mercury Content EMEA ONLY	30.3
Bulb Material	Hard glass
Primary Application	Street Lighting
	Motion-Sensing & Security
	High Intensity Discharge
Product Technology	1
Lamp Count	18.3
Life in Years	Carton, Tray Pack
Requested Structure	E39
Base	ED28
Bulb Shape	

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	6630 lm
Nominal Lumens per Watt	45 lm
Color Rendering Index-CRI	50
Color Temperature	3900 K

PRODUCT INFORMATION

Product Code	26439
Description	HR175DX39/CP
Alternative Unit Of Measure	CASE
Standard Package Quantity	4
Ean UPC	043168264396
Standard Package GTIN	30043168264397
No Of Items Per Sales Unit	
No Of Items Per Standard Package	4
Sales Unit	Case
UCC	043168264396
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168264396
Standard Package GTIN	00043168264396
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168264396

DIMENSIONS

Diameter	3.5 in
Light Center Length Millimeter	5.0 in
Nominal Length	8.25 in

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Open Circuit Voltage (peak lead ballast) (MIN)	318 V
Open Circuit Voltage (RMS lag ballast) (MIN)	225 V

CAUTIONS & WARNINGS

WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/uruburns.html>

Caution

- Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use excessive force when installing lamp.

Do not use lamp if outer glass is scratched or broken.

Warning

Unexpected lamp rupture may cause injury, fire, or property damage

Do not exceed rated voltage.

Do not store flammable materials near/below S-rated lamp in open fixture

Do not turn on lamp until fully installed.

Do not use beyond rated life.

Do not use lamp if outer glass is scratched or broken.

Do not use where directl

A damaged lamp emits UV radiation which may cause eye/skin injury

Turn power off if glass bulb is broken. Remove and dispose of lamp.

Risk of Burn

Allow lamp to cool before handling.

Do not turn on lamp until fully installed.

Risk of Fire

Keep combustible materials away from lamp.

Use in fixture rated for this product.

Risk of Electric Shock

Do not use where directly exposed to water or outdoors without an enclosed fixture.

Turn power off before inspection

installation or removal.

