

25426 - GE kitchen & bath 13 watt T5 1-pack

F13T5/WW/CARD

- GE's Warm White Thin Line lights are ideal for display or shelf lighting and under cabinets.
- 0.6 inch diameter T5 with miniature bi-pin (g5) base
- 3000K warm white light appearance
- For use in kitchens, bathrooms, and living areas
- GE kitchen & bath fluorescent bulbs deliver a warmer tone to create a comfortable and inviting atmosphere. These warm white bulbs are best for living areas throughout your home, hotels, commercial restrooms, reception areas and food preparation
- Lasts 2.3 years based on 6 hours per day usage
- Warm, inviting light that complements any décor
- 21 inches long

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	Miniature Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	6 mg
Mercury-Picogram per mean lm hr	1666.7
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Soda lime
Rated Life Hours-nominal	5000 h
Primary Application	Kitchen & Bath
Product Technology	Linear Fluorescent
Base	G5
Bulb Shape	T5

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	720 lm
Nominal Initial Lumen per Watt	67
Initial Lumens-nominal	870 lm
Color Rendering Index-CRI	52
Color Temperature	3000 K

PRODUCT INFORMATION

Product Code	25426
Description	F13T5/WW/CARD
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168254267
Standard Package GTIN	10043168254264
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168254267
Alternative Unit Of Measure	CASE
Standard Package Quantity	5
Ean UPC	043168254267
Standard Package GTIN	00043168254267
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	5
Sales Unit	Case
UCC	043168254267

DIMENSIONS

Bulb Diameter (DIA) <Max>	0.63 in
Bulb Diameter (DIA) <Min>	0.53 in
Diameter	0.62 in
Face to End of Opposing Pin (B) <Max>	20.63 in
Face to End of Opposing Pin (B) <Min>	20.53 in
Nominal Length	21.0 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Open Circuit Voltage (rapid start) Min @ Temperature	180.00 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Rated power (Watts)	13 W

CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning

- Risk of Electric Shock

Turn power off before inspection
installation or removal.

