

26422 - GE HID 70 watt B17 1-pack

LU70/MED/CP

- ☞ 1900K light appearance
- ☞ B17 shape with Medium Screw (E26) base
- ☞ Count on GE quality lighting for residential and commercial lighting applications. GE light bulbs are built to last, so you can replace them and forget about them
- ☞ Lasts 24000+ hours
- ☞ Provides 6400 lumens
- ☞ Uses 70 watts

PRODUCT PHOTO



GENERAL CHARACTERISTICS

| | |
|---------------------------------|---------------------------|
| Base Description | Medium Screw |
| Base Type | Screw-In |
| Lamp Enclosure Type (LET) | Open or enclosed fixtures |
| Mercury-Picogram per mean lm hr | 104.7 |
| Rated Life Hours-nominal | 24000 h |
| Bulb Finishes and Colors | Clear |
| Mercury Content EMEA ONLY | 13.7 |
| Bulb Material | Soft glass |
| Primary Application | Motion-Sensing & Security |
| Product Technology | High Intensity Discharge |
| Lamp Count | 1 |
| Life in Years | 21.9 |
| Requested Structure | Carton, Tray Pack |
| Base | E26 |
| Bulb Shape | ED17 |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------|---------|
| Effective Arc Length | 1.06 in |
| Mean Lumens nominal | 5450 lm |
| Nominal Lumens per Watt | 91 lm |
| Color Rendering Index-CRI | 22 |
| Color Temperature | 1900 K |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 26422 |
| Description | LU70/MED/CP |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | 4 |
| Ean UPC | 043168264228 |
| Standard Package GTIN | 30043168264229 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | 4 |
| Sales Unit | Case |
| UCC | 043168264228 |
| Alternative Unit Of Measure | EACH |
| Standard Package Quantity | 1 |
| Ean UPC | 043168264228 |
| Standard Package GTIN | 00043168264228 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | 1 |
| Sales Unit | Each |
| UCC | |

DIMENSIONS

| | |
|--------------------------------|---------|
| Diameter | 2.12 in |
| Light Center Length Millimeter | 3.43 in |
| Nominal Length | 5.43 in |

ELECTRICAL CHARACTERISTICS

| | |
|--|----------------------------|
| Burn Position | Universal burning position |
| Open Circuit Voltage (RMS lag ballast) (MIN) | 110 V |
| Rated power (Watts) | 70 W |

CAUTIONS & WARNINGS

WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

Caution

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use excessive force when installing lamp.

Do not use lamp if outer glass is scratched or broken.

Wear safety glasses and gloves when handling lamp.

Risk of Burn

Allow lamp to cool before handling.

Do not turn on lamp until fully installed.

Warning

Contains sodium ? chemical burn risk

Avoid skin contact with broken pieces.

Risk of Electric Shock

Do not use where directly exposed to water or outdoors without an enclosed fixture.

Turn power off before inspection

installation or removal.

Risk of Fire

Keep combustible materials away from lamp.

Use in fixture rated for this product.

Unexpected lamp rupture may cause injury, fire, or property damage

Do not exceed rated voltage.

Do not store flammable materials near/below S-rated lamp in open fixture

Do not turn on lamp until fully installed.

Do not use lamp if outer glass is scratched or broken.

Do not use where directly exposed to water or outdoors

