



Representative Image

Catalog No. THQL2160

Description: THQL 2 POLE 120/240V 10K IC 60 AMP

UPC No 783164048483

Home > Circuit Breakers > Residential Circuit Breakers > Feeder Plug-in Circuit Breakers

Q line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications. The QL breakers are plug-in versions of the Q Line used for connection to load centers and lighting panels. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers are available in 1, 2, and 3 pole versions, can be ordered with auxiliary contact and shunt trip accessories, and can be ordered for use in HID applications. 2160 Amps 60 A 21608483

| Descriptors | |
|-------------|--|
|-------------|--|

| Category | Feeder Plug-in Circuit Breakers |
|-------------|---------------------------------|
| GO Schedule | R5 |

Specifications

| Trip Style | Non-Interchangeable |
|---------------------------------|----------------------|
| Frame Type | Q-Line |
| Amperage | 60 A |
| System Voltage | 120 Vac, 120/240 Vac |
| Poles | 2 |
| Trip Function | LI |
| Continuous Current Rated | Standard |
| 120 Vac Interrupting Rating | 10 KAIC |
| 120/240 Vac Interrupting Rating | 10 KAIC |
| Suitable for Reverse Feed | Yes |
| Product Line | Q-Line (Plug-In) |
| Long Time | Fixed |
| Instantaneous | Fixed |
| Protective Relays | No |
| Current Metering | No |
| Special Markings | HACR |
| GSA Compliance | Yes |

Classifications

| UL File # | E11592 |
|-----------|--------|

geindustrial.com Created on: 08/13/2018

| Publications | | |
|---|------------------------|-------------------------------------|
| Title | Publication No. | Publication Type |
| PowerMark Gold* Load Centers, Q-Line Circuit Breakers and Accessories Guide | | Application and |
| Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Q-Line Plug-In MCCB, 100A Frame 1-, 2-, or 3- Pole, Drawing | DET1023 | Technical |
| 1-Page fully dimensioned outline drawing in .pdf format | 455C872-SH1 | Drawings-Outline and Dimensional |
| 60A 2P THQL BREAKER 10K @ 120/240V FOR USE WITH 125A GE METER STACKS | | Drawings-Outline and Dimensional |
| THQL2160 - 2P 60A 10K Breaker for 125A Sockets Outline Drawing | DEE-852 | |

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

geindustrial.com Created on: 08/13/2018