

93883 - GE LFL Multi-Volt ProLine™ Electronic Multivolt Instant Start Ballast

GE232MAXG-N-DIYB MV

- ☞ High performance electronic ballast for all general fluorescent applications
- ☞ Instant start electronic ballast for long lamp starting cycles and low initial cost
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ Light-weight, Low Profile Housing
- ☞ Parallel lamp operation means system maintenance is easier to manage

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Ballast Factor	Normal
Ballast Type	Multivolt Instant Start
Case Temperature (Max)	70 °C
Line Voltage Regulation (+/-)	10%
Classification (Regulations)	cUL Listed FCC - CLASS A Non-Consumer NRCAN UL Class P UL Listed UL Type 1 Outdoor UL Type HL Product is compliant with material restriction requirements of RoHS
Sound Rating	A (20-24 decibels)
Starting Method	Instant start
Product Technology	Linear Fluorescent
Lamp Wiring	Parallel
Power Factor Correction	Active
Lamp Count	1
Requested Structure	Carton

PRODUCT INFORMATION

Product Code	93883
Description	GE232MAXG-N-DIYB MV
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168722773
Standard Package GTIN	10043168722770
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168722773
Alternative Unit Of Measure	EACH
Standard Package Quantity	4
Ean UPC	043168722773
Standard Package GTIN	00043168722773
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	4
Sales Unit	Each
UCC	043168722773
Alternative Unit Of Measure	CASE
Standard Package Quantity	4
Ean UPC	043168938839
Standard Package GTIN	10043168938836
No Of Items Per Sales Unit	
No Of Items Per Standard Package	4
Sales Unit	Case
UCC	
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168938839
Standard Package GTIN	00043168938839
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	

DIMENSIONS

Weight	1.4 lb
Exit Type	
Remote Mount Distance	18.0 ft

Case Dimensions

Length	9.5in
Width	1.3in
Height	1.18in

Mounting Dimensions









Mount Length	8.9in
Mount Width	1.1in
Mount Slot	0.3in

Lead Color	Qty	Exit	Length (± 1 in.)
Black	1	Left	25in
Red	1	Right	45in
Blue	2	Right	31in
White	1	Left	25in

ELECTRICAL CHARACTERISTICS

Estimated Energy Cost per Year	0.12
Rated power (Watts)	1 W

SAFETY & PERFORMANCE

-  cUL_Listed
-  FCC_CS_NCons
-  NR_Can
-  UL_Cls_P
-  UL_Listed
-  UL_Type1_Out
-  UL_Type_HL
-  Pro_comp_res_req

CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

Properly ground ballast and fixture.

Turn power off before servicing--see instructions.

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
F17T8	2	120	31	0.26	0.88	3	0.99	1.7	6	0
F40T8	1	120	44	0.37	1.08	2	0.99	1.7	5	0
F17T8	1	120	20	0.17	1.05	5	0.99	1.7	8	0
F32T8	2	120	57	0.48	0.88	2	0.99	1.7	4	0
F25T8	1	277	28	0.11	1.08	4	0.95	1.7	9	0
F32T8/WM	2	277	51	0.19	0.87	2	0.97	1.7	8	60
F32T8/25W	2	277	43	0.0	1.02	2	0.97	1.7	10	60
F25T8	1	120	28	0.23	1.08	4	0.99	1.7	7	0
F28T8	1	120	31	0.26	1.02	3	0.99	1.7	6	60
F25T8	2	277	44	0.16	0.91	2	0.97	1.7	7	0
F32T8/WM	1	277	33	0.12	1.05	3	0.96	1.7	8	60
F17T8	1	277	21	0.08	1.05	5	0.92	1.7	14	0
F40T8	1	277	43	0.16	1.08	3	0.96	1.7	8	0
F32T8	2	277	55	0.2	0.88	2	0.98	1.7	9	0
F32T8	1	120	35	0.3	1.08	3	0.99	1.7	5	0
F28T8	2	120	47	0.39	83.0	177	0.99	1.7	4	60
F32T8/WM	1	120	33	0.28	1.05	3	0.99	1.7	6	60
F28T8	2	277	47	0.17	0.83	2	0.97	1.7	8	60
F32T8/25W	1	120	28	0.0	1.02	4	0.99	1.7	10	60
F32T8	1	277	35	0.13	1.08	3	0.97	1.7	8	0
F28T8	1	277	31	0.11	1.02	3	0.95	1.7	9	60
F25T8	2	120	44	0.37	0.9	2	0.99	1.7	5	0
F32T8/WM	2	120	53	0.44	0.86	2	0.99	1.7	4	60
F17T8	2	277	31	0.12	0.88	3	0.95	1.7	9	0



Jun 26, 2019 6:37:12 AM | For additional information, visit products.currentbyge.com