

current

powered by GE

11084 - GE kitchen & bath circline 22 watt T9 circline 1-pack

FC8T9/KB

- ☞ For use in kitchens and baths
- ☞ Food looks fresher & skin tones are more attractive
- ☞ Lasts up to 8 years!
- ☞ 1.1 inch diameter T9 circline with 4-pin (g10q) base
- ☞ Lasts 5.5 years based on 6 hours per day usage
- ☞ 3000K warm white light appearance
- ☞ For use in kitchens, bathrooms, and living areas
- ☞ GE kitchen & bath circline fluorescent bulbs deliver a warmer tone to create a comfortable and inviting atmosphere. These warm white bulbs are best for living areas throughout your home, hotels, commercial restrooms, reception areas and food preparation
- ☞ Warm, inviting light that complements any décor

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	4-Pin (G10q)
Base Type	Pin/Plug-In
Mercury Content	7 mg
Mercury-Picogram per mean lm hr	520.8
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Lead glass
Rated Life Hours-nominal	12000 h
Primary Application	Full Wattage Kitchen & Bath
Product Technology	Linear Fluorescent
Base	G10q
Bulb Shape	T9

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	1120 lm
Nominal Initial Lumen per Watt	63.6363636364
Initial Lumens-nominal	1400 lm
Color Temperature	3000 K

PRODUCT INFORMATION

Product Code	11084
Description	FC8T9/KB
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168110846
Standard Package GTIN	00043168110846
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168110846
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168110846
Standard Package GTIN	10043168110843
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168110846
Alternative Unit Of Measure	CASE
Standard Package Quantity	0
Ean UPC	043168110846
Standard Package GTIN	00110846
No Of Items Per Sales Unit	
No Of Items Per Standard Package	0
Sales Unit	Case
UCC	

DIMENSIONS

Bulb Diameter (DIA) <Max>	1.22 in
Bulb Diameter (DIA) <Min>	1.03 in
Diameter	1.12 in
Nominal Length	8.25 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Open Circuit Voltage (instant start) Min @ Temperature	180.00 V @ 10 °C
Open Circuit Voltage (rapid start) Min @ Temperature	230.00 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Input Voltage [nom]	61 W
Rated power (Watts)	22 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Wear safety glasses and gloves when handling lamp.

Do not use excessive force when installing lamp.

Warning

Risk of Electric Shock

Turn power off before inspection

installation or removal.

Avoid direct water/liquid contact.

