current
powered by GE

12525 - GE garage & basement 55 watt T12 1-pack

F72T12CWUPC 10PK

- 4100K cool white light appearance
- Cool white light perfect for sizable spaces
- For use in large spaces such as basements and garages
- GE garage & basement fluorescent bulbs' cool white light is perfect for illuminating sizable spaces throughout your home. Use in large open spaces in your home including finished and unfinished basements, garages and rec rooms
- Lasts 5.5 years based on 6 hours per day usage
- 1.5 inch diameter T12 with single pin (fa8) base
- 72 inches long

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	Single Pin (Fa8)
Base Type	Pin/Plug-In
Mercury Content	90 mg
Mercury-Picogrm per mean lm hr	1811.6
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Soda lime
Rated Life Hours-nominal	12000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	Fa8
Bulb Shape	T12

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	4140 lm
Nominal Initial Lumen per Watt	79.4642857143
Initial Lumens-nominal	4450 lm
Color Rendering Index-CRI	60
Color Temperature	4100 K

PRODUCT INFORMATION

Product Code	12525
Description	F72T12CWUPC 10PK
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168125253
Standard Package GTIN	10043168125250
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168125253
Alternative Unit Of Measure	CASE
Standard Package Quantity	10
Ean UPC	043168125253
Standard Package GTIN	00043168125253
No Of Items Per Sales Unit	
No Of Items Per Standard Package	10
Sales Unit	Case
UCC	

DIMENSIONS

Bulb Diameter (DIA) <Max>	1.59 in
Bulb Diameter (DIA) <Min>	1.41 in
Diameter	1.5 in
End of Base Pin to Pin	69.73 in
Face to End of Opposing Pin (B) <Max>	69.65 in
Face to End of Opposing Pin (B) <Min>	69.42 in
Nominal Length	72.0 in

ELECTRICAL CHARACTERISTICS

Current Crest Factor (MAX)	1.7
Open Circuit Voltage (instant start) Min @ Temperature	475.00 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.250
Cathode Resistance Ratio - Rh/Rc (MAX)	6.500
Rated power (Watts)	56 W

CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

Turn power off before inspection

installation or removal.

Caution

Lamp may shatter and cause injury if broken

Wear safety glasses and gloves when handling lamp.

Do not use excessive force when installing lamp.





