

24 in LED Direct Wire Undercabinet Bar



Light Output (Lumens) Watts Lumens per Watt (Efficacy) Color Accuracy Color Rendering Index (CRI) Bright White Daylight 2700K 3000K All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results. Visit www.lightingfacts.com for the Label Reference Guide. Registration Number: VP1G-JX226G (7/14/2015) Model Number: UC1052-XXX-24LF0-X Type: Luminaire - Other

General Product Information:

Common Model Numbers

UC1052-SGM-24LF0-E

Construction: Stamped metal housing
Finish: SGM = Silver Gloss Metallic

Diffuser Material: PC

Diffuser Finish: FST Clear Frosted

Mounting: 0 Head Adjustment: NA Motion Detection Range: NA

Application Type: Damp Location

Safety Listing: ETL Energy Star: Yes

Dimensional Information:

ADA Compliant:

Total Lumens:

Chain/Stem Length: NA
Canopy Dia.: NA

Fixture Dimensions: 2.75"x1"x24"
Fixture Weight: 1.9 lbs

Electrical Information:

Lamp Included: Yes
Lamp Type: LED
Number of Lamps: 0
Lamp Wattage: 12.34W
Lamp CCT: 3152K
Lamp CRI: 84
Lamp Life: 0

Dimming: Yes
Dimming Type: Triac Wall Dimmer
Pallast / Driver: KTL D-12-1-0A38-EF

Ballast/Driver: KTLD-12-1-0A38-FDIM Input Voltage: 120V, 60Hz, 0.14A Max.

Battery Included: NA
Battery Type: NA
Battery Life at Full Charge: NA
Power Cord: NA
Linkable: Yes

Connector Cord: Receptacle + 3 conductor cord

Visit us at: www.goodearthlighting.com

904

Power Switch: On/Off Rocker Switch





