



MATERIAL TECHNICAL SHEET

Effective Date : March 1, 2010

COPPER-GREEN® & COPPER GREEN BROWN WOOD PRESERVATIVE

EPA REG. # 66591-1

CAUTION: COMBUSTIBLE MIXTURE FOR EXTERIOR USE ONLY.

ACTIVE INGREDIENTS

**Copper Napthenate.....10%*
Inert Ingredients.....90%
100%
**Copper Expressed as Metallic...1.0%*
Max V.O.C.=350 grams per liter.

OBJECTIVE

TO PREVENT DETERIORATION CAUSED BY

- TERMITES
- POWDER POST BEETLES
- FUNGUS
- ROT
- DECAY
- CONTROLS WARPING & SWELLING
- REPELS WATER/PAINTABLE

PRODUCT DESCRIPTION

COPPER-GREEN is a copper naphthenate and hydrocarbon solvent wood preservative that may be brush applied for surface protection of most woods. Dip soaking or pressure impregnation of COPPER-GREEN will result in deeper penetration resulting in longer preservation of treatable species. The copper in COPPER-GREEN reacts with the cellulose of wood. As a result it is not easily lost from the wood by leaching. This formulation extends the service life of wood products. FOR EXTERIOR USE ONLY.



MATERIAL TECHNICAL SHEET

RECOMMENDED FOR:

Window frames, doors, stairs, porches, posts, siding, shingles, trellises, steps, outdoor furniture, fence pickets, fence rails, furring strips arbors, and beverage cases. Also for use on fence posts, poles, foundations, sills, decks, boats and all wood exposed to moisture or weather. COPPER-GREEN can be used to treat wood for greenhouses, i.e. nursery flats, etc. In addition to preventing decay, blue stain, and insect attack on wood this preservative controls warping, swelling, shrinking and end checking caused by changes in moisture content of lumber and plywood products. Wood to be protected against subterranean termites should be treated before use in construction. Termites and powder post beetles will not attack wood treated with COPPER-GREEN Wood Preservative.