FRSC Chemical Solutions

SAFETY DATA SHEET

1. Identification

Product identifier Motor Medic Lead Substitute

Other means of identification

SDS number M5012 Part No. M5012

Tariff code 3811.19.0000

Recommended use Gasoline Fuel Additive

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company nameAddress
RSC Chemical Solutions 600 Radiator Road

Indian Trail, NC 28079 United States

Telephone Customer Service: (704) 821-7643

Technical: (704) 684-1811

Website www.rscbrands.com

E-mail Not available.

Emergency phone number Emergency Telephone: (303) 623-5716

Emergency Contact: RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsCarcinogenicityCategory 2Environmental hazardsHazardous to the aquatic environment, acuteCategory 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements





Signal word Warning

Hazard statement Flammable liquid and vapor. Suspected of causing cancer. Harmful to aquatic life. Harmful to

aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release to the environment. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to

extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: Motor Medic Lead Substitute M5012 Version #: 01 Issue date: 04-10-2015 Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

73.2% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 73.2% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Petroleum Distillate Aliphatic		68476-34-6	80 - < 90
Kerosene (petroleum) Hydrodesulfurized		64742-81-0	3 - < 5
NAPHTHALENE		91-20-3	< 0.3
Other components below reportable	evels		10 - < 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Specific methods

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Motor Medic Lead Substitute M5012 Version #: 01 Issue date: 04-10-2015

Methods and materials for containment and cleaning up

Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
NAPHTHALENE (CAS 91-20-3)	PEL	50 mg/m3	
,		10 ppm	
JS. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)	TWA	200 mg/m3	Non-aerosol.
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	
Petroleum Distillate Aliphatic (CAS 68476-34-6)	TWA	100 mg/m3	Inhalable fraction and vapor.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	
Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)	TWA	100 mg/m3	
NAPHTHALENE (CAS 91-20-3)	STEL	75 mg/m3	
,		15 ppm	
	TWA	50 mg/m3	
		10 ppm	
ogical limit values	No biological exposure limits noted for the ingredient(s).		

Biological limit values Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

Kerosene (petroleum) Hydrodesulfurized (CAS Can be absorbed through the skin. 64742-81-0)

NAPHTHALENE (CAS 91-20-3) Petroleum Distillate Aliphatic (CAS 68476-34-6) Can be absorbed through the skin. Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to

maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear.
Physical state Liquid.
Form Liquid.
Color Dark red

Odor Pungent. Diesel odor

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 300 °F (> 148.89 °C)

Flash point 136.0 °F (57.8 °C) Tag Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure2.2 hPa estimatedVapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 7.13 lbs/gal
Explosive properties Not explosive.

Flammability class Combustible II estimated

< 0.5 % Moisture Oxidizing properties Not oxidizing.

Specific gravity 0.86

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

No adverse effects due to skin contact are expected. Skin contact Eve contact Direct contact with eyes may cause temporary irritation.

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
NAPHTHALENE (CAS 91-20)-3)	

Acute Dermal

LD50 Rabbit > 2 g/kg Rat > 20 g/kg

Oral

LD50 Guinea pig 1200 mg/kg Rat 490 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer. IARC Monographs. Overall Evaluation of Carcinogenicity

> NAPHTHALENE (CAS 91-20-3) 2B Possibly carcinogenic to humans.

Petroleum Distillate Aliphatic (CAS 68476-34-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

NAPHTHALENE (CAS 91-20-3) Reasonably Anticipated to be a Human Carcinogen.

^{*} Estimates for product may be based on additional component data not shown.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
NAPHTHALENE (CAS	S 91-20-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	1.11 - 1.68 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

3.3 **NAPHTHALENE**

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number Not available.

UN proper shipping name

Transport hazard class(es)

Class

Consumer commodity

ORM-D

Subsidiary risk

Label(s) None

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Packaging exceptions 156, 306 Packaging non bulk 156, 306

Packaging bulk None

IATA

ID8000 **UN number**

UN proper shipping name Consumer commodity

Transport hazard class(es)

Class

Subsidiary risk

Packing group Not applicable.

Environmental hazards No. **ERG Code** 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed.

IMDG

UN number UN1202

UN proper shipping name GAS OIL or DIESEL FUEL or HEATING OIL, LIGHT solution (Petroleum Distillate Aliphatic) **Transport hazard class(es)**

Class 3
Subsidiary risk Packing group ||||

Environmental hazards

Marine pollutant No. EmS F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and the IBC Code

IATA



IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

NAPHTHALENE (CAS 91-20-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
NAPHTHALENE	91-20-3	< 0.3	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)

NAPHTHALENE (CAS 91-20-3)

Petroleum Distillate Aliphatic (CAS 68476-34-6)

US. Massachusetts RTK - Substance List

Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)

NAPHTHALENE (CAS 91-20-3)

US. New Jersey Worker and Community Right-to-Know Act

Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)

NAPHTHALENE (CAS 91-20-3)

Petroleum Distillate Aliphatic (CAS 68476-34-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)

NAPHTHALENE (CAS 91-20-3)

Petroleum Distillate Aliphatic (CAS 68476-34-6)

US. Rhode Island RTK

NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

NAPHTHALENE (CAS 91-20-3) Listed: April 19, 2002

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No

Country(s) or region Inventory name On inventory (yes/no)*

New Zealand New Zealand Inventory No.

Philippines Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-10-2015

Version # 01

HMIS® ratings Health: 1*

Flammability: 3

Physical hazard: 0

NFPA ratings Health: 0

Flammability: 3 Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Material name: Motor Medic Lead Substitute
M5012 Version #: 01 Issue date: 04-10-2015