PRODUCT INFORMATION



LEAD SUBSTITUTE

CODE M5012, M5032 PAGE 1 of 1 DATE 04/11/2008

<u>FUNCTION AND APPLICATION</u>: Allows older engines designed for use with "leaded" gasoline's to run safely with low lead or unleaded fuels when used as directed.

OUTSTANDING PROPERTIES: Prevents valve damage and upper cylinder wear in older engines with "soft" valves by coating with a protective metallic film designed to prevent valve recession.

<u>USE DIRECTIONS</u>: Add to fuel tank before refilling. Use one bottle of M50-12 for up to 20 gallons, M50-32 treat at the rate of 4 oz for 10 gallons. For Off Road Use Only.

PRODUCT LIMITATION: Product "must" be used in every tankful in cars designed for leaded gasoline's.

PRECAUTIONS: Contains Aliphatic Petroleum Distillate (CAS# 68476-34-6). Harmful or fatal if swallowed. Combustible. Vapor harmful. Eye and skin irritant. **FIRST AID:** If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. In case of inhalation, move to fresh air immediately. If breathing becomes difficult, get prompt medical attention. If eyes contacted, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use. If irritation persists, get prompt medical attention.

STORAGE & HANDLING: Store in a cool place below 120⁰F away from acids, ignition sources and oxidizing agents. Use in well ventilated area. Wearing contact lenses while working with this product is inadvisable. Keep away from children.

<u>DISPOSAL</u>: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: Packaged in 12 oz or 32 oz plastic bottle.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.