## Gaco Western

## Product Data Sheet:

## GacoRoof GRT50 RoofTape August 2013 Supersedes 05/06

## **GACOROOF GRT50 ROOF TAPE** SELF-ADHESIVE SEAM TAPE

- **DESCRIPTION:** RoofTape is a fleece-backed self-adhesive tape consisting of lightly cross-linked polymers of butyls and EPDM rubber. RoofTape is highly resistant to temperature extremes and harsh UV rays. Its unique properties allow it to conform to just about any roof surface, providing a durable watertight seal. USAGE: RoofTape will add strength and flexibility to seams, joints and edge transitions. RoofTape is intended for sealing seams, fasteners, edge transitions, small cracks, vents and drains before application of GacoRoof 100% Silicone Roof Coating. LIMITATIONS: RoofTape must not be left exposed; coat with a GacoFlex Silicone Coating as soon as it has been applied. COLOR: Fleece backing is white, adhesive is light tan. APPLIED PRODUCT DATA TENSILE: ASTM D412 at 2" per minute. Strength: 35 psi (3.31 MPa) Elongation: 250% ADHESION: 180° Peel Galvanized: 21 pli Stainless Steel: 20 pli WATER RESISTANCE: ASTM D1056 0.5% maximum PACKAGED PRODUCT DATA COVERAGE: 2" wide, 50 feet per roll. THICKNESS: 30 Mils STORAGE STABILITY: Eighteen months from date of manufacture. **APPLICATION** Surface must be COMPLETELY CLEAN AND DRY before applying Gaco RoofTape. Cut tape to **APPLICATION:** desired length and peel off release liner. Center tape over seam and firmly press into place, removing all buckles and bubbles. If applying over fasteners, press tape over all sides to conform tape to the shape of the fastener. If more than one piece is going to be used, overlap any adjoining pieces of tape by a minimum of  $\frac{1}{2}$ ". CLEAN UP: Application tools and equipment may be cleaned with GacoFlex Silicone Solvent or 100% Pure Mineral Spirits. DO NOT USE WATER OR RECLAIMED SOLVENTS. Made in the USA 800.331.0196 gaco.com