



Architectural Coatings

GLIDDEN® *Grab-N-Go* Door & Trim Interior/Exterior High Gloss**GENERAL DESCRIPTION**

Glidden Grab-N-Go Door & Trim Interior/Exterior High Gloss is ideal for use on all interior and exterior trim, doors, cabinets and molding, including properly prepared or previously painted wood, composite and metal surfaces.

RECOMMENDED SUBSTRATES

Composites
Ferrous Metal
Wood

FEATURES / BENEFITS

Resists Stains, Scuffs & Chips
Super Durable
Easy Clean
For All Doors, Trim, Cabinets & Molding

CONFORMANCE STANDARDS

VOC compliant in all regulated areas

TINTING AND BASE INFORMATION

7601D	White
7650D	Red
7699D	Black

Ready-Mixed Paint, DO NOT TINT.

PACKAGING

Quart (946 mL)

PRODUCT DATA

PRODUCT TYPE:	100% Acrylic Latex
SHEEN:	Gloss, 70-80 @ 60°
VOLUME SOLIDS*:	40% +/- 2%
WEIGHT SOLIDS*:	51% +/- 2%
WEIGHT/GALLON*:	10.2 lbs. (4.6 kg) +/- 0.2 lbs. (91 g)
VOC:	<50 g/L (0.4 lbs./gal.)

*Product data calculated on product 7601D.

COVERAGE: Approximately 75 sq. ft. (7 sq. meters) per U.S. quart (946 mL) on primed, smooth, nonporous surfaces.

Wet Film Thickness:	5.3 mils
Wet Microns:	135
Dry Film Thickness:	2.1 mils
Dry Microns:	53

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing. Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

DRYING TIME: Dry time @77°F (25°C) & 50% relative humidity.

To Touch:	30 minutes
To Recoat:	1 hour
To Full Cure:	30 days

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement. Shelving may be put into use seven days after final coat. Doors or cabinets may be closed forty-eight hours after final coat.

CLEANUP: Clean tools with warm, soapy water. Clean spills immediately with a damp cloth.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

LIMITATIONS OF USE

Apply only when air, surface and product temperatures are above 50°F (10°C) and will remain above 50°F (10°C) for 24 hours. The surface temperature must be at least 5°F (3°C) above the dew point. Do not apply late in the day when dew and condensation are likely to form or if rain is expected within 48 hours. Avoid painting in direct sunlight or on hot surfaces.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our website or by calling 1-800-441-9695.

PROTECT FROM FREEZING.

Read Label and Safety Data Sheet Prior to Use. See other cautions on last page.

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all loose, peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough and patched surfaces. Prime all bare surfaces with the appropriate primer. Some cabinet finishes may not be suitable for painting. For best results test for adhesion in an inconspicuous area prior to painting.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

COMPOSTES (VINYL & ARCHITECTURAL PLASTICS): Vinyl and similar architectural plastics may present potential adhesion problems. A primer may be required to promote proper adhesion. Consult the manufacturer's guidelines prior to painting. Primer and Topcoat should be spot applied, allowed to cure overnight, then evaluated for adhesion. If adhesion is good, the application may proceed. Check adhesion by applying a piece of masking tape. When the masking tape is removed, if the coating peels off, the surface must be scuff sanded prior to proceeding to ensure mechanical adhesion. Color selection for vinyl siding is limited. Do not paint vinyl siding with a topcoat color darker than the original to prevent potential warping due to heat absorption.

FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed with a metal primer.

WOOD: Countersink all nails, putty flush with surface. Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting.

APPLICATION INFORMATION

Stir thoroughly before using and occasionally when in use. When using more than one can of the same color, intermix to ensure color uniformity.

Application Equipment: Brushing is the preferred method of application. Apply by a premium quality nylon/polyester blend brush. Dip brush into the quart can and begin brushing, applying in thin coats. Heavy application may cause product to run. Minor brush marks will self-level. If touch-up is required after the enamel has set, wait until it has dried to touch. Two coats will provide best durability, gloss and uniformity.

Brush: Polyester/Nylon Brush

Thinning: DO NOT THIN

Permissible temperatures during application:

Material: 50 to 90°F 10 to 32°C

Ambient: 50 to 90°F 10 to 32°C

Substrate: 50 to 90°F 10 to 32°C

PRECAUTIONS

WARNING! Sanding and grinding dusts may be harmful if inhaled. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2018 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Glidden is a registered trademark and the Glidden Logo is a trademark of the PPG Group of Companies.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-454-3336.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.glidden.com

Technical Services
1-800-GLIDDEN