



Architectural Coatings

## PORCH & FLOOR

## PF7010N Series

GLIDDEN® Porch & Floor Interior/Exterior Satin

### GENERAL DESCRIPTION

Glidden Porch & Floor Interior/Exterior Satin is ideal for properly prepared new or previously painted horizontal wood, incidental metal, concrete basement floors, patios, breezeways, decks, steps, and porches. Do not use on below grade concrete floors laid directly on damp or water-bearing surfaces. Not recommended for use on garage floors or carports that are subject to tire traffic.

### RECOMMENDED SUBSTRATES

Concrete/Masonry  
Ferrous Metal  
Wood

### FEATURES / BENEFITS

High durability  
Scratch resistant  
Easy application - fast drying

### CONFORMANCE STANDARDS

VOC compliant in all regulated areas

### TINTING AND BASE INFORMATION

PF7010N White & Pastel Base  
PF7090N Ultra Deep Base\*

\*Must be tinted before use.

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

### PACKAGING

1-Gallon (3.78 L)

### PRODUCT DATA

**PRODUCT TYPE:** 100% Acrylic Latex  
**SHEEN:** Satin  
**VOLUME SOLIDS\*:** 41% +/- 2%  
**WEIGHT SOLIDS\*:** 54% +/- 2%  
**WEIGHT/GALLON\*:** 10.7 lbs. (4.9 kg) +/- 0.2 lbs. (91 g)  
**VOC:** <50 g/L (0.4 lbs./gal.)

\*Product data calculated on product PF7010N.

**COVERAGE:** Approximately 300–350 sq. ft. (28–33 sq. meters) per U.S. gallon (3.78 Liters) on primed, smooth, nonporous surfaces.

Wet Film Thickness: 4.6-5.3 mils  
Wet Microns: 117-135  
Dry Film Thickness: 1.9-2.2 mils  
Dry Microns: 48-56

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing. Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

**DRYING TIME:** Dry time @77°F (25°C) & 50% relative humidity.

To Touch: 2-4 hours  
To Recoat: 8 hours  
Light Foot Traffic: 24 hours

Keep standing water off of painted surface for a minimum of one week. Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

**CLEANUP:** Clean tools with warm, soapy water. Clean spills immediately with a damp cloth.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

### LIMITATIONS OF USE

Apply only when air, surface and product temperatures are above 50°F (10°C) and will remain above 50°F (10°C) for 24 hours. The surface temperature must be at least 5°F (3°C) above the dew point. Do not apply late in the day when dew and condensation are likely to form or if rain is expected within 48 hours. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our website or by calling 1-800-441-9695. PROTECT FROM FREEZING.

**CAUTION:** Surfaces coated with this product may become slippery when wet. For additional slip resistance in areas of pedestrian traffic, add anti-skid texturing material.

Read Label and Safety Data Sheet Prior to Use. See other cautions on last page.

PF7010N Series

**GENERAL SURFACE PREPARATION**

Surface must be clean and dry. Remove all loose and peeling paint, dirt, grease and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough and patched surfaces. Masonry and plaster surfaces must be allowed to cure for 30 days prior to painting. When applied to an uncoated substrate or to bare wood, two coats are required with the first coat acting as the primer. Uncoated substrates, repaired surfaces or lightly stained areas may require additional coats. For severe stains, water marks, and other challenging conditions such as bare metal or chalky surfaces use an appropriate specialty primer.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**CONCRETE/MASONRY:** New concrete and masonry should cure for at least 30 days and preferably 90 days prior to priming. The pH of the substrate must be less than 10 before priming with an alkali resistant primer.

**FERROUS METAL:** The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed with a metal primer.

**WOOD:** Countersink all nails, putty flush with surface. Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting.

**CAUTION:** Surfaces coated with this product may become slippery when wet. For additional slip resistance in areas of pedestrian traffic, add anti-skid texturing material.

**APPLICATION INFORMATION**

Stir thoroughly before using and occasionally when in use. When using more than one can of the same color, intermix to ensure color uniformity.

**Application Equipment:** Apply with a high quality brush, roller, paint pad or by spray equipment. Two coats are suggested for best results.

**Airless Spray:** For airless spray application, use tip size .015" - .021" and pressure range of 1500-2000 psi. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

**Brush:** Polyester/Nylon Brush

**Roller:** 3/16" - 1/2" nap roller cover

**Thinning:** DO NOT THIN

**Permissible temperatures during application:**

Material: 50 to 90°F 10 to 32°C

Ambient: 50 to 90°F 10 to 32°C

Substrate: 50 to 90°F 10 to 32°C

**PRECAUTIONS**

**WARNING! HARMFUL IF INHALED. HARMFUL IF SWALLOWED.** Do not breathe vapor or mist. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2018 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Glidden is a registered trademark and the Glidden Logo is a trademark of the PPG Group of Companies.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-454-3336.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.glidden.com](http://www.glidden.com)

Technical Services  
1-800-GLIDDEN