



### Physical Properties

<b>Appearance</b> Black liquid	<b>Freezability</b> Do not freeze	<b>Specific Gravity @ 77° F (25°C)</b> 1.14
<b>Color</b> Black brown	<b>Maximum VOC</b> 25 g/l	<b>Weight Per Gallon</b> 9.5-9.8 lbs
<b>Flash Point</b> >212° F	<b>Solids By Weight</b> 38.1%	

### Description

**HE175 - DRIVEWAY ASPHALT FILLER & SEALER** is an easy to use combination of finely graded aggregate and petroleum asphalt and water emulsion. Designed to improve traction and appearance. Protects weathered and cracked blacktop pavement. Fills surface cracks up to 1/8". Properly applied, it will not flake, peel, track or crack. Dries to a uniform and long lasting jet black finish. Dries to touch in approximately 4 hours and can be driven on in 24 hours under normal conditions.

### Usage

Recommended for use as a filler and sealer coat for blacktop pavements such as home driveways.

### Coverage

Weathered or unsealed surfaces range from 200-400 sq. ft. per 5 gallon pail. Recently sealed and smooth, tightly compacted surfaces range from 400-500 sq. ft. per 5 gallon pail. Coverage may vary according to surface age and porosity, climate conditions when applying, and method of application.

### Surface Preparation

Pavement surface should be swept clean of dust and loose stone. Remove grease and oil spots and scrub with an asphalt driveway cleaner or detergent. Repair small cracks, fissures, and small holes up to 1/4" with **Henry #305 Crack Filler**. Allow Crack Filler to dry at least 24-48 hours before applying driveway sealer. To repair larger cracks and for leveling, use **Henry #308 Crack Repair**. Allow Crack Repair to cure 24-48 hours before sealing or driving on the repaired area. Use **Henry #304 Pothole Patch** for holes that are too large for **Henry #308 Crack Repair**. Allow Pothole Patch to cure 90 days before sealing. Allow all repairs to cure completely. Follow label directions.

### Application

Stir product thoroughly, 5 to 10 minutes, with a wooden paddle until sealer is of smooth and uniform consistency. Try to apply sealer early in the day to gain maximum benefit of daytime warmth for drying. Apply material with the brush side of a squeegee. Spread out excess sealer on the surface. Smooth out and remove ridges. Work in a 3 or 4 foot area brushing in a cross pattern, first one way then the other, so all pores are filled. Follow consistent pattern for best appearance. Coating should be applied under normal environmental conditions without thinning.

### Precautions

**DO NOT APPLY TOO THICK. A THICK APPLICATION DRIES SLOWLY AND CAN RESULT IN TRACKING. DO NOT USE ON CONCRETE. DO NOT USE ON ASPHALT SURFACES LESS THAN SIX MONTHS OLD.** Do not dilute. Do not apply when temperature is below 50°F (10°C), when temperature will fall below 50°F (10°C) within 24 hours after application or when rain or frost is forecast within 24 hours. On hot days, wetting surface before application is recommended for best results. Be sure to sweep away puddles. When transporting this product, be sure the pail is secured and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

### Cleanup

Clean hands and tools with clean water before emulsion has dried. Dried emulsion can be cleaned with mineral spirits.

## Caution

CAUTION! Close container after each use. Do not heat container or store at temperatures greater than 120°F. DO NOT TAKE INTERNALLY! Use protective measures to avoid contact with eyes and skin. **If swallowed**, CALL PHYSICIAN IMMEDIATELY!**In case of eye contact**, open eyelids wide and flush immediately with plenty of water for at least 15 minutes.

**KEEP OUT OF REACH OF CHILDREN!**

**FOR EXTERIOR USE ONLY!**

**KEEP FROM FREEZING.**

Dispose of container and unused contents in accordance with Local, State and Federal regulations.

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

**Employers** should obtain a copy of the **Material Safety Data Sheet** from your supplier or directly from Henry at the toll free number or website below.

## Product Sizes

5 GALLON (57 lb)

## Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 3 years of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**