



Last Rev Date: 04/11/2013

Physical Properties

Appearance Black liquid	Drying Time @ 50% R.H. 68°F (20°C) Dry to touch in 4 hours	Solids By Weight 42 - 46%
Application Temperature 50°F (10°C) and rising	Flash Point >212 °F (100°C)	Specific Gravity @ 77° F (25°C) 1.14 - 1.20
Brookfield Viscosity 5000-7500 cPs	Freezability Do not freeze	Weight Per Gallon 9.5 - 10.0 lbs
Color Black brown	Maximum VOC 50 g/l	

Description

- Easy-to-stir
- Fills surface cracks up to 1/8 inch
- Dries to the touch in approximately 4 hours. Can be driven on in 24-48 hours under normal conditions

Usage

HE200 - DRIVEWAY ASPHALT SEALER is recommended for use as a filler and sealer coat for blacktop pavements such as home driveways.

Coverage

Coverage is 250-400 sq. ft. (23 to 38 sq. m) per 5 gallon (17L) pail depending on roughness of surface. Coverage may vary according to surface age and porosity, climate conditions when applying and method of application.

Surface Preparation

Pavement surface should be swept clean of loose stone. Dust should be removed from the pavement surface with a garden hose. Remove grease and oil spots and scrub with an asphalt driveway cleaner or detergent. Repair cracks and small holes up to 1/4" with **Henry 305** or **Henry 308 Crack Filler/Repair**. Repair larger cracks (up to 1/2") with **Henry 308 Crack Repair**. For potholes 2" wide or larger use **Henry 304 Pot Hole Patch**. Allow all repairs to cure thoroughly.

Application

Mix thoroughly with wooden paddle in a circular bottom to top fashion. Material may appear brown, but dries to a rich black color. Apply early in the day for maximum benefit of daytime warmth for drying. Apply using brush side of a squeegee or roller. Spread out excess sealer on the surface. Smooth out and remove ridges. Work in a 3 or 4 foot area brushing in a cross pattern so all pores are filled. Follow consistent pattern for best appearance. Coatings should be applied under normal environmental conditions without thinning.

Precautions

Do not mix product with a coal tar pitch emulsion or asphalt/solvent-based sealer. Do not dilute. Do not apply when temperature is below 50°F (10°C) or when rain, frost and temperatures below 50°F (10°C) are forecasted within 48 hours. On hot days, dampen surface before application. Sweep away puddles. Do not use on concrete, or on asphalt surfaces less than six months old.

Do not apply more than one coat. Do not apply too thickly. Applying more than one coat or applying too thickly will cause slow drying and tracking. When transporting this product, be sure the pail is secured and the lid is tight. Do not allow pail to tumble as this may loosen the lid and allow leakage to occur.

Cleanup

To clean emulsion before drying, use clean water. To clean dried emulsion, use biodegradable terpene solvent.

Caution

CAUTION! Close container after each use. **DO NOT TAKE INTERNALLY!** Use protective measures to avoid contact with eyes and skin. **If swallowed, CALL PHYSICIAN IMMEDIATELY! In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION.** Dispose of container and unused contents in accordance with Local, State and Federal regulations.

KEEP OUT OF REACH OF CHILDREN! KEEP FROM FREEZING!

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

EMPLOYERS should obtain a copy of the **Material Data Safety Sheet (MSDS)** from your supplier or directly from the toll free number or website below.

Product Sizes

5 GALLON (50.8 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 4 years of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**