

HCC Holdings, Inc.

4700 West 160th
Cleveland, Ohio 44135

Phone: 800-321-9532
Website: www.Oatey.com



MEGATAPE Professional PTFE Tape

Date: August 2017

Hercules Megatape provides a clean, positive seal on threaded connections. Megatape is an all-purpose thread sealing tape and can be used with plastic, brass, copper, aluminum, stainless steel, galvanized steel or black iron piping. Its high density and 3.5 mil thickness make it the perfect choice for Plumbing Professionals.



APPROVALS & LISTINGS

Meets UL 31 RO and 7N15 MH18499

SPECIFIC APPLICATIONS

Hercules Mega Tape can be used on plastic, brass, copper, aluminum, stainless steel, galvanized steel or black iron piping.

NOT FOR USE WITH LINES CARRYING OXYGEN.

*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at www.Oatey.com.

DIRECTIONS FOR USE

For threads up to 1-½" diameter, use ½" width of thread seal tape. For larger diameter threads, use ¾" or 1" width of thread seal tape. Clean the male and female threads of any oil or dirt. Apply the thread seal tape a minimum of three wraps, using care to wrap in the direction of the thread rotation. Be sure to keep tension on the tape while wrapping. Do not overlap the tape on the ends of the fitting.

WARNINGS OR CAUTIONS

Read all cautions and directions carefully before using this product

PHYSICAL PROPERTIES

Appearance: Gray Tape
 Density: 0.70 to 1.00 g/c3
 Pressure Rating:* 10,000 psi
 Temperature Range: -450° F to 500° F
 Tensile Strength: 1245 to 2500 psi
 Thickness: 0.0035"
 Shelf Life: Indefinite

**Pressure rating is relative to the torque and quality of the threads and the amount of tape used.*

MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #7305E

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of www.Oatey.com

When used for the intended end use application, this product is considered an "article" as defined in OSHA 29 CFR 1910.1200(c).

HMIS® ratings Health: 0
 Flammability: 0
 Physical hazard: 0

SIZE & PACKING

STOCK NUMBER	DESCRIPTION	UPC
15100	½" X 1000", 3.5 mil Thick Grey PTFE Tape	50032628151005
15110	¾" X 1000", 3.5 mil Thick Grey PTFE Tape	50032628151104
15120	1" X 1000", 3.5 mil Thick Grey PTFE Tape	50032628151203