## **VACU-STACK® SPECIFICATIONS**

## vacu-Stack Model VSS-RS

(RAINSEAL™)

## WITH SCREEN AND BUILT-IN RAIN COLLAR

Application: Extra rain protection for round chimneys other than air cooled and for masonry chimneys using the ICP masonry adapter. This is the premier cap for solving common wind-related chimney draft problems caused by conditions such as hills and mountains in the vicinity, tall trees near the chimney, or tall buildings nearby.

Standard Materials: 100% austenitic stainless steel, stainless steel screen.

Alternate materials: Copper and Type 316

stainless steel for marine environments.



MODEL # (1" SCREEN OPENING*)	MODEL # (1/2" SCREEN OPENING*)	INSIDE FLUE DIAMETER (INCHES)	MAXIMUM DIAMETER (INCHES)	SHIPPING WEIGHT (POUNDS)
VSS-4-RS-S	VSS-4-RS-S5	4	8	7
VSS-5-RS-S	VSS-5-RS-S5	5	13	7
VSS-6-RS-S	VSS-6-RS-S5	6	13	9
VSS-7-RS-S	VSS-7-RS-S5	7	13	9
VSS-8-RS-S	VSS-8-RS-S5	8	13	12
VSS-9-RS-S	VSS-9-RS-S5	9	13	14
VSS 9.5-RS-S	VSS-9.5-RS-S5	9.5	13	14
VSS-10-RS-S	VSS-10-RS-S5	10	13	14
VSS-11-RS-S	VSS-11-RS-S5	11	16	22
VSS-11.5-RS-S	VSS-11.5-RS-S5	11.5	16	22
VSS-12-RS-S	VSS-12-RS-S5	12	16	22

SIZES: Custom sizes available up to 48". Call for price and specific requirements.

CHIMNEY TYPES: Single wall, solid pack insulated, Class A, B vent, and square or rectangular masonry chimneys using ICP masonry adapter.

SCREENS: Available as noted above in 1" and 1/2" mesh openings. Check local regulations for what is required in your area.



<sup>\*</sup> Nominal dimension