

**IKO**

TECHNICAL DATA SHEET

STOCK NO. 4540XXX**September 2018**

ARMOUR STARTER

Packaged at 21 strips per bundle, each Armour Starter strip is made using our own quality raw materials to ensure optimum roofing quality, and is compatible with all existing IKO Armourshake shingles. Special algae-inhibiting granules have been added to provide long-lasting algae resistance. Armourstarter is produced in a complete range of color blends to match the Armourshake line. Installation information is printed on the package with easy-to-follow instructions. Conveniently packaged in easy-to-carry lightweight bundles. This shingle meets ASTM D3018 Class A, ASTM D3462, ASTM D3161, ASTM E108 Class A, and CSA A123.5.

CHARACTERISTIC	UNITS	NOMINAL VALUE	TEST METHOD	STANDARD LIMITS
QUANTITY PER PALLET:	-	60	-	N/A
LENGTH:	mm (in)	1000 (39 3/8)	-	± 3 (± 1/8)
WIDTH:	mm (in)	336 (13 1/4)	-	± 3 (± 1/8)
HEADLAP:	mm (in)	50 (2)	-	± 3 (± 1/8)
BUNDLE QUANTITY:	-	21	-	-
COVERAGE PER BUNDLE:	lin. m. (lin. ft.)	21 (68.9)	-	-
EXPOSURE:	mm (in)	152 (6)	-	± 3 (± 1/8)
HEAT RESISTANCE:	-	PASS	*	90°C (192°F)

* Sample shows no sliding or dripping of the bitumen coating when suspended vertically in an oven at 90°C (192°F) for 2 hours.

See also Material Information Sheet – MIS # 1713

The information on this Technical Data sheet is based upon data considered to be true and accurate, based on laboratory tests and production measurements, and is offered solely for the user's consideration, investigation and verification. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible. The manufacturer does not assume any responsibility for any misrepresentation or assumptions the reader may formulate.