



OIL & GREASE EMULSIFIER V600

Features

- Concentrated and must be mixed with water
- Biodegradable and phosphate-free
- Use on metal, fiberglass, vinyl, and masonry surfaces
- Rinses clean with no residue

General Description

Oil & Grease Emulsifier is designed for cleaning walls, floors and equipment. This cleaner is extremely effective in removing oil, grease, fats, blood and animal by-products. It may also be used for cleaning concrete, asphalt, vinyl, metal, plastic, fiberglass, etc.; it is also very effective for cleaning equipment, tools, brushes, rollers and spray equipment.

Recommended For

Corotech® Oil & Grease Emulsifier is designed for cleaning walls, floors and equipment. It may also be used for cleaning concrete, asphalt, vinyl, metal, plastic, fiberglass, etc.; it is also very effective for cleaning equipment, tools, brushes, rollers and spray equipment.

Limitations

Product Information																			
Colors — Standard: N/A	Technical Data^Δ N/A																		
— Tint Bases: N/A	Vehicle Type N/A Pigment Type N/A Volume Solids N/A Coverage per Gallon at (Mixed) 100 Sq. Ft. Recommended Film Thickness (9.3 sq. m.)																		
— Special Colors: N/A	Recommended – Wet N/A Film Thickness – Dry N/A																		
Certification & Qualifications: <p>The product supported by this data sheet is not regulated by coatings VOC rules.</p> <p>Does not apply to LEED (Leadership in Energy and Environmental Design) standards.</p> <p>Suitable for use in USDA inspected facilities</p> <table border="1" style="margin-left: 20px;"> <thead> <tr> <th>VOC REGION</th> <th>COMPLIANT</th> </tr> </thead> <tbody> <tr><td>FEDERAL</td><td>YES</td></tr> <tr><td>OTC</td><td>YES</td></tr> <tr><td>OTCII</td><td>YES</td></tr> <tr><td>CARB</td><td>NO</td></tr> <tr><td>CARB07</td><td>NO</td></tr> <tr><td>UTAH</td><td>YES</td></tr> <tr><td>AZMC</td><td>YES</td></tr> <tr><td>SCAQMD</td><td>NO</td></tr> </tbody> </table>	VOC REGION	COMPLIANT	FEDERAL	YES	OTC	YES	OTCII	YES	CARB	NO	CARB07	NO	UTAH	YES	AZMC	YES	SCAQMD	NO	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint. Dry Time @ 77°F – Tack Free N/A (25°C) @ 50% RH – To Recoat N/A High humidity and cool temperatures will result in longer dry, recoat and service times.
VOC REGION	COMPLIANT																		
FEDERAL	YES																		
OTC	YES																		
OTCII	YES																		
CARB	NO																		
CARB07	NO																		
UTAH	YES																		
AZMC	YES																		
SCAQMD	NO																		
Technical Assistance: Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit www.benjaminmoore.com	Dries By N/A Dry Heat Resistance N/A Viscosity N/A Flash Point N/A Gloss / Sheen N/A Surface Temperature – Min. N/A at Application – Max N/A Thin With Water Clean Up Thinner Clean Water Weight Per Gallon 8.9 lbs. Storage Temperature – Min. 40 °F (4.4 °C) – Max 95 °F (35 °C)																		
	<p style="text-align: center;">Volatile Organic Compounds (VOC)</p> <p style="text-align: center;">157 g/L 1.31 Lbs./Gallon</p>																		

Oil & Grease Emulsifier V600

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Shake well before using.

Corotech® Oil & Grease Emulsifier should be mixed with water before use, 6 parts water to 1 part emulsifier for heavy cleaning requirements and 15 parts water to 1 part emulsifier for light cleaning. A mixed gallon will clean approximately 100 square feet of area. Pour the water and emulsifier mixture onto the surface to be cleaned. Allow this solution to work for 15 to 30 minutes then scrub the surface with a stiff bristled brush. Rinse thoroughly with clean water or pick up residue with a wet/dry vacuum. Repeat the cleaning procedure if necessary.

Clean Up

Clean up with clean water.

Environmental Health & Safety Information

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling. Refer to Safety Data Sheet for additional health and safety information.

3.3% of the mixture consists of ingredient(s) of unknown toxicity.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**