# SAFETY DATA SHEET.

Issuing date 07-May-2015 Revision Date 07-May-2015 Version 1

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 57300 (108A) BLACK OIL

Recommended use of the chemical

and restrictions on use

Product code F01469

Product Type Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use Lubricant.

Uses advised against No information available

Manufactured For:

Kellogg's Professional Products

325 Pearl Street Sandusky, OH 44870

Emergency telephone number

**Chemical Emergency Phone** 

Number

Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

# Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

# DANGER

#### **Hazard Statements**

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance opaque

Physical state Aerosol

Odor Solvent

### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

# **Precautionary Statements - Response**

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

\_\_\_\_\_\_

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

None

### Other information

- · May be harmful in contact with skin
- 1.80829% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # 64742-49-0, COMMERCIAL HEXANES, MAY BE SUBSTITUTED FOR CAS #110-54-3.

Chemical Name	CAS-No	Weight %*
PETROLEUM BITUMEN	8052-42-4	50-60
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
HYDROCARBON SOLVENT	64742-96-7	10-20
HEXANE	64742-49-0	1-10
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	1-10

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

### First aid measures for different exposure routes

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. If symptoms persist, call a physician.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen

may be necessary. If breathing has stopped, contact emergency medical services

immediately.

**Ingestion** Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Drink plenty of water. Call a physician or Poison Control Center immediately.

# Most important symptoms/effects, acute and delayed

Main Symptoms Irritating to skin. Causes eye irritation. Inhalation causing Central Nervous System effects.

Ingestion causing lung damage.

# Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Water fog.Dry chemical. Carbon dioxide (CO2). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Keep away from heat and sources of ignition. Do not smoke. Cool containers / tanks with water spray.

#### Specific hazards arising from the chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

### **Explosion Data**

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Absorb with sand ,clay, or other suitable material. Hard surfaces may be mopped with

water. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Avoid dust formation. Remove all sources of ignition. Keep people away from and upwind of spill/leak.

Take precautionary measures against static discharges.

### **Environmental precautions**

**Environmental precautions** Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in

low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains.

### Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

Clean contaminated surface thereusely. After cleaning, flush away traces with water. Take

Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take

precautionary measures against static discharges.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top

of can.

# Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

**Incompatible products** Strong acids, alkalis, or oxidizing agents.

Aerosol Level 3

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Guidelines** ACGIH TLV **OSHA PEL** NIOSH IDLH **Chemical Name** PETROLEUM BITUMEN TWA: 0.5 ma/m3 benzene soluble Ceiling: 5 mg/m3 fume 15 min 8052-42-4 aerosol fume, inhalable fraction PROPANE/ISOBUTANE/N-BUTANE 74-98-6:IDLH: 2100 ppm 74-98-6: TWA: 1000 ppm 74-98-6:TWA: 1000 ppm 68476-86-8 106-97-8: STEL: 1000 ppm TWA: 1800 mg/m<sup>3</sup> TWA: 1000 ppm 75-28-5: STEL: 1000 ppm (vacated) TWA: 1000 ppm TWA: 1800 mg/m<sup>3</sup> (vacated) TWA: 1800 mg/m<sup>3</sup> 106-97-8:TWA: 800 ppm 106-97-8: (vacated) TWA: 800 TWA: 1900 mg/m<sup>3</sup> 75-28-5:TWA: 800 ppm ppm (vacated) TWA: 1900 mg/m<sup>3</sup> TWA: 1900 mg/m<sup>3</sup> HEXANE TWA: 50 ppm TWA: 500 ppm IDLH: 1100 ppm Skin - potential significant TWA: 1800 mg/m<sup>3</sup> 64742-49-0 TWA: 50 ppm contribution to overall exposure (vacated) TWA: 50 ppm TWA: 180 mg/m<sup>3</sup> by the cutaneous route (vacated) TWA: 180 mg/m<sup>3</sup>

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

### **Exposure controls**

Engineering Measures Showers

Eyewash stations Ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin and body protection** Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and chemical properties

Physical stateAerosolAppearanceOdorSolvent

ColorOdor ThresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Methods</u>

pH No information available
Melting/freezing point No information available
Boiling point/boiling range
Flash Point No information available
No information available
-97 °C / -142 °F

Flash Point -97 °C / -142 °F Based on propellant Evaporation rate No information available

Flammability (solid, gas)

Flammability Limits in Air

upper flammability limit
lower flammability limit
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific Gravity 0.823

Water solubility Practically insoluble

Partition coefficient: n-octanol/waterNo information available
Autoignition temperature No information available

Decomposition temperatureNo information availableViscosityNo information availableExplosive propertiesNo information available

Other information

VOC Content(%) 23.65

# 10. STABILITY AND REACTIVITY

### Reactivity

No data available

## **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

### **Incompatible Materials**

Strong acids, alkalis, or oxidizing agents.

# **Hazardous Decomposition Products**

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

# **Product Information**

**Inhalation** Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness

based on components. May cause irritation of respiratory tract. Avoid breathing vapors or

Not applicable

mists.

**Eye contact** Irritating to eyes. Avoid contact with eyes.

**Skin contact** Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin

contact may defat the skin and produce dermatitis. Avoid contact with skin.

Ingestion May be harmful if swallowed. Aspiration into the lungs during swallowing may cause serious

lung damage which may be fatal.

**Component Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM BITUMEN 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	-
HYDROCARBON SOLVENT 64742-96-7	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.28 mg/L (Rat)4 h
HEXANE 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg(Rabbit)	= 73680 ppm (Rat) 4 h

## Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Irritating to respiratory system. Irritating to skin and eyes. May be harmful or fatal if

ingested.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Eye damage/irritation Irritating to eyes.

Irritation Irritating to eyes, respiratory system and skin.

Sensitization None known. **Germ Cell Mutagenicity** None known.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
PETROLEUM BITUMEN	-	Group 2B	-	-
8052-42-4		·		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic

toxicity (single exposure)

Specific target organ systemic

toxicity (repeated exposure)

No information available.

**Target Organ Effects** Eyes, Respiratory system, Skin.

**Neurological effects** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

May cause respiratory irritation. May cause drowsiness and dizziness.

May be fatal if swallowed and enters airways. **Aspiration hazard** 

# Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 1.80829% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

6371 mg/kg ATEmix (oral) ATEmix (dermal) 2597 mg/kg

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	-	-	-	-
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical Name	log Pow
PETROLEUM BITUMEN 8052-42-4	6
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods It must undergo special treatment, e.g. at suitable disposal site, to comply with local

regulations.

**Contaminated packaging** Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

# 15. REGULATORY INFORMATION

### **International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM BITUMEN	Х	Х	Х	Х	Х	Х	Х	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	X	Not listed	X	X	X	Х
HYDROCARBON SOLVENT	Х	Х	X	Not listed	Х	Х	Х	Х
HEXANE	Χ	X	X	X	X	X	X	X
NAPHTHENIC OIL, SEVERLY HYDROT	Х	Х	Х	Х	X	Х	Х	Х

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

# SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

# **U.S. State Regulations**

### **California Proposition 65**

This product does not contain any known Proposition 65 chemicals.

### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM BITUMEN	X	X	X
8052-42-4			

EPA Pesticide Registration Number Not applicable

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

# **16. OTHER INFORMATION**

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards -

HMIS Health Hazard 2\* Flammability 4 Physical Hazard 1 Personal protection X Chronic Hazard Star Legend Chronic Health Hazard Repeated or prolonged exposure may cause central nervous system damage

Prepared By American Jetway

American Jetway 34136 Myrtle Street Wayne, MI 48184

Tel.734-721-5930

Issuing date07-May-2015Revision Date07-May-2015

**Revision Note** 

No information available

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**