

www.rustoleum.com 11 Hawthorn Pkwy., Vernon Hills, IL 60061 1-877-815-2536



MULTI-PURPOSE PRESSURE WASHER CONCENTRATE

Directions for Use:

IMPORTANT-READ ENTIRE LABEL BEFORE USE

- 1. When using a pressure washer to clean painted surfaces, please be aware that water pressure alone may remove paint, or highlight existing discoloration caused by the sun's UV rays.
- 2. From the garden hose, rinse any nearby plants with clean water.
- 3. Always test on an inconspicuous area first.
- 4. Any overspray can be neutralized with large volumes of water.
- 5. For heavy oil and grease stains (such as on driveways and garage floors), pour product directly onto the stain. Allow to penetrate for 5 to 10 minutes, then follow normal application procedures.
- 6. In case of severe oil and grease stains on porous surfaces; oil may bleed to the surface or leave a residual stain. Repeat applications may lighten stains, but not remove stains completely.
- 7. Do not mix this product with any other chemicals.

General Directions:

- 1. Rinse surrounding plants with water, before and after application.
- 2. Wet the surface to be cleaned, prior to applying the product.
- 3. Place detergent application siphon tube and screen filter directly into container. Open meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full strength) into pressure washer.
- 4. Spray at low pressure onto a wet surface.

If you have any questions or concerns regarding this product please contact Krud Kutter customer support at (800) 466-7126



www.rustoleum.com 11 Hawthorn Pkwy., Vernon Hills, IL 60061 1-877-815-2536

- 5. On vertical surfaces, always spray from the top down.
- 6. Allow product to remain on the surface for 3 to 5 minutes to penetrate. Do not allow product to dry on surface.
- 7. Remove siphon tube from solution and rinse surface with high-pressure spray thoroughly. 8. Flush siphon tube with clean water prior to storage.

NOTE: Can be diluted 1:10 with water for use in a pump up sprayer