



www.rustoleum.com

11 Hawthorn Pkwy., Vernon Hills, IL 60061 1-877-815-2536



CONCRETE & DRIVEWAY PRESSURE WASHER

Directions for Use:

Important - Read Entire Label Before Use

1. When using a pressure washer to clean painted surfaces, please be aware that water pressure alone may remove paint, or highlight existing discoloration caused by the sun's UV rays.
2. From the garden hose, rinse any nearby plants with clean water.
3. Always test on an inconspicuous area first.
4. Any overspray can be neutralized with large volumes of water.
5. In case of severe oil and grease stains on porous surfaces, oil may bleed to the surface or leave a residual stain. Repeat applications may lighten stains, but not remove stains completely.
6. Do not mix this product with any other chemicals.

Pressure Washer Application

1. Rinse surrounding plants with water, before and after application.
2. Wet the surface to be cleaned, prior to applying the product.
3. Place detergent application siphon tube and screen filter directly into container. Open meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full strength) into pressure washer.
4. Spray at low pressure onto a wet surface.

If you have any questions or concerns regarding this product please contact Krud Kutter customer support at (800) 466-7126



www.rustoleum.com

11 Hawthorn Pkwy., Vernon Hills, IL 60061 1-877-815-2536

5. Allow product to remain on the surface for 5 to 10 minutes to penetrate. Do not allow product to dry on surface.
6. Remove siphon tube from solution and rinse surface with high pressure spray thoroughly.
7. Flush siphon tube with clean water prior to storage.

Heavy Stain Removal

1. Wet the surface to be cleaned, prior to applying the product.
2. Pour KRUD KUTTER directly from container on area to be cleaned.
3. Work into surface with a stiff brush or broom.
4. Wait 5 to 10 minutes, then scrub again.
5. Rinse surface thoroughly with water or power wash to remove all cleaner residue.

NOTE: If cleaner dries before rinsing, apply more cleaner, scrub and rinse. When using cleaner on asphalt, some of the natural oils found in asphalt may be removed along with grease and oil. Test a small amount in an inconspicuous area to ensure compatibility. Resealing of asphalt may be necessary after cleaning.

If you have any questions or concerns regarding this product please contact Krud Kutter customer support at (800) 466-7126