



**KRUD KUTTER®
THE MUST FOR RUST
RUST REMOVER & INHIBITOR GEL**

DESCRIPTION AND USES

Krud Kutter® The Must for Rust is a unique rust remover and inhibitor gel that removes rust and protects metal in one step. The gel formula clings to metal surfaces, penetrates into voids on the metal surface and dissolves rust and oxidation through chemical action. Small rust-inhibiting crystals are formed and become integral with the surface molecules of the metal to resist future rusting.

PRODUCTS

SKU	Description
305982	32 oz. Trigger Sprayer
315318	32 oz. Trigger Spray

PRODUCT APPLICATION

DIRECTIONS

IMPORTANT – READ ENTIRE LABEL BEFORE USE

Always test on an inconspicuous area first. For best results apply in ambient temperature of 70°F or above. On metal, maintain wet solution on surface to remove rust. Once the rust is dissolved, rinse or wipe the surface, and wait one hour or more before painting. Do not allow remover to dry on painted surfaces. For improved paint adhesion on clean metal surfaces, apply solution, let stand for 5-10 minutes and rinse or wipe the surface with a clean cloth. To use as a rust inhibitor on unpainted metal, wipe the surface with a clean cloth after the rust is dissolved. The remover will then protect bare metal against rust for up to 12 months. Do not use on non-metal surfaces.

Remove any oil, grease or dirt from the surface to be treated. On heavily rusted surfaces, remove any loose rust particles with a wire brush. Rinse the metal with water to break the surface tension and wash away loose dirt. Turn sprayer to “SPRAY” position and apply remover liberally to the surface. Continue to apply the remover as needed, keeping the surface wet until the rust is dissolved. Disassemble units composed of moveable parts before applying remover. Clean parts and allow to dry before reassembling.

PRODUCT APPLICATION (cont.)

DIRECTIONS (cont.)

DISSOLVING RUST FROM IRON OR STEEL: Turn sprayer to “SPRAY” position and apply remover liberally to the surface. Continue to apply the remover as needed, keeping the surface wet until the rust is dissolved. Chemical action begins at once. Cleaning time will vary according to the severity of the rust. Medium to light rust will be dissolved in 10-30 minutes or less, while heavier deposits may require a second application. Once the rust is dissolved, rinse with water and wipe the surface dry. After one hour or more, the surface is ready to be painted.

ALUMINUM/CHROME: Apply the remover to wet surface. Allow time to dissolve the rust; then rinse away with clean water and buff dry with a cloth.

GALVANIZED SURFACE: Where surface is unbroken, treat as suggested for aluminum. Where rust is showing at the surface, treat as for iron or steel. New galvanizing is properly prepared for painting by applying the remover, allowing 3-5 minutes to work and then wiping the surface clean.

DANGER! Contains phosphoric acid. Causes eye burns and skin irritation. May be harmful if swallowed. **Use only with adequate ventilation.** Avoid breathing vapors or spray mist. Do not get into eyes. Wash thoroughly after handling. **FIRST AID:** In case of eye or skin contact, flush immediately with plenty of fresh water for at least 15 minutes. Remove contaminated clothing. Get medical attention immediately. If swallowed, **DO NOT induce vomiting.** Get medical attention immediately. In case of spillage, absorb with an inert material and dispose of in accordance with applicable regulations.

KEEP OUT OF REACH OF CHILDREN.



TECHNICAL DATA

KRUD KUTTER® THE MUST FOR RUST - RUST REMOVER & INHIBITOR GEL

PHYSICAL PROPERTIES

		THE MUST FOR RUST – RUST REMOVER & INHIBITOR GEL
Composition		Phosphoric Acid and other Proprietary Ingredients
Weight	Per Gallon	9.90 lbs.
	Per Liter	1.18 kg
Solids	By Weight	34.5%
	By Volume	22.9%
Color		Light Yellow
pH		1.0-2.0
VOC		0% by weight
Practical Coverage		Varies with type of surface and severity of rust
Shelf Life		7 years
Flash Point		200°F (93°C)
Danger!		Contains phosphoric acid. Causes eye burns and skin irritation. May be harmful if swallowed. Use only with adequate ventilation. Avoid breathing vapors or spray mist. Do not get into eyes. Wash thoroughly after handling. FIRST AID: In case of eye or skin contact, flush immediately with plenty of fresh water for at least 15 minutes. Remove contaminated clothing. Get medical attention immediately. If swallowed, DO NOT induce vomiting. Get medical attention immediately. In case of spillage, absorb with an inert material and dispose of in accordance with applicable regulations. KEEP OUT OF REACH OF CHILDREN.
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.