

SAFETY DATA SHEET

1. Identification

Product identifier KILZ® Stainblocking Color Changing Ceiling Paint - White

Other means of identification

Product code 6800

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Masterchem Industries LLC
3135 Old Highway M
Imperial, MO 63052-2834

Telephone 636-942-2510

Emergency telephone +1 760 476 3962
+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Specific target organ toxicity, repeated exposure Category 2 (kidney)

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause damage to organs (kidney) through prolonged or repeated exposure.

Precautionary statement

Prevention Do not breathe mist/vapors.

Response Get medical advice/attention if you feel unwell.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Limestone	1317-65-3	7 - 13
Titanium dioxide	13463-67-7	7 - 13
Cristobalite	14464-46-1	1 - 5
Diatomaceous Earth (Flux calcined)	68855-54-9	0.5 - 1.5
Ethylene glycol	107-21-1	0.5 - 1.5

Quartz (SiO ₂)	14808-60-7	0.1 - 1
Composition comments	<p>All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.</p> <p>The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.</p>	
4. First-aid measures		
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.	
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.	
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.	
Ingestion	Rinse mouth. Get medical attention if symptoms occur.	
Most important symptoms/effects, acute and delayed	Edema. Prolonged exposure may cause chronic effects.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.	
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
5. Fire-fighting measures		
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.	
General fire hazards	No unusual fire or explosion hazards noted.	
6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures	<p>Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.</p>	
Methods and materials for containment and cleaning up	<p>This product is miscible in water.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.</p>	
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.	
7. Handling and storage		
Precautions for safe handling	Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.	
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).	

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	TWA	0.05 mg/m3
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.05 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
Limestone (CAS 1317-65-3)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
Limestone (CAS 1317-65-3)	TWA	5 mg/m3 10 mg/m3	Respirable. Total
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Skin protection	
Other	Wear suitable protective clothing. Use of an impervious apron is recommended.
Respiratory protection	If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Liquid.
Color	White.
Odor	Slight.
Odor threshold	Not available.
pH	7 - 10
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 99 °F (> 37.2 °C)
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.37
Solubility(ies)	
Solubility (water)	Soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	50 - 140 KU at 25°C
Other information	
Density	11.38 lbs/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	21 g/l (excluding water) (Coating) 46 g/l (including water) (Material)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Edema. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Ethylene glycol (CAS 107-21-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	9530 mg/kg
Quartz (SiO ₂) (CAS 14808-60-7)		
<u>Chronic</u>		
Inhalation		
LOEC	Human	0.0563 mg/m ³
Titanium dioxide (CAS 13463-67-7)		
<u>Acute</u>		
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Due to the form of the product, exposure to the potentially carcinogenic components is not expected.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1)	1 Carcinogenic to humans.
Quartz (SiO ₂) (CAS 14808-60-7)	1 Carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Cristobalite (CAS 14464-46-1)	Known To Be Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.
Quartz (SiO ₂) (CAS 14808-60-7)	Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Cristobalite (CAS 14464-46-1)	Cancer
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	Cancer
Quartz (SiO ₂) (CAS 14808-60-7)	Cancer

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	May cause damage to organs (kidney) through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No data available.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylene glycol (CAS 107-21-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Cristobalite (CAS 14464-46-1)	Cancer
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	Cancer
Quartz (SiO ₂) (CAS 14808-60-7)	Cancer
Cristobalite (CAS 14464-46-1)	lung effects
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	lung effects
Quartz (SiO ₂) (CAS 14808-60-7)	lung effects

Cristobalite (CAS 14464-46-1)	immune system effects
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	immune system effects
Quartz (SiO2) (CAS 14808-60-7)	immune system effects
Cristobalite (CAS 14464-46-1)	kidney effects
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)	kidney effects
Quartz (SiO2) (CAS 14808-60-7)	kidney effects

Toxic Substances Control Act (TSCA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylene glycol	107-21-1	0.5 - 1.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations

US. Massachusetts RTK - Substance List

Cristobalite (CAS 14464-46-1)
Ethylene glycol (CAS 107-21-1)
Limestone (CAS 1317-65-3)
Quartz (SiO2) (CAS 14808-60-7)
Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Cristobalite (CAS 14464-46-1)
Ethylene glycol (CAS 107-21-1)
Limestone (CAS 1317-65-3)
Quartz (SiO2) (CAS 14808-60-7)
Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Cristobalite (CAS 14464-46-1)
Diatomaceous Earth (Flux calcined) (CAS 68855-54-9)
Ethylene glycol (CAS 107-21-1)
Limestone (CAS 1317-65-3)
Quartz (SiO2) (CAS 14808-60-7)
Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Cristobalite (CAS 14464-46-1)
Ethylene glycol (CAS 107-21-1)
Limestone (CAS 1317-65-3)
Quartz (SiO2) (CAS 14808-60-7)
Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

Issue date 10-September-2020
Revision date -
Version # 01

HMIS® ratings

Health: 2*
Flammability: 0
Physical hazard: 0

List of abbreviations

DOT: Department of Transportation (49 CFR 172.101).
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
LD50: Lethal Dose, 50%.
LOEC: Lowest observable effect concentration.
MARPOL: International Convention for the Prevention of Pollution from Ships.
PEL: Permissible Exposure Limit.
STEL: Short-Term Exposure Limit.
TWA: Time Weighted Average Value.

References

HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer

Masterchem Industries LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.