



CONTRACTOR ALL-SURFACE ENAMEL

AEROSOL

Product Numbers: 5809, 5810, 5811, 5812, 5813, 5814, 5815, 5816, 5817, 5818, 5819, 5820

PRODUCT DESCRIPTION	APPLICATION CONT.	CAUTIONS
<p>Contractor All-Surface Enamels have superior bonding qualities on a variety of surfaces. Use on metal, wicker, wood, most plastics, and masonry. Dries to touch in 25 minutes and can be handled in 2 to 3 hours.</p> <p>Features:</p> <ul style="list-style-type: none"> - Superior coverage - Resists rust - Larger, contractor-size can 	<p>spraying until only clear gas comes out. If button becomes clogged, wear eye protection, wipe off the button opening with lacquer thinner - DO NOT stick pin in spray button opening. Dispose in accordance with local, state or federal regulations.</p> <p>NOTE: EZ Touch Fanspray Nozzle requires 50% less finger pressure to operate than a regular valve. Its fast delivery allows greater coverage with less overspray. Its elongated pattern is manipulated like a professional spray gun.</p>	<p>CONTAINS KETONES, TOLUENE AND XYLENE.</p> <p>EXTREMELY FLAMMABLE. Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</p>
SURFACE PREPARATION	CHARACTERISTICS	
<p>WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead. Surface must be free of grease, dust, dirt and wax. Remove loose paint from surface. Scuff sand rusted, glossy or hard surfaces.</p>	<p>Color: Red, Blue, Green, Orange, Yellow, Almond, Gray, White, Black</p> <p>Coverage: 30 Square Feet</p> <p>Drying Time, @ 77°F, 50% RH: <i>Drying time and recoat times are temperature, humidity, and film thickness dependent.</i></p> <p>Touch: 25 minutes</p> <p>To Handle: 2-3 hours</p> <p>Recoat: Before 2 hours; after 48 hours</p> <p>Vehicle Type: Alkyd</p> <p>Finishes: Gloss, Flat</p> <p>VOC: 60 - 85%</p> <p>Volume Solids: 8 - 13%</p> <p>Weight Solids: 14 - 25%</p> <p>Flash Point: -20°F</p> <p>Gloss (60° Gloss Reading): Gloss 85+, Flat 0 to 5</p>	
APPLICATION		PERFORMANCE TESTING
<p>Product should be sprayed in a well-ventilated area. Use at room temperature 70°F for best results. Avoid high humidity. Shake until ball inside can breaks loose and rattles. Hold can at top and swing bottom of can in a circle for 3 minutes, making can ball travel around groove of can. Hold can 6 to 8 inches from surface. Never spray with valve only partly open. Move can with short 'dusting' strokes, allowing paint to become tacky between light mist coats. Clean valve by holding can upside down and</p>		<p>Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse.</p>