



Revision Number: 002.0

Issue date: 05/25/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>LePage No More Nails Heavy Duty Construction Adhesive</b>	<b>IDH number:</b>	2048231
<b>Product type:</b>	Acrylic Adhesive	<b>Region:</b>	United States
<b>Restriction of Use:</b>	None identified	<b>Contact information:</b>	
<b>Company address:</b>	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com		
Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067			

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**WARNING:** CAUSES SERIOUS EYE IRRITATION.

### HAZARD CLASS

EYE IRRITATION

### HAZARD CATEGORY

2A

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Wash affected area thoroughly after handling. Wear eye and face protection.
<b>Response:</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	30 - 40
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Distillates (petroleum), hydrotreated light	64742-47-8	0.1 - 1
Quartz (SiO <sub>2</sub> ), <1% respirable	14808-60-7	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice.
<b>Skin contact:</b>	Wash with soap and water. If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Seek medical advice.
<b>Symptoms:</b>	See Section 11.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	carbon dioxide, foam, powder, water spray jet, fine water spray
<b>Special firefighting procedures:</b>	Not available.
<b>Unusual fire or explosion hazards:</b>	None known.
<b>Hazardous combustion products:</b>	Oxides of carbon.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	None known
<b>Clean-up methods:</b>	Scrape up as much material as possible. Clean residue with soap and water.

#### 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes. Avoid prolonged or repeated skin contact with this material. Do not taste or swallow. Keep out of the reach of children.
<b>Storage:</b>	Protect from freezing. Store in a cool, dry area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m <sup>3</sup> TWA Total dust.	5 mg/m <sup>3</sup> PEL Respirable fraction. 15 mg/m <sup>3</sup> PEL Total dust.	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m <sup>3</sup> TWA Inhalable dust. 3 mg/m <sup>3</sup> TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m <sup>3</sup> TWA	None	None
Distillates (petroleum), hydrotreated light	None	100 ppm (400 mg/m <sup>3</sup> ) PEL	None	None
Quartz (SiO <sub>2</sub> ), <1% respirable	0.025 mg/m <sup>3</sup> TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m <sup>3</sup> TWA Respirable. 0.05 mg/m <sup>3</sup> TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m <sup>3</sup> OSHA_ACT (Respirable dust.) 0.05 mg/m <sup>3</sup> PEL Respirable dust.	None	None

**Engineering controls:**

Not normally needed.

**Respiratory protection:**

No personal respiratory protective equipment normally required.

**Eye/face protection:**

No special measures required if used properly.

**Skin protection:**

No special measures required if used properly.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Solid
<b>Color:</b>	White
<b>Odor:</b>	Acrylic
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	8.5
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	> 100 °C (> 212°F)
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.345 (Water = 1)
<b>Vapor density:</b>	0.62 (Air = 1)
<b>Flash point:</b>	Not classified as a flammable solid per DOT Classification Guidelines Part 173 Appendix H 7/10/2002.
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	1 (Water = 1)
<b>Solubility in water:</b>	emulsifiable
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	0.1 %; 27 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
<b>Viscosity:</b>	2,500,000 mPa.s
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	None known
<b>Incompatible materials:</b>	Strong acids and oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	None known.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Eyes, Skin

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	Not a relevant route of exposure. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
<b>Skin contact:</b>	Prolonged and/or repeated skin contact with this product may cause irritation.
<b>Eye contact:</b>	May cause irritation.
<b>Ingestion:</b>	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Distillates (petroleum), hydrotreated light	None	Irritant, Lung
Quartz (SiO <sub>2</sub> ), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Distillates (petroleum), hydrotreated light	No	No	No
Quartz (SiO <sub>2</sub> ), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

<b>Recommended method of disposal:</b>	Dispose of according to Federal, State and local governmental regulations.
<b>Hazardous waste number:</b>	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of Ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

<b>Proper shipping name:</b>	Not regulated
<b>Hazard class or division:</b>	None
<b>Identification number:</b>	None
<b>Packing group:</b>	None

#### International Air Transportation (ICAO/IATA)

<b>Proper shipping name:</b>	Not regulated
<b>Hazard class or division:</b>	None
<b>Identification number:</b>	None
<b>Packing group:</b>	None

#### Water Transportation (IMO/IMDG)

<b>Proper shipping name:</b>	Not regulated
<b>Hazard class or division:</b>	None
<b>Identification number:</b>	None
<b>Packing group:</b>	None

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

<b>TSCA 8 (b) Inventory Status:</b>	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
<b>TSCA 12 (b) Export Notification:</b>	None above reporting de minimis
<b>CERCLA/SARA Section 302 EHS:</b>	None above reporting de minimis. Acrylamide (CAS# 79-06-1).
<b>CERCLA/SARA Section 311/312:</b>	None
<b>CERCLA/SARA Section 313:</b>	None above reporting de minimis.
<b>California Proposition 65:</b>	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.

#### Canada Regulatory Information

<b>CEPA DSL/NDL Status:</b>	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 2,3,8,11,15,16

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 05/25/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.