



TECHNICAL DATA SHEET



No More Nails® All-Purpose Construction Adhesive

Description: LePage No More Nails All-Purpose construction adhesive is a premium quality, latex-based adhesive for interior construction and multi-purpose use. It is formulated to provide high strength and water resistant bonds. It greatly reduces the need for nails and screws in many applications. No More Nails fills minor gaps on uneven surfaces, dries clear and is paintable. The unique pressure pack dispenser is convenient and easy to use by eliminating the need for a caulking gun.

Available As:

Item #	Size	Package
1673141	170 g	Pressure Pack

Features & Benefits:

- High Instant Grab – No Clamping Required
- Dries Clear
- Water Resistant
- Water-Based Adhesive - Low Odor and Easy Clean-Up
- Unique Pressure Pack Eliminates Need for Caulking Gun

Recommended For:

LePage No More Nails All-Purpose bonds a variety of construction materials, such as wood or metal studs, drywall, masonry, glass and ceramics, carpet and carpet grippers, polystyrene and polyurethane foam board, cork, PVC, decorative wall trim and molding, plywood, stainless steel, plaster, stone and concrete.

For Best Results:

Not suitable for the following applications:

- Bonding two non-porous surfaces (at least one surface should be porous)
- Continuously wet areas or water immersion.
- Use on metals that will corrode, mirrors, natural marble (causes staining), polyethylene, polypropylene, nylon, polytetrafluoroethylene (PTFE) / Teflon® or on Cement board (Durock®)
- Exterior use (unless protected from the elements)

Coverage:

For an 170 g pressure pack:

- A 6 mm (1/4") bead extrudes approximately 5.2 m (17.1 ft)
- A 9.5 mm (3/8") bead extrudes approximately 2.3 m (7.6 ft)



TECHNICAL DATA SHEET

Typical Uncured Physical Properties:

Color:	White (Dries clear)	
Appearance:	Thick paste	
Base:	Synthetic latex	
Odor:	Minimal	
% Solids:	50%	
Specific Gravity:	1.03 to 1.07	
Flash Point:	>93°C (200°F)	
VOC Content:	<0.5% by weight	CARB
	37 g/l	SCAQMD rule 1168
Shelf Life:	24 months from date of manufacture (unopened)	
Lot Code Explanation:	YYDDD	
Stamped on bottom edge of cartridge body	YY= Last two digits of year of manufacture	
	DDD= Day of manufacture based on 365 days in a year	
	Example: 14061 = 61 st day of 2014 = March 2, 2014	

Typical Application Properties:

Application Temperature:	Apply and cure above 10°C (50°F)	
Open Time:	15 minutes*	@25°C (77°F) and 50% R.H
Repositioning Time:	15 minutes*	@25°C (77°F) and 50% R.H
Initial Cure Time:	24 hours*	@25°C (77°F) and 50% R.H
Full Cure:	7 to 14 days*	
	*Times are dependent on temperature, humidity, porosity of surface bonded and amount of adhesive used	
Initial Tack:	25 g/cm ²	

Typical Cured Performance Properties:

Color:	Clear	
Cured Form:	Non-flammable solid	
Service Temperature:	-18°C (0°F) to 50°C (122°F)	
Water Resistant:	Yes	
Paintable:	Yes	
Sandable:	No	
Bond Strength:	APA AFG-01 – Test C	
Douglas Fir to Dry Lumber	1.97 N/mm ² (285 psi)	

Directions:

Tools Typically Required:

Utility knife, caulking gun.

Safety Precautions:

Wear gloves and wash hands after use.

Preparation:

The temperature of the adhesive, the surfaces and the working area must be above 10°C (50°F). One surface must be porous. Surfaces must be clean, dry and free of frost, grease, dust and other contaminants. To obtain maximum adhesion, surfaces should be flat to provide adequate contact. Painted surfaces must be well cured and free of loose paint. Sand glossy surfaces to a dull finish. Pre-fit all materials before applying adhesive. To open the container, tear the black strip off of the red area marked "OPEN". Pull off the red cap from the nozzle and turn the nozzle clockwise 180°. Slide the red tab marked "OPEN" from left to right to regulate the flow. Sliding the tab all the way to the right will deliver the maximum amount of flow and all the way to the left will close the dispenser.

Application:

Product applies white then dries clear. To dispense product, press the red lever. Apply a continuous bead to one of the surfaces then press material firmly into place within 15 minutes. Repositioning time is approximately 15 minutes, depending on bead size. For larger areas such as panels and drywall, apply adhesive around the perimeter 3 cm (1") in from the edge and vertically



TECHNICAL DATA SHEET

every 15 cm (6"). Alternatively apply a continuous bead to all furring strips, studs and top and bottom plates. When applying materials to a vertical surface, the maximum vertical load the adhesive is safely rated for on a porous substrate is 10 grams/cm² (20 lbs/ft²) of bond area. No bracing is usually required, however, use clamps or other means of support for materials that exceed the maximum vertical load to ensure maximum contact for 24 hours or until dry. For exterior use, protect the cured adhesive from sun, rain and snow by painting it or with structural coverings that allow good air circulation.

Clean-up:

Clean tools and uncured adhesive residue immediately with warm water and soap. Cured adhesive may be carefully cut away with a sharp-edged tool.

Storage & Disposal:

DAMAGED BY FREEZING. Store at room temperature in a dry, heated area. Use an approved hazardous waste facility for disposal.

Label Precautions:

CAUTION. IRRITANT. MAY IRRITATE EYES AND SKIN. Do not get in eyes or on skin or clothing. **KEEP OUT OF REACH OF CHILDREN. FIRST AID TREATMENT:** Contains isoparaffinic solvent. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse well with water for at least 15 minutes. If on skin, rinse well with water.

Refer to Material Safety Data Sheet (MSDS) for further information.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



LePage Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Canada Corporation - Professional & Consumer Adhesives Headquarters – Mississauga, ON L5N 6C3
www.henkelna.com

Revision Date: 03/19/2015 Supercedes: 12/02/2013 Ref. #: 1585430