



Premium Quality
Adhesives

Leech Products

Post Office Box 2147
Hutchinson, KS 67504-2147

www.leechadhesives.com

620.669.0145
800.992.9018
FAX 620.669.1183

sales@leechadhesives.com

TECHNICAL DATA SHEET

LEECH *Real* WOOD FILLER

PRODUCT DESCRIPTION

Real Wood Filler is a resin-based wood filler, developed for the plywood and furniture industries, used to repair defects in plywood, furniture, laminated beams, cabinet work, and other woodworking applications. It molds like putty and is consistent, uniform, waterproof and fast-setting with minimal shrinkage. Made with genuine wood flour, Real Wood Filler can be sanded, stained, sawed, planed or drilled like ordinary wood.

WHERE TO USE/APPLICATIONS

Use to fill cracks or holes in wood. Spread evenly into cracks or hole, let dry and sand smooth to surface repaired. Paint or stain to match wood surface.

FEATURES AND BENEFITS

ACTS LIKE REAL WOOD- saw, drill, sand, plane and nail

INTERIOR/EXTERIOR- use indoors or outdoors

WON'T CRACK OR SHRINK-spread evenly into cracks and holes without crumbling or cracking

SUPERIOR STRNGTH- hard finish with little or no shrinkage

QUALITY FINISH- takes stains and paints evenly with minimal sanding

TECHNICAL INFORMATION

Physical properties

Color: Natural

VOC: 215 gram/liter

Solvent: Acetone and Methyl Ethyl Ketone

Density: 12 to 13 lbs. /gal

Solids: 75% +/- 1.0% (by weight)



Vehicle: Nitrocellulose Lacquer
Premium Quality
Adhesives

Leech Products

Post Office Box 2147
Hutchinson, KS 67504-2147

www.leechadhesives.com

620.669.0145
800.992.9018
FAX 620.669.1183

sales@leechadhesives.com

Application temperature: 10 to 80° F (4 to 27° C)
Service temperature: 10 to 150° F (-12 to 66° C)
Storage temperature: 45 and 85° F (7 and 29° C)
Freeze/thaw stability: Does not freeze
Shelf life: 1 year

DIRECTIONS AND APPLICATION NOTES

Read all directions before using and test a small area before full use.

- Step 1 For best adhesion, cracks or defects should be clean and dry.
- Step 2 Press wood filler firmly into defect by hand, or with putty knife.
- Step 3 Lower temperatures require longer drying periods.
- Step 4 When dry, sand flush with surrounding surfaces.
- Step 5 Surfaces may be painted, varnished, lacquered, waxed or shellacked when wood filler is dry.
- Step 6 Close container after each use.

For technical assistance, call 800-992-9018

Leech Real Wood Filler can be drilled, nailed, planed, or sawed like ordinary wood.

Sizes

Gallon, Quart, Pint, 8 oz., 4 oz. and 1.25 oz. .tubes.

HEALTH AND SAFETY

Before working with this product, read and become familiar with information concerning hazards, proper use and handling, SDS is available on line at: www.leechadhesives.com

LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including without limitation, the implied warranty of merchantability and implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. The warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or call 800-992-9018. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.