

Warning

DANGER: VAPOR HARMFUL. FLAMMABLE. EYE & SKIN IRRITANT. Do not swallow. Do not breathe fumes. Do not use near heat, sparks or flames. Do not smoke. Do not get in eyes. Do not get on skin or clothing. **KEEP OUT OF REACH OF CHILDREN.** Wear safety glasses and chemical resistant gloves. Use only in a well-ventilated area.

Contains toluene.

FIRST AID: If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air.


Warranty

Limited Lifetime Warranty: Sashco warrants this product will substantially meet published specifications on the date of sale. If it fails to do so, return unused portion with original sales receipt for replacement or refund, at Sashco's sole option. These are purchaser's sole and exclusive remedies for any breach of warranty. Purchaser must determine suitability of product for purchaser's specific needs and assumes all risk associated with its use. Sashco will not be liable for direct or indirect damages.

Except as stated above there are no warranties for this product. The foregoing express warranty is in lieu of all other warranties, express or implied, including without limitation implied warranties of merchantability or fitness for a particular purpose, which warranties are specifically excluded and disclaimed. This Limited Warranty gives you specific legal rights. You may have other rights which vary from state to state. Some states do not allow exclusion of implied warranties in consumer or other sales, limitations on the duration of implied warranties, or exclusion or limitation of incidental or consequential damages. Thus, the limitations or exclusions contained above may not apply to you depending upon your specific circumstances.

Alyster Plunger

10.5 cartridges come with Sashco's unique Alyster plunger. A flexible telescopic diaphragm not only stops material flow, it actually pulls material back into the nozzle!



- **Tight Seal** – Increases shelf life and minimizes leakage.
- **Stop Flow** – The flexible telescopic diaphragm assures that material flow will stop when caulk gun pressure is released.

Typical Properties

PROPERTY	VALUE
Colors	Clear & White
Packaging	10.5 oz. plastic cartridges, 5 oz. squeeze tubes
Paintability	With latex paint/stain after 24-48 hours or oil-base paint/stain after 3-4 weeks
Joint Size	Maximum 2"
Clarity (NTU)	< 13
Radon Barrier	Stops 94%
Application Range	0°F to 120°F (-18°C to 49°C) surface temperature
Service Range	-30°F to 200°F (-34°C to 93°C)
Freeze-thaw Stability	Won't freeze
Tensile Properties	Recovery at 50% stretch: 96% in 1 minute Recovery at 100% stretch: 96% in 1 minute
VOC	Clear ¹ & White ^{3,4} Cartridge: ≤380 g/L, <43 wt% Clear ² & White ^{3,4} Squeeze Tube: ≤410 g/L, <47 wt% White Lower VOC Cartridge ³ & Squeeze Tube ³ : ≤40 g/L, <4 wt% Clear Lower VOC Squeeze Tube: ≤380 g/L, <43 wt%

TEST DATA:

PROPERTY	RESULTS	TEST METHOD
Durability	25% total joint movement (10 cycles @ -15°F/-26°C)	ASTM C719
Hardness, Shore A	25 (21-day cure)	ASTM C661
Slump	< 1/8"	ASTM D2202
Solids	46-58% by weight depending on product	ASTM C1250
Extrusion Rate	80 g/min (1/8" orifice at 40 psi)	ASTM C603
Cured	1 week (dependent on temperature, humidity and bead size/thickness)	ASTM C679
Tack-free	Less than 30 minutes	ASTM C679
Low Temp. Flexibility	Pass (not artificially weathered)	ASTM C734
Adhesion-in-peel Passing Substrates	See "ADHERES TO" section	ASTM C794

SPECIFICATIONS:

- Meets FHA requirements.

The data reported here are believed to be reliable. No warranty is made concerning their accuracy or the results obtained from their use.

¹ Clear Cartridge sold in all 50 US states and Canada.

² Clear Squeeze Tube not for sale in California. Clear Squeeze Tube Lower VOC required in California.

³ All White products not for sale in California.

⁴ White Cartridge and White Squeeze Tube not for sale in CT, DC, DE, IL, IN, MA, MD, ME, MI, NH, NJ, NY, OH, PA, RI, UT (select counties), VA (select counties), VT, and Canada. White Cartridge Lower VOC and White Squeeze Tube Lower VOC required in these areas.

LXL 002 10-18

The Tough Elastic Sealant for Every Job

Lexel®

Sticks to Almost Anything*



10300 E. 107th Place
Brighton, CO 80601
800-767-5656

www.sashco.com

Keep up with Sashcoinc on:



