

LN-207

Interior & Exterior

## ***A clear, permanent, fast-bonding construction adhesive for most common building materials.***

### **PRODUCT DESCRIPTION**

LIQUID NAILS® Clear Small Projects Silicone Adhesive (LN-207) is a moisture curing adhesive designed for use in all types of household repair and light assembly and remodeling applications. The adhesive is non-flammable, cures quickly, and has outstanding environmental resistance to heat, cold, and moisture. Clear Adhesive adheres to a wide range of surfaces including most plastics, aluminum and other metals, concrete and masonry, and wood.

**RECOMMENDED FOR** bonding all common building materials, including:

- Wood
- Concrete
- Painted surfaces
- Vinyl cove base
- Metal
- Fiberglass
- Vinyl
- Porcelain

Clear Small Projects Silicone Adhesive can be used for a variety of applications that include:

- House numbers
- Countertops
- Moldings
- Carpets
- Floor tile
- Canvas/fabrics

**NOT RECOMMENDED FOR** windows, wood flooring, tubs/sinks, aquariums or ceiling applications.

*Please research all installation instructions and read entire label for safety, health & environmental information prior to use.*

Look for other LIQUID NAILS products which are right for your specific project

### **PRODUCT ADVANTAGES**

- Works where hammer and nails can't
- Fast-bonding
- Waterproof
- Resealable cap / Precision applicator
- Won't shrink
- Clear Adhesive
- Permanently flexible
- Construction grade
- Non-flammable



### **SURFACE PREPARATION**

Make sure that all surfaces are clean, dry and structurally sound before product is applied. Apply in well-ventilated area.

### **APPLYING THE PRODUCT**

**General application:** Apply a bead of adhesive to the material being bonded and position immediately. For faster setting or uneven surfaces, pull materials apart right after pressing together and allow adhesive to air dry for 5 to 10 minutes before pressing back.

**For fabric and canvas:** Apply a bead of adhesive to fabric/canvas. Work wet adhesive into fibers. Press surfaces together. Remove any excess adhesive. Keep clamped or pressed together for 24 hours.

**For countertops, carpets and flooring:** Apply a bead of adhesive as close to the center of the material as possible. Press surface down and apply pressure from the center out to the edges. Remove any excess adhesive. Carefully pull materials apart and allow to vent for 2 to 3 minutes. Reapply from the center to the edges. Clamp or place weight on materials for 24 hours.

**For porcelain and ceramics:** Apply a bead of adhesive to one surface; press into place. Remove any excess adhesive. Pull materials apart and vent for 2 to 3 minutes. Reapply materials and clamp together for 24 hours. Do not use for 48 hours.

**For ceramic tile:** Apply a bead of adhesive to the back of the tile. Press tile into place. Remove any excess adhesive. Remove tile and vent for 2 to 3 minutes, then reapply tile and brace if necessary.

### **CLEAN-UP**

Uncured adhesive may be removed by wiping with a clean cloth dampened with mineral spirits. Dried adhesive may be removed by scraping.

### **DISPOSAL**

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants. EAD-C9

### **LIMITED WARRANTY**

Macco warrants satisfaction with this product when handled and applied according to label instructions. If this product is not as warranted, please call 1-800-634-0015 for refund or product replacement details. This warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made.** Macco shall not be liable for any special, incidental or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so the limitations may not apply. This warranty gives specific legal rights. You may also have other rights that vary from state to state.

**WARNING!** CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. Avoid contact with eyes and skin. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.** MAC134-0108

### **LN-207**

### **TECHNICAL INFORMATION**

**Base:** Silicone Pre-polymer

**Type:** Moisture-curing

**Color:** Translucent clear

**Appearance:** Smooth gel

**Application Temperature:** -35° to 140° F  
(-37° to 60° C)

**Service Temperature:** -80° to 350° F  
(-62° to 177° C)

**Adhesion:** Excellent to most common substrates

**Consistency:** Squeeze tube grade

**Bridging Ability:** Very good

**Extrudability:** Very good

**Shear Strength (in psi to wood):**

24 hours – 85 psi

48 hours – 106 psi

**Peel Strength**

(in pli, canvas to canvas, T-peel):

24 hours – 12.0 pli

1 week – 13.9 pli

**Peel Strength**

(in pli, 180 after one week cure time):

Aluminum – 11.5 pli

ABS Plastic – 20.5 pli

Glass – 20.1 pli

**Durability:** Excellent

**Flexibility:** Excellent

**Water Resistance:** Excellent

**Exterior Weathering:** Excellent

**Accelerated Aging (Q-UV Weatherometer):**

No change in 500 hrs.

**Shore A Hardness:** 27

**Cure Rate (24 hrs):** 3 mm

**Freeze-Thaw Stable:** Stable through 5 cycles

**Bleed:** None

**Staining:** Do not use on marble or granite

**Odor:** Mild

**Skin Time:** 9 minutes

**Tack Free Time:** 20 minutes

**Open Time:** 10-15 minutes

**Paintability:** Not paintable

**Weight Per Gallon:** 8.6 pounds (3.2 kg)

**Viscosity:** 290,000 CPS

**Volatiles:** <5%

**Solids:** >95%

**Flammability:** Non-flammable

**Flash Point:** Not applicable

**Shelf Life:** 12 months from date of purchase

**MAX VOC:** 46 g/L



15885 West Sprague Rd.  
Strongsville, OH 44136

[www.liquidnails.com](http://www.liquidnails.com)

Customer Service 1-800-634-0015