Conforms to USDOL OSHA 29CFR 1910.1200 HAZCOM

SAFETY DATA SHEET

HEALTH - HYGIENE - HOME

Lysol Brand Disinfectant Concentrate

1. Product and company identification

Product name	: Lysol Brand Disinfectant Concentrate
Distributed by	: Reckitt Benckiser LLC. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225 +1 973 404 2600
Emergency telephone number (Medical)	: 1-800-338-6167
Emergency telephone number (Transport) Website:	: 1-800-424-9300 (U.S. & Canada) CHEMTREC Outside U.S. and Canada (North America), call Chemtrec:703-527-3887 http://www.rbnainfo.com

Product use : Disinfectant.

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS #	: 353773PSDS v3.0
Formulation #:	: 269-005 (353773 v10.0)
EPA ID No.	: 777-94
UPC Code / Sizes	: 19200-02201-10; 19200-77500-10 (12 fl.oz. PET Amber Pour Bottle with CRC cap)

2. Hazards identification	
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 4 SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
GHS label elements Hazard pictograms	
Signal word Hazard statements	 Danger Combustible liquid.
Precautionary statements	Causes severe skin burns and eye damage.
Code # : FF353773 (353773PSDS	SDS # : 353773PSDS v3.0 Date of issue : 01/04/2015. 1/16

2. Hazards identification

General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	 Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from flames and hot surfaces No smoking. Wash hands thoroughly after handling.
Response	: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: None known.
Hazards not otherwise classified	: None known.

3. Composition/information on ingredients

Substance/mixture	: Mixture
Substance/inixture	

Ingredient name	%	CAS number
clorofene	5 - 10	120-32-1
potassium hydroxide	2.5 - 5	1310-58-3
Ethyl alcohol	1 - 2.5	64-17-5
Isopropyl alcohol	1 - 2.5	67-63-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Description of necess	sary first aid measures
Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4. First aid measures

Skin contact	: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

wost important symptoms/e	anects, acute and delayed
Potential acute health effect	<u>ets</u>
Eye contact	: Causes serious eye damage.
Inhalation	: May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system.
Skin contact	: Causes severe burns.
Ingestion	: May cause burns to mouth, throat and stomach.
<u>Over-exposure signs/symp</u>	<u>itoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	•	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and
	explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively,
	or if water-insoluble, absorb with an inert dry material and place in an appropriate waste
	disposal container. Dispose of via a licensed waste disposal contractor.

6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Precautions for safe handling

Protective measures :	Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, : including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Control

Occupational exposure limits

(353773PSDS)

Ingredient name	Exposure limits
potassium hydroxide	ACGIH TLV (United States, 6/2013). C: 2 mg/m ³
	OSHA PEL 1989 (United States, 3/1989). CEIL: 2 mg/m ³
	NIOSH REL (United States, 10/2013).
	TWA: 2 mg/m ³ 10 hours.
Ethyl alcohol	ACGIH TLV (United States, 6/2013).
	STEL: 1000 ppm 15 minutes.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 1000 ppm 8 hours.
	TWA: 1900 mg/m ³ 8 hours.
	NIOSH REL (United States, 10/2013).
	TWA: 1000 ppm 10 hours.
	TWA: 1900 mg/m ³ 10 hours.
	OSHA PEL (United States, 2/2013).
ode # : FF353773	SDS # : 353773PSDS v3.0 Date of issue : 01/04/2015. 5/16

8. Exposure controls/personal protection

 TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours. ACGIH TLV (United States, 6/2013). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 400 ppm 15 minutes. STEL: 500 ppm 15 minutes. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 500 ppm 15 minutes. STEL: 500 ppm 15 minutes. TWA: 400 ppm 10 hours. TWA: 980 mg/m³ 15 minutes. STEL: 1225 mg/m³ 15 minutes. STEL: 1225 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes. TWA: 980 mg/m³ 16 hours. TWA: 400 ppm 8 hours. 			
TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes. STEL: 1225 mg/m³ 15 minutes. STEL: 1225 mg/m³ 15 minutes.			
OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes. STEL: 1225 mg/m³ 15 minutes. STEL: 1225 mg/m³ 15 minutes. TWA: 400 ppm 8 hours.			
TWA: 400 ppm 8 hours. TWA: 980 mg/m ³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m ³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
TWA: 980 mg/m ³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m ³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m ³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
STEL: 1225 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m ³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m ³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
TWA: 400 ppm 10 hours. TWA: 980 mg/m ³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
TWA: 980 mg/m ³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
STEL: 1225 mg/m ³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours.			
TWA: 400 ppm 8 hours.			
•••			
e only with adequate ventilation. Use process enclosures, local exhaust ventilation or ler engineering controls to keep worker exposure to airborne contaminants below any commended or statutory limits. The engineering controls also need to keep gas, vapor dust concentrations below any lower explosive limits. Use explosion-proof ventilation uipment.			
Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be			
cessary to reduce emissions to acceptable levels.			
ash hands, forearms and face thoroughly after handling chemical products, before ting, smoking and using the lavatory and at the end of the working period. Appropriate hniques should be used to remove potentially contaminated clothing. Wash intaminated clothing before reusing. Ensure that eyewash stations and safety showers e close to the workstation location.			
fety eyewear complying with an approved standard should be used when a risk sessment indicates this is necessary to avoid exposure to liquid splashes, mists, ses or dusts. If contact is possible, the following protection should be worn, unless assessment indicates a higher degree of protection: chemical splash goggles and/or e shield. If inhalation hazards exist, a full-face respirator may be required instead.			
emical-resistant, impervious gloves complying with an approved standard should be rn at all times when handling chemical products if a risk assessment indicates this is cessary. Considering the parameters specified by the glove manufacturer, check ring use that the gloves are still retaining their protective properties. It should be ted that the time to breakthrough for any glove material may be different for different ve manufacturers. In the case of mixtures, consisting of several substances, the otection time of the gloves cannot be accurately estimated.			
rsonal protective equipment for the body should be selected based on the task being			

8. Exposure controls/personal protection

Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

9. Physical and chemical properties

<u>Appearance</u>		
Physical state	: Liquid. [Clear.]	
Color	Red.	
Odor	soap	
Odor threshold	Not available.	
рН	: 10.3 to 11.1 [Conc. (% w/w): 100%]	
Melting point	Not available.	
Boiling point	Not available.	
Flash point	: Closed cup: 62.8°C (145°F)	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Lower and upper explosive (flammable) limits	Not available.	
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	: 1.024 to 1.034	
Solubility	: Easily soluble in the following materials: cold water and hot w	ater.
Partition coefficient: n-	Not available.	

Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	4	Not available.

10. Stability and reactivity

octanol/water

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
clorofene	LD50 Oral	Rat	1700 mg/kg	-	
Ethyl alcohol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours	
-	LD50 Oral	Rat	7 g/kg	-	
Isopropyl alcohol	LD50 Dermal	Rabbit	12800 mg/kg	-	
	LD50 Oral	Rat	5000 mg/kg	-	
*Lysol Brand Disinfectant	LC50 Inhalation Vapor	Rat	>2.07 mg/l	4 hours	
Concentrate, Original Scent					
	LD50 Dermal	Rabbit	>5000 mg/kg	-	
	LD50 Oral	Rat	5000 mg/kg	-	

Conclusion/Summary : Not classified Harmful. *Information is based on toxicity test result of a similar product.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
clorofene	Skin - Mild irritant	Human	-	48 hours 1	-
				Percent	
potassium hydroxide	Eyes - Moderate irritant	Rabbit	-	24 hours 1	-
				milligrams	
	Skin - Severe irritant	Guinea pig	-	24 hours 50	-
				milligrams	
	Skin - Severe irritant	Human	-	24 hours 50	-
				milligrams	
	Skin - Severe irritant	Rabbit	-	24 hours 50	-
				milligrams	
Ethyl alcohol	Eyes - Moderate irritant	Rabbit	-	0.066666667	-
				minutes 100	
				milligrams	
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				milligrams	
	Eyes - Moderate irritant	Rabbit	-	100	-
				microliters	
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				milligrams	
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				milligrams	
	Eyes - Moderate irritant	Rabbit	-	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
*Lysol Brand Disinfectant	Skin - Visible necrosis	Rabbit	-	240 minutes	14 days
Concentrate, Original Scent					
	Eyes - Cornea opacity	Rabbit	>3	-	-
Conclusion/Summary					
Skin	: Causes burns. *Informati	on is based on t	oxicity test re	esult of a similar pr	oduct.
Eyes	: Causes irreversible eye of	damage *Informa	tion is based	d on toxicity test re	sult of a similar
-	product.	0		,	-

Sensitization

SDS #

11. Toxicological information Product/ingredient name Route of exposure Species Result *Lysol Brand Disinfectant Concentrate, Original Scent skin Guinea pig Not sensitizing

Conclusion/Summary

Skin

: Non-sensitizer to skin. *Information is based on toxicity test result of a similar product.

Mutagenicity Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Ethyl alcohol	-	1	-
Isopropyl alcohol	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Isopropyl alcohol	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

(353773PSDS)

Not available.

Aspiration hazard

Not available.

Information on the likely
routes of exposure: Not available.Potential acute health effects:Eye contact: Causes serious eye damage.Inhalation: May give off gas, vapor or dust that is very irritating or corrosive to the respiratory
system.Skin contact: Causes severe burns.Ingestion: May cause burns to mouth, throat and stomach.

Symptoms related to th	ne physical, chemical and toxicological characteristics	
Eye contact	: Adverse symptoms may include the following: pain watering redness	
Code # : FF353773	SDS # : 353773PSDS v3.0 Date of issue : 01/04/2015.	9/16

11. Toxicological information

Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

Delayed and immediate effect	cts	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>5</u>
Not available.		
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure	
clorofene	Acute EC50 0.59 ppm Fresh water	Daphnia - Daphnia magna	48 hours	
	Acute LC50 0.33 ppm Fresh water	Fish - Lepomis macrochirus	96 hours	
potassium hydroxide	Acute LC50 80 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours	
Ethyl alcohol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours	
-	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours	
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours	
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days	
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours	
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki -	12 weeks	
Code # : FF353773 (353773PSDS)	SDS # : 353773PSDS v3.0	Date of issue : 01/04/2015.	10/16	

12. Ecological information

0			
		Larvae Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
clorofene	3.6	-	low
Ethyl alcohol	-0.35	-	low
Isopropyl alcohol	0.05	-	low

Mobility in soil

Soil/water partition : Not available. coefficient (K_{oc})

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
Code # : FF3	53773	SDS # : 35377	/ 73PSDS v3.0 D	ate of iss	 ue::01/	04/2015. 11/16
Code # : FF3 (353	53773 3773PSDS)	SDS # : 35377	73PSDS v3.0 D	ate of iss	 a ue : 01/	 04/2015. 1

UN1760	s. (potassium hydroxide, 2,4-xylenol)	8	II	CORROSIVE	Reportable quantity 25990.9 lbs / 11799.9 kg [3029.3 gal / 1146
	RQ (potassium hydroxide, 2,4-xylenol)			×	3 L] Package sizes shipped in quantities less than the product reportable quantity ar not subject to the RQ (reportable quantity) transportation requirements.
					Yes. <u>Packaging</u> <u>instruction</u> Passenger aircraft Quantity limitation: 1 I
					Cargo aircraft Quantity limitation: 30 L
					Special provisions B2, IB2, T11, TP2, TP27
UN1760	CORROSIVE LIQUID, N.O.S. (potassium hydroxide, 2,4-xylenol)	8	11		Explosive Limit and Limited Quantity Index 1
					Passenger Carrying <u>Road or Rail Index</u> 1
					Special provisions 16
UN1760	LIQUIDO CORROSIVO, N.E.P. (potassium hydroxide, 2,4-xylenol)	8	II	1 2 2 2 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	<u>Special provisions</u> 274
UN1760	CORROSIVE LIQUID, N.O.S. (potassium hydroxide, 2,4-xylenol)	8	11	*****	Emergency schedules (EmS) F-A, S-B Special provisions
	UN1760	N.O.S. (potassium hydroxide, 2,4-xylenol)UN1760LIQUIDO CORROSIVO, N.E.P. (potassium hydroxide, 2,4-xylenol)UN1760CORROSIVE LIQUID, N.O.S. (potassium)	N.O.S. (potassium hydroxide, 2,4-xylenol)UN1760LIQUIDO CORROSIVO, N.E.P. (potassium hydroxide, 2,4-xylenol)UN1760CORROSIVE LIQUID, N.O.S. (potassium)	N.O.S. (potassium hydroxide, 2,4-xylenol)UN1760LIQUIDO CORROSIVO, N.E.P. (potassium hydroxide, 2,4-xylenol)8IIUN1760CORROSIVE LIQUID, N.O.S. (potassium8II	N.O.S. (potassium hydroxide, 2,4-xylenol) Image: Constant of the system UN1760 LIQUIDO CORROSIVO, N.E.P. (potassium hydroxide, 2,4-xylenol) 8 II UN1760 CORROSIVE LIQUID, N.O.S. (potassium 8 II

Code # : FF353773 (353773PSDS) 12/16

14. Transpo	UN1760	ation Corrosive liquid, n.o.s. (potassium hydroxide, 2,4-xylenol)	8		Passenger and Cargo Aircraft Quantity limitation: 1 L Packaging instructions 851 Cargo Aircraft Only Quantity limitation: 30 L Packaging instructions 855 Limited Quantities - Passenger Aircraft
					Quantity limitation: 0.5 L Packaging instructions Y840
					Special provisions A3, A803

PG* : Packing group

15. Regulatory infe	ormation
U.S. Federal regulations	: TSCA 8(a) PAIR: 2-methylpropan-2-ol
	TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	United States inventory (TSCA 8b): Not determined.
	Clean Water Act (CWA) 307: clorofene; 2,4-xylenol
	Clean Water Act (CWA) 311: potassium hydroxide; sodium hydroxide; ammonia, anhydrous; xylenol; m-cresol; p-cresol
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
<u>SARA 302/304</u>	

<u>Composition/information on ingredients</u>

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ammonia	< 0.01	Yes.	500	-	100	-

SARA 304 RQ

15. Regulatory information

SARA 311/312

Classification

: Fire hazard

Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
clorofene	5 - 10	No.	No.	No.	Yes.	No.
potassium hydroxide	2.5 - 5	No.	No.	No.	Yes.	No.
Ethyl alcohol	1 - 2.5	Yes.	No.	No.	Yes.	No.
Isopropyl alcohol	1 - 2.5	Yes.	No.	No.	Yes.	No.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements		120-32-1 67-63-0	5.4998 1.8333
Supplier notification		120-32-1 67-63-0	5.4998 1.8333


SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	: The following components are listed: POTASSIUM HYDROXIDE; ISOPROPYL ALCOHOL; ETHYL ALCOHOL
New York	: The following components are listed: Potassium hydroxide
New Jersey	: The following components are listed: POTASSIUM HYDROXIDE; CAUSTIC POTASH; ISOPROPYL ALCOHOL; 2-PROPANOL; ETHYL ALCOHOL; ALCOHOL
Pennsylvania	: The following components are listed: POTASSIUM HYDROXIDE (K(OH)); CHLORINATED PHENOLS; 2-PROPANOL; DENATURED ALCOHOL
Label elements	
Signal word:	: DANGER
Hazard statements	: Harmful if swallowed.
	Corrosive Causes irreversible eye damage
	Corrosive CAUSES SKIN BURNS.
Precautionary measures	 Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or mist. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash it before reuse. Avoid breathing dust/fume/gas/mist/vapors/spray.
Pennsylvania <u>Label elements</u> Signal word: Hazard statements	 ISOPROPYL ALCOHOL; 2-PROPANOL; ETHYL ALCOHOL; ALCOHOL The following components are listed: POTASSIUM HYDROXIDE (K(OH)); CHLORINATED PHENOLS; 2-PROPANOL; DENATURED ALCOHOL DANGER Harmful if swallowed. Corrosive Causes irreversible eye damage Corrosive CAUSES SKIN BURNS. Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or mist. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly with soap and water after handling and before eating, drinking, cl gum, using tobacco or using the toilet. Remove contaminated clothing and wash it before reuse.

16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

5

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
Date of issue	: 01/04/2015.
Date of previous issue	: 09/04/2010.
Version	: 3

16. Other information

Pre	par	ed	bv
	~~.	•••	~ ,

: Reckitt Benckiser LLC. Product Safety Department 1 Philips Parkway Montvale, New Jersey 07646-1810 USA. FAX: 201-476-7770

Revision comments : Update as per US GHS.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.