

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

1. Identification	
Product identifier used on the label:	MAG 1 20W50 6/1QT
Stock Number:	MAG61654
Other means of identification: Synonyms:	No data available
Recommended use of the chemical and re	strictions on use:
Recommended use:	Motor Oil
Restrictions on use:	Uses other than those described above
Name, address, and telephone number	Warren Distribution, Inc.
of the chemical manufacturer,	950 S. 10th St., Suite 300
importer, or other responsible party:	Omaha, NE 68108-3296
Phone number:	+01 (800) 825-1235 +01 (402) 341-9397
E-mail address:	sds@wd-wpp.com
Emergency phone number:	CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

### 2. Hazard(s) identification

#### Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification:Not classified as hazardous under OSHAHazards not otherwise classified:No data available

#### 3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Petroleum distillates,	No data available	64742-54-7	80 - 100
hydrotreated heavy paraffinic			
Highly refined synthetic base	No data available	64742-54-7	0.1 - 1
stocks			
Petroleum distillates, solvent	No data available	64742-65-0	0.1 - 1
dewaxed heavy paraffinic			

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eye Contact:	None expected to be needed, however, use an eye wash to remove a chemical from your eye regardless of the level of hazard.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion:	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
Most important symptoms/effects, acute and delayed:	No data available
Indication of immediate medical attention and special treatment needed, if necessary:	No additional first aid information available.

5 Fi	re-fin	htina	measures
J. I I	1 6-110	nnunu	ilicasules

#### Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Unsuitable extinguishing media:	No data available
Specific hazards arising from the chemical:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Hazardous combustion products:	Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, oxides of phosphorus, Hydrogen sulfide
Special protective equipment and precautions for fire-fighters:	Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

6. Accidental release measures

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

Personal precautions, protective equipment and emergency procedures:	No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS.
Methods and materials for containment and cleaning up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.
7. Handling and storage	
Precautions for safe handling:	Mildly irritating material. Avoid unnecessary exposure. Follow all protective equipment recommendations provided in Section 8.
Conditions for safe storage, including any incompatibilities: Safe storage conditions:	Store in a cool dry place. Isolate from incompatible materials.
Materials to Avoid/Chemical Incompatibility:	Strong oxidizing agents

#### 8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Petroleum distillates,	5 mg/m3	5 mg/m3	10 mg/m3	No data available
hydrotreated heavy				
paraffinic				
Petroleum distillates,	5 mg/m3	5 mg/m3	10 mg/m3	No data available
solvent dewaxed heavy				
paraffinic				
Highly refined synthetic	5 mg/m3	5 mg/m3	10 mg/m3	No data available
base stocks				

Appropriate engineering controls:

Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:Respiratory Protection:Respiratory protection may be required to avoid overexposure when

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

	handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.
Respirator Type(s):	None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.
Eye protection:	Wear safety glasses when handling this product if there is a likelihood of contact with eyes.
Skin protection:	Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Gloves:	Neoprene, Nitrile
General hygiene conditions:	Follow all protective equipment recommendations provided in Section 8.

#### 9. Physical and chemical properties Appearance (physical state, color etc.): **Physical state:** Liquid Color: Brown Odor: **MildPetroleum Odor Threshold:** Not determined pH: No data available Melting point/freezing point: **Melting Point:** No data available Freezing point: No data available Initial boiling point and boiling range No data available (°C): 240 Flash Point (°C): No data available **Evaporation Rate:** Flammability (solid, gas): No data available Upper/lower flammability or explosive limits: Upper flammability or explosive Not established limits: Lower flammability or explosive Not established

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

limits:	
Vapor pressure:	No data available
Vapor density:	No data available
Relative density:	0.88
Solubility(ies):	Insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition Temperature:	Not determined
Viscosity:	164.9

### 10. Stability and reactivity

Reactivity: Chemical stability:	There are no known reactivity hazards associated with this product. Stable under normal conditions.
Possibility of hazardous reactions:	None expected under standard conditions of storage.
Conditions to avoid (e.g., static discharge, shock, or vibration):	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, oxides of phosphorus, Hydrogen sulfide

#### 11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Skin contact, Inhalation, Ingestion, Eye contact
Symptoms related to the physical, chemical and toxicological characteristics:	No data available
Delayed and immediate effects and also ch	nronic effects from short- and long-term exposure:
Ingestion:	No hazard in normal industrial use. Estimated to be > 5.0 g/kg.
Skin Contact:	This material is likely to be slightly irritating to skin based on animal data.Can cause minor skin irritation, defatting, and dermatitis.

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

Absorption: Inhalation:	Estimated to be > 5.0 g/kg; practically non-toxic No hazard in normal industrial use. Likely to be practically non-toxic based on animal data.
Eye Contact:	This material is likely to be non-irritating to eyes based on animal data.
Sensitization:	Non-hazardous under Respiratory Sensitization category.No data available to indicate product or components may be a skin sensitizer.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Carcinogenicity:	Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
STOT-single exposure:	Based on available data, the classification criteria are not met.
STOT-repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Other information:	None known.

#### Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	Chemical Name LD50 Oral LD50 Dermal		LC50 Inhalation
Highly refined synthetic base stocks	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	
Petroleum distillates, solvent dewaxed heavy paraffinic	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 2400 MG/M3
Petroleum distillates, hydrotreated heavy paraffinic	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

12. Ecological information
----------------------------

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

Ecotoxicity (aquatic and terrestrial,	
where available):	

Slight ecological hazard. In high concentrations, this product may be dangerous to plants and/or wildlife.

#### **Ecological Toxicity Data:**

No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L Aquatic LC50 (96h)
No data available	5000 mg/L
	<u>v</u>
	Aquatic LC50 (96h)
No data available	Rainbow Trout >
	5000 mg/L
	Aquatic LC50 (96h)
No data available	Rainbow Trout >
	5000 mg/L
	No data available

Bioaccumulative potential:	Bioconcentration may occur.
Mobility in soil:	This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.
Other adverse effects (such as hazardous to the ozone layer):	None known.

#### 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:	Spent or discarded material is non-hazardous according to environmental regulations.
Contaminated packaging:	Recycle containers whenever possible.

#### 14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:			
DOT Basic Description:	Not regulated for road transport		

International carriage of dangerous goods by sea (IMDG/IMO):

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

UN number: UN Proper shipping name: Transport hazard class(es): Packing group, if applicable:	Not regulated by IMDG Not applicable Not applicable Not applicable
International carriage of dangerous goods	s by air (IATA):
UN number:	Not regulated by IATA
UN Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group, if applicable:	Not applicable
Environmental hazards (e.g., Marine pollutant (Yes/No)):	None.
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	No data available
Special precautions which a user needs to be aware of or needs to comply with in connection with transport or conveyance either within or outside their premises:	No data available

### 15. Regulatory information

### Safety, health and environmental regulations specific for the product in question:

**TSCA Status:** 

All components of this material are on the Active US TSCA Inventory or are exempt.

#### **Regulated Components:**

Chemical Name	CAS #	CERCLA	Sara EHS	Sara 313	U.S. HAP
Petroleum distillates,					
hydrotreated heavy	64742-54-7	Ν	N	N	N
paraffinic					
Petroleum distillates,					
solvent dewaxed	64742-65-0	Ν	N	N	N
heavy paraffinic					
Highly refined	61710 51 7	N	N	N	N
synthetic base stocks	64742-54-7	Ν	N	N	N

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

Chemical Name	CAS #	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Ν	Ν	Ν	Ν
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Ν	Ν	Ν	Ν
Highly refined synthetic base stocks	64742-54-7	Ν	N	Ν	Ν

Chemical Name	CAS #	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Ν	Ν	Ν	Ν	Ν
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Ν	Ν	Ν	Ν	Ν
Highly refined synthetic base stocks	64742-54-7	Ν	Ν	Ν	Ν	Ν

#### 16. Other information, including date of preparation or last revision.

SDS Prepared by: **CDURSTON Revision Date:** 04-10-2020 3 **Revision Number: Reason for revision: NEW VERSION References:** No data available Other Info: No data available **Disclaimer:** This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we

believe the information to be correct, but cannot guarantee its accuracy

Product identifier used on the label: MAG 1 20W50 6/1QT Stock Number: MAG61654 Revision Date: 04-10-2020 Replaces:

> or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.