



PRINT



SAVE AS PDF

# MAG 1<sup>®</sup> MULTI-VEHICLE TRANSMISSION FLUID

## PASSENGER CAR TRANSMISSION PRODUCTS AUTOMATIC TRANSMISSION PRODUCTS



MAG 1<sup>®</sup> Multi-Vehicle Automatic Transmission Fluid is engineered to extend transmission life and smooth operation of many automatic transmissions from a variety of OEMs.

### PROTECTION FOR TODAY'S AUTOMATIC TRANSMISSION DESIGNS

Automotive transmissions have evolved dramatically, requiring highly specialized fluids for unique applications. One brand has evolved right alongside – MAG 1. Only the most advanced transmission fluids meet the difficult challenges of effectively balancing performance, strength and durability.

Featuring MAG 1<sup>®</sup> with FMX<sup>®</sup> Technology – Friction Management for Xtreme protection<sup>™</sup>. MAG 1 is designed to provide unsurpassed protection.

### PERFORMANCE

- Delivers superior friction stability to maintain smooth, consistent shifting and prevent shudder.

### STRENGTH

- Provides a strong oil film to prevent metal-to-metal contact between rotating parts to prevent wear.

### DURABILITY

- Resists thickening due to high operating temperatures.

### APPLICATIONS

- Also recommended for all transmissions requiring Audi/VW G 052 025, 052 162, 055 025, GM Dexron<sup>®</sup> -III, II, Honda DW-1, Z-1, Nissan Matic-D, J, K, 402, Subaru ATF, ATF-HP, Toyota T-II, T-III, T-IV, WS. Do not use this product in General Motors vehicles after model year 2005 and Ford<sup>®</sup> vehicles after model year 2006. Do not use this product in transmissions that specify Ford Type F or GM Dexron<sup>®</sup> VI fluid.

### INDUSTRY/OEM SPECIFICATIONS

MAN 339 Type Z1, Z2, V1	Meets Requirements
ZF TE-ML 14B	Meets Requirements
Allison C-4	Suitable for Use
Audi G 052 025, 052 162, 055 025	Suitable for Use
BMW 7045E, LA2634, LT71141	Suitable for Use
BMW P/N 83 22 0 024 359, ETL-8072B	Suitable for Use
BMW P/N 83 22 0 0246 922, ETL-7045E	Suitable for Use

BMW P/N 83 22 0 403 249, ETL-8072B	Suitable for Use
BMW P/N 83 22 9 407 765, LA 2634	Suitable for Use
BMW P/N 83 22 9 407 807, LT 711 41	Suitable for Use
Chrysler AS68RC, AS68 RC (T-IV), Diamond SP-III	Suitable for Use
Chrysler P/N 05127382AA, P/N 68043742AA	Suitable for Use
Dexron III G/H, Dexron II, Dexron, AW1	Suitable for Use
Esso 71141	Suitable for Use
Ford P/N XT-2-DX (MERC), Ford P/N XT-2-SM (SYN MERC)	Suitable for Use
Fuchs 3353	Suitable for Use
Honda DW-1, Z-1	Suitable for Use
Hyundai/Kia/Mitsubishi Diamond SP-II and SP-III, RED-1, SP-IV	Suitable for Use
Hyundai NSWS9638	Suitable for Use
IDEMITSU APOROIL ATF HP	Suitable for Use
Idemitsu K17	Suitable for Use
ISUZU 08200-9001 / Genuine ATF	Suitable for Use
Jaguar P/N WSS-M2C922-A-1	Suitable for Use
JWS 3309, Any 3309	Suitable for Use
JWS 3324	Suitable for Use
M315-2004 JASO 1A, 2A	Suitable for Use
Mazda ATF M-III, MV, T-IV	Suitable for Use
MB236.1,2,5,6,7,9, 10, 11	Suitable for Use
Mercon, Ford ESP-M2C166-H	Suitable for Use
MINI P/N 83 22 0 402 413	Suitable for Use
Nissan Matic-D, J, K	Suitable for Use
Porsche P/N 999 917 547 00 (A2)	Suitable for Use
SAAB P/N 22 717 466, 93 165 147 (AW-1)	Suitable for Use
Saturn P/N 21005966	Suitable for Use
Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF	Suitable for Use
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B	Suitable for Use
Shell 3403 M115	Suitable for Use
Subaru ATF, ATF-HP	Suitable for Use
Suzuki 3314, 3317	Suitable for Use
Texaco N402	Suitable for Use
Toyota T-II, T-III, T-IV, WS, Ford XT8QAW	Suitable for Use
Voith 55.6335 (G607)	Suitable for Use
Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342	Suitable for Use
Volvo P/N 1161540-8	Suitable for Use
VW G 052 025, 162, 099, 055 025	Suitable for Use
VW P/N GUS 000 162	Suitable for Use
ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C	Suitable for Use

\*TES 389 is a registered trademark of Allison Transmissions, Inc.

## TYPICAL PROPERTIES

Brookfield Viscosity at -40°C, cP	ASTM D2983	11,300
Color	ASTM D1500	Red
Gravity, °API	ASTM D287	33.02
Pour Point °C (°F)	ASTM D5950	-51°C (-60°F)
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8601
Viscosity @ 100°C cSt	ASTM D445	7.56
Viscosity @ 40°C cSt	ASTM D445	35.43

**CONTAINER/BULK AVAILABILITY**

55 Gallon Drum

Product Number - 60613

6/1 Quart

Product Number - 00915

---

**Available in Bulk**

Information accurate as of January 1, 2021