

TABLE 1: Crack injection usage estimating guide SINGLE COMPONENT¹

Approximate Coverage Rates Linear Feet (Linear Meters)			
Crack Width in. (cm)	Crack Depth in (cm)	Cartridge Size	
		13 oz. (266 ml)	20 oz. (473 ml)
1/16 in. or 0.0625 (0.159)	0.25 (0.6)	125.1 (38.1)	192.5 (58.7)
	0.375 (1.0)	83.4 (25.4)	128.3 (39.1)
	0.5 (1.3)	62.6 (19.1)	96.3 (29.3)
	0.75 (1.9)	41.7 (12.7)	64.2 (19.6)
1/8 in. or 0.1250 (0.318)	0.25 (0.6)	62.6 (19.1)	96.3 (29.3)
	0.375 (1.0)	41.7 (12.7)	64.2 (19.6)
	0.5 (1.3)	31.3 (9.5)	48.1 (14.7)
	0.75 (1.9)	20.9 (6.4)	32.1 (9.8)
3/16 in. or 0.1875 (0.476)	0.25 (0.6)	41.7 (12.7)	64.2 (19.6)
	0.375 (1.0)	27.8 (8.5)	42.8 (13.0)
	0.5 (1.3)	20.9 (6.4)	32.1 (9.8)
	0.75 (1.9)	13.9 (4.2)	21.4 (6.5)
1/4 in. or 0.25 (0.635)	0.25 (0.6)	31.3 (9.5)	48.1 (14.7)
	0.375 (1.0)	20.9 (6.4)	32.1 (9.8)
	0.5 (1.3)	15.6 (4.8)	24.1 (7.3)
	0.75 (1.9)	10.4 (3.2)	16.0 (4.9)
3/8 in. or 0.3750 (0.953)	0.25 (0.6)	20.9 (6.4)	32.1 (9.8)
	0.375 (1.0)	13.9 (4.2)	21.4 (6.5)
	0.5 (1.3)	10.4 (3.2)	16.0 (4.9)
	0.75 (1.9)	7.0 (2.1)	10.7 (3.3)
1/2 in. or 0.50 (1.270)	0.25 (0.6)	10.8 (3.3)	24.1 (7.3)
	0.375 (1.0)	10.4 (3.2)	16.0 (4.9)
	0.5 (1.3)	7.8 (2.4)	12.0 (3.7)
	0.75 (1.9)	5.2 (1.6)	8.0 (2.4)

1. Values are approximate and may vary depending on waste, concrete and user technique.