# MOTOR MEDIC

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Solder Seal/Gunk Motor Medic Oil Treatment

Other means of identification

SDS number M1815

Part No. M1815, M1949
Tariff code 3811.29.0000
Recommended use Oil Additive
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name

Address

RSC Chemical Solutions
600 Radiator Road
Indian Trail, NC 28079

**United States** 

**Telephone** Customer Service: (704) 821-7643

Technical: (704) 684-1811

Website www.rscbrands.com E-mail sds@rscbrands.com

**Emergency phone number** Emergency Telephone: (303) 623-5716

Emergency Contact: RMPDC (877) 740-5015

# 2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Distillates, Petroleum, Solvent-dewaxed Heavy Paraffinic		64742-65-0	60 - < 70
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	20 - < 30
2,6-di-tert-butyl-p-cresol		128-37-0	< 1
Other components below reportabl	e levels		5 - < 10

Material name: Solder Seal/Gunk Motor Medic Oil Treatment

SDS US

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware General information

of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation, Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

SDS US

pistillates (petroleum), lydrotreated Heavy laphthenic (CAS 4742-52-5)  pistillates, Petroleum, colvent-dewaxed Heavy taraffinic (CAS 4742-65-0)  IS. ACGIH Threshold Limit Values components	PEL PEL Type	5 mg/m3 2000 mg/m3 500 ppm 5 mg/m3 2000 mg/m3 500 ppm	Mist.	
olvent-dewaxed Heavy Paraffinic (CAS 4742-65-0) US. ACGIH Threshold Limit Values		500 ppm 5 mg/m3 2000 mg/m3	Mist.	
olvent-dewaxed Heavy Paraffinic (CAS 4742-65-0) US. ACGIH Threshold Limit Values		5 mg/m3 2000 mg/m3	Mist.	
olvent-dewaxed Heavy Paraffinic (CAS 4742-65-0) US. ACGIH Threshold Limit Values		2000 mg/m3	MIST.	
S. ACGIH Threshold Limit Values	Туре	•		
	Туре	500 ppm		
	Туре			
Components	Туре			
		Value	Form	
,6-di-tert-butyl-p-cresol CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.	
Distillates (petroleum),	TWA	5 mg/m3	Inhalable fraction.	
lydrotreated Heavy laphthenic (CAS 4742-52-5)		•		
vistillates, Petroleum, solvent-dewaxed Heavy Paraffinic (CAS 4742-65-0)	TWA	5 mg/m3	Inhalable fraction.	
S. NIOSH: Pocket Guide to Chemical Ha	ızards			
components	Туре	Value	Form	
,6-di-tert-butyl-p-cresol CAS 128-37-0)	TWA	10 mg/m3		
vistillates (petroleum), lydrotreated Heavy laphthenic (CAS 4742-52-5)	Ceiling	1800 mg/m3		
,	STEL	10 mg/m3	Mist.	
Distillates, Petroleum, Holvent-dewaxed Heavy Paraffinic (CAS 4742-65-0)	Ceiling	1800 mg/m3		
,	STEL	10 mg/m3	Mist.	
gical limit values No biologica	I exposure limits noted for the ingre	dient(s).		
ols should be m or other eng	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.			

Biol

**App** conf

# Indi

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear protective gloves. Wear protective gloves. Other

**Respiratory protection** If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Viscous. Liquid **Appearance** 

Physical state Liquid. Form Liquid.
Color Light yellow.

Odor Mild

Odor threshold Not available.

**pH** 10.5

Melting point/freezing point -20 °F (-28.89 °C) estimated Initial boiling point and boiling 500 °F (260 °C) estimated

range

Flash point 397.4 °F (203.0 °C) Cleveland Open Cup

Evaporation rateNot available.Flammability (solid, gas)Not applicable.Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure < 0.1 mm Hg

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

**Decomposition temperature** Not available. **Viscosity** 400 cSt

Other information

Density7.17 lbs/galExplosive propertiesNot explosive.Flammability classNot FlammableFlash point class212 °F (100 °C)Oxidizing propertiesNot oxidizing.

Specific gravity 0.86 VOC 0 % w/w

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid**Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

**Skin contact** Prolonged and repeated contact with skin can cause defatting and drying of skin which may result

in skin irritation and dermatitis.

**Eye contact** May be irritating to eyes.

Material name: Solder Seal/Gunk Motor Medic Oil Treatment

M1815, M1949 Version #: 05 Revision date: 03-15-2017 Issue date: 04-21-2015

**Ingestion** May cause irritation of the mucous membranes.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

#### Information on toxicological effects

Acute toxicity Not known.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

May be irritating to eyes.

#### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

#### Carcinogenicity

#### IARC Monographs. Overall Evaluation of Carcinogenicity

2,6-di-tert-butyl-p-cresol (CAS 128-37-0)

3 Not classifiable as to carcinogenicity to humans.

Distillates, Petroleum, Solvent-dewaxed Heavy Paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-65-0)

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

Chronic effects Not available.

#### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

# DOT

Not regulated as dangerous goods.

M1815, M1949 Version #: 05 Revision date: 03-15-2017 Issue date: 04-21-2015

#### IATA

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to Not

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

# 15. Regulatory information

**US federal regulations**This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard 2012, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

# CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

# SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

# SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

**US state regulations**California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5) Distillates, Petroleum, Solvent-dewaxed Heavy Paraffinic (CAS 64742-65-0)

# **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes

Country(s) or region Inventory name On inventory (yes/no)\*

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 04-21-2015

 Revision date
 03-15-2017

Version # 05

HMIS® ratings Health: 0

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 0

Flammability: 1 Instability: 0

**NFPA** ratings



**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** Physical & Chemical Properties: Multiple Properties

Material name: Solder Seal/Gunk Motor Medic Oil Treatment

M1815, M1949 Version #: 05 Revision date: 03-15-2017 Issue date: 04-21-2015

Yes