



MAASDAM

POWER-PULL®

THE ORIGINAL SINCE 1946

*MAASDAM - THE ORIGINAL
OFTEN IMITATED....NEVER DUPLICATED™*

TABLE OF CONTENTS

CABLE POW'R PULLS	3
LONG HAUL ROPE POW'R PULLS	4
STRAP POW'R PULLS	4
CAL SERIES	5
POST PULLER	5
FENCING TOOLS	5
REPLACEMENT ROPE & STRAPS	6
POW'R REACH	6
REPLACEMENT KITS	6
CABLE PULLER PARTS	7
STRAP PULLER PARTS	7
JACKALL & PARTS	7
LOAD BINDERS	8
MANUAL CHAIN HOISTS	9
LEVER HOIST	9
TROLLEY JACKS	10
JACK STANDS	10
BOTTLE JACKS	11

▼ REFER TO BOTTOM OF PAGE WHEN YOU SEE THIS SYMBOL

MADE IN THE USA OF U.S. AND IMPORT PARTS

CABLE PULLERS

Lifetime Warranty

1 TON CABLE PULLER ▼

- » Model #: 144S-6
- » Weight: 7.63 lbs
- » Cable Length: 12 ft.
- » Cable Lift: 12 ft.
- » Cable Diameter: 3/16-in.
- » Leverage: 15:1

2 TON CABLE PULLER ▼

- » Model #: 144SB-6
- » Weight: 8.75 lbs
- » Cable Length: 12 ft.
- » Cable Lift: 6 ft.
- » Cable Diameter: 3/16-in.
- » Leverage: 30:1

1 & 2 TON CABLE PULLER ▼

- » Model #: 144C-6
- » Weight: 9.13 lbs
- » Cable Length: 12 ft.(1 & 2 Ton)
- » Cable Lift: 12 ft. (1 Ton), 6 ft (2 Ton)
- » Cable Diameter: 3/16-in.
- » Leverage: 15:1 (1 Ton), 30:1 (2 Ton)


3/4 TON CABLE PULLER ▼

- » Model #: 264S-5
- » Weight: 7.86 lbs
- » Cable Length: 22 ft.
- » Cable Lift: 22 ft.
- » Cable Diameter: 5/32-in.
- » Leverage: 15:1

ADDITIONAL FEATURES:

- 1 piece, aluminum alloy ratchet wheel
- High strength, electro-plated steel parts
- "Notch-at-a-time" letdown
- Drop forged steel slip hooks
- Non-slip plastic grip
- OSHA recommended safety latches
- Uses galvanized, aircraft-quality cable

For over 60 years, Maasdam® has produced Pow'R-Pulls to exacting standards. Using only premium components, we produce the finest quality winch/puller available, backed by a full Lifetime Warranty - a first for domestic winches.



MADE IN THE USA OF U.S. AND IMPORT PARTS

HEAVY-DUTY POW'R PULLS

Lifetime Warranty

3 TON CABLE PULLER ▼

- » Model #: 6000S
- » Weight: 29.0 lbs
- » Cable Length: 12 ft.
- » Cable Lift: 12 ft.
- » Cable Diameter: 5/16-in.
- » Leverage: 35:1

4 TON CABLE PULLER ▼

- » Model #: 8000SB
- » Weight: 34 lbs
- » Cable Length: 6 ft.
- » Cable Lift: 6 ft.
- » Cable Diameter: 5/16-in.
- » Leverage: 65:1



ADDITIONAL FEATURES:

- 1 piece, aluminum alloy ratchet wheel
- High strength, electro-plated steel parts
- Galvanized 5/16" Aircraft Cable
- "Notch-at-a-time" letdown
- Drop forged steel slip hooks
- Permanent, non-slip plastic grip
- 8000SB has patented compound lever

SUGGESTED APPLICATIONS:

- Lifting construction material
- Moving, placing and installing heavy equipment
- Tightening conveyor belts
- Clearing debris
- Erecting buildings and towers

AIRCRAFT CABLE RATINGS



Cable Swaging

Method of securely inserting aircraft cable into terminal end for everlasting bond

AIRCRAFT CABLE RATINGS	CABLE DIAMETER	MINIMUM BREAKING STRENGTH TESTED
• Based on military specs	3/16-in.	4,200 lbs.
• 70-in. x 19-in. galvanized aircraft cable	5/32-in.	2,800 lbs.
	1/8-in.	2,000 lbs.

LONG HAUL ROPE POW'R PULLS

Lifetime Warranty

3/4 TON ROPE PULLER ▼

MODEL #: A-0

- » Weight: 7.0 lbs.
- » Rope Length: No Rope
- » Rope Lift: No Rope
- » Rope Diameter: No Rope.
- » Leverage: 10:1



3/4 TON ROPE PULLER ▼

MODEL #: A-20

- » Weight: 8.8 lbs
- » Rope Length: 20 ft.
- » Rope Lift: 20 ft.
- » Rope Diameter: 1/2-in.
- » Leverage: 10:1



3/4 TON ROPE PULLER ▼

MODEL #: A-50

- » Weight: 11.25 lbs
- » Rope Length: 50 ft.
- » Rope Lift: 50 ft.
- » Rope Diameter: 1/2-in.
- » Leverage: 10:1



3/4 TON ROPE PULLER ▼

MODEL #: A-100

- » Weight: 14.31 lbs
- » Rope Length: 100 ft.
- » Rope Lift: 100 ft.
- » Rope Diameter: 1/2-in.
- » Leverage: 10:1



FEATURES:

- Manufactured to the same exacting standards as our cable pullers
- Uses highway approved, 1/2" diameter wear resistant Dacron® polyester rope - twisted or braided
- Can accommodate an unlimited length of rope

SUGGESTED APPLICATIONS:

- Recovering vehicles
- Handling logs, trees and stumps
- Transporting furniture
- Securing material to trucks
- Moving boats and trailers
- Clearing debris

STRAP POW'R PULLS

Lifetime Warranty

1 TON STRAP PULLER ▼

MODEL #: WS-1

- » Weight: 7.22 lbs
- » Strap Length: 12 ft.
- » Strap Lift: 11 ft. 6-in.
- » Strap Width: 1-in.
- » Leverage: 10:1



2 TON STRAP PULLER ▼

MODEL #: WS-2

- » Weight: 8.33 lbs
- » Strap Length: 12 ft.
- » Strap Lift: 5 ft. 8-in.
- » Strap Width: 1-in.
- » Leverage: 20:1



1 TON STRAP PULLER ▼

MODEL #: WS-25

- » Weight: 7.67 lbs
- » Strap Length: 25 ft.
- » Strap Lift: 10 ft.
- » Strap Width: 1-in.
- » Leverage: 10:1



FEATURES:

- Flexible strapping material conforms to and controls the load - non-conductive properties
- Precision-cast aluminum alloy ratchet wheel - one piece construction
- Interlocking, precision fit, steel alloy pawls with safety spacer sleeve
- Cold rolled, high strength, tempered steel frame and handle
- Drop-forged steel slip hooks with OSHA recommended safety latches
- Heavy gauge steel, reinforced ratchet guard
- Aircraft-type, heat treated bolts
- High tensile, fully rotating steel swivel
- Trouble free, "Notch-at-a-time" letdown
- Permanent, comfortable, non-slip grip

SUGGESTED APPLICATIONS:


- Vehicle recovery/rescue
- Race car/auto tie down
- Furniture/appliance moving
- Securing motorcycles/ATV's
- Animal loading assistance

CAL SERIES

EZ2000 1/2 TO 1 TON CAPACITY ▼

Limited Quantity - While Supplies Last

- » Weight: 7.34 lbs
- » Cable Length: 5 - 10 ft.
- » Cable Lift: 5 ft. (max.)
- » Cable Diameter: 3/16-in.




EZ WINCH UNIT FEATURES:

- 1/2 - 1 ton capacity, 5 - 10 foot reach
- Portable fold away unit takes up very little space convenient storage, dimensions: 12-in. x 4-in. x 9-in.
- Easy storage plastic molded case - No loose metal parts to mar or scratch
- OSHA approved safety latches so hooks stay connected
- Snap block included for easy conversion from 1,000 to 2,000 lb. pull.

CAL-1 1 TON CAPACITY ▼

Limited Quantity - While Supplies Last

- » Weight: 7.5 lbs.
- » Cable Length: 12 ft.
- » Cable Lift: 12 ft.
- » Cable Diameter: 3/16-in.



CAL-2 2 TON CAPACITY ▼

Limited Quantity - While Supplies Last

- » Weight: 9.0 lbs.
- » Cable Length: 12 ft.
- » Cable Lift: 6 ft.
- » Cable Diameter: 3/16-in.



CAL-3 3 TON CAPACITY ▼

Limited Quantity - While Supplies Last


- » Weight: 9.5 lbs.
- » Cable Length: 6 ft.
- » Cable Lift: 6 ft.
- » Cable Diameter: 3/16-in.



CAL-4 4 TON CAPACITY ▼

Limited Quantity - While Supplies Last

- » Weight: 10.5 lbs.
- » Cable Length: 6 ft.
- » Cable Lift: 6 ft.
- » Cable Diameter: 1/4-in.



CAL UNIT FEATURES:

- Galvanized, aircraft quality cable
- Double locking drive pawls
- Drop-forged steel frame galvanized against rust
- Forged steel hooks with OSHA recommended safety latches
- Oversized steel safety guard
- Reliable stainless steel springs
- Automatic let-down with safety catch
- Cable guide guards against excessive wear

POST PULLER

MODEL #: PP-100 ▼

- » Dimensions: 36.5-in. x 6-in. x 5-in.
- » Weight: 14.0 lbs.



- Easy to use—attaches to most posts or stakes in seconds
- Perfect balance maximizes the user's leverage while minimizing effort
- Pulls post straight out of the ground—does not bend post, so it can be reused
- Cost effective—no need to rent or buy heavy equipment

FENCING TOOLS

FENCE STRETCHER ▼

MODEL #: 8060

- » Dimensions: 17.37-in. x 1-in. x 4-in.
- » Weight: 2.0 lbs.



- Tightens tension bar toward end of post for easy tie-off
- Self locking action allows easier two handed tie-off
- Universal adjustment for posts from 1-3/8-in. - 4-in.

FENCE PULL CHAIN ▼

MODEL #: 8035-10

- » Chain length: 58-in.
- » Weight: 4.9 lbs




- Perfect Pow'R-Pull accessory for stretching chain link fence - 1/2 ton (1000 lbs.) rating
- Grab lock fits tension bars
- Adjustable 53-in. grade 30 proof coil chain

WIRE GRIP ▼

MODEL #: 8050-10

- » Dimensions: 7.25-in. x 3.25-in. x .87-in.
- » Weight: 4.9 lbs.



- Handles smooth or barbed wire as small as 5/32-in.
- Cam action insures tighter lock
- Shields and protects hand from barbed wire
- 1000 lb. (1/2 ton) capacity
- Cast malleable iron, plated to prevent rusting

10-IN. FENCE PLIERS ROUND NOSE ▼

MODEL #: 8090

- » Dimensions: 10.25-in. x 1.5-in. x .63-in.
- » Weight: 1.1 lbs.



- Smooth working action
- Forged construction
- Wire cutters

REPLACEMENT ROPES & STRAPS

All dimensions given as length x width x height



ROPE ONLY - SUPPLIED WITH 1/4-IN. HOOK ▼

Part No.	Length	Diameter	Weight
» 3973	» 20 ft.	» 1/2-in.	» 1.81 lbs.
» 3973-50	» 50 ft.	» 1/2-in.	» 4.25 lbs.
» 3973-100	» 100 ft.	» 1/2-in.	» 5.63 lbs.



STRAP ONLY - SUPPLIED WITH 1/4-IN. HOOK ▼

Part No.	Length	Width	Weight
» 6010-1WS	» 12 ft.	» 1-in.	» 0.75 lbs.
» 6010-25WS	» 25 ft.	» 1-in.	» 1.1 lbs.
» 6010-2WS (no hook)	» 12 ft.	» 1-in.	» 0.75 lbs.

POW'R REACH

POW'R-REACH CABLE EXTENDER ▼

MODEL #: 8106

- » Size: 6-ft.
- » Weight: 0.75 lbs.

- Extensions for cable Pow'R-Pulls
- 3/16-in. vinyl coated aircraft cable with cable eye on each end



POW'R-REACH CABLE EXTENDER ▼

MODEL #: 8112

- » Size: 12-ft.
- » Weight: 1.2 lbs.

- Extensions for cable Pow'R-Pulls
- 3/16-in. vinyl coated aircraft cable with cable eye on each end



POW'R-REACH STRAP EXTENDER ▼

MODEL #: SC12

- » Size: 12-ft.
- » Weight: 0.5 lbs.

- Extensions for strap Pow'R-Pulls
- Loops on both end - use loop-to-hook or as a slip knot
- Idea for wrapping around posts or trees



REPLACEMENT KITS

HANDLE ASSEMBLY REPLACEMENT KIT

MODEL #: MPPHRK ▼

Kit includes:

- A - 9000 Handle Assembly
- B - 7968AU Leaf Spring
- C - 7968B Screw




FRAME ASSEMBLY REPLACEMENT KIT

MODEL #: MPPFRK ▼

Kit includes:

- D - 9100 - Frame Assembly
- E - 7978 - Cable guide
- F - 7981 - Guide bolt
- G - 7981A - Nut



RATCHET WHEEL REPLACEMENT KIT

MODEL #: MPPRWRK ▼

Kit includes:

- H - 7963X - Ratchet wheel
- I - 7963A - Set Screw
- J - 7985 - Cable retainer spring
- K - 7988 - Ratchet wheel bolt
- L - 7981A - Nut
- M - 7987 - Ratchet wheel spacer sleeve




ROPE PULLER REPLACEMENT KIT

MODEL #: MPPRPRK ▼

Kit includes:

- N - 3961 - Frame Assembly
- O - 3962 - Ratchet Wheel
- P - 3965 - Guide
- Q - 7981 - Guide bolt
- R - 7981A - Nut
- S - 7987 - Ratchet wheel spacer sleeve
- T - 7988 - Ratchet wheel bolt




STRAP PULLER REPLACEMENT KIT

MODEL #: MPPSPRK ▼

Kit includes:

- U - 6000W - Ratchet Wheel
- V - 7988 - Ratchet wheel bolt
- W - 7981A - Nut
- X - 7987 - Ratchet wheel spacer sleeve



CABLE PULLER PARTS



1/4-IN. HOOK KIT MODEL #: 7977J ▼

- » 7973 - 1/4-in. Hook
- » 7977A - Yoke
- » 7980 - Swivel body bolt & nut
- » Weight: 0.54 lbs.

MODEL #: 7975J ▼

- » Swivel 1/4-in. hook assembly for 1 ton unit
- » Weight: 0.88 lbs.



MODEL #: 7975JA ▼

- » Swivel 5/16-in. hook assembly for 2 ton unit
- » Weight: 1.0 lbs.

MODEL #: 8049 ▼

- » Snap block with 5/16-in. hook
- » Use with Cable Puller
- » Weight: 1.25 lbs.



MODEL #: 9700BX ▼

- » 12-ft. cable for 144-S, SB, C & D
- » Weight: 1.0 lbs.

MODEL #: 9704BX ▼

- » 22-ft. cable for 264S-5
- » Weight: 1.25 lbs.



STRAP PULLER PARTS



MODEL #: 6020 ▼

- » Snap block with 5/16-in. hook - Strap Puller
- » Weight: 1.25 lbs.

JACKALL

MODEL #: 1130 ▼

- » Size: 48-in.
- » Weight: 28.5 lbs.

MODEL #: 1235 ▼

- » Size: 60-in.
- » Weight: 29.0 lbs.

FEATURES:

- Lift, pull, winch, push, hoist from 50 up to 8000 lbs. (4 tons)*
- Precision cast components; long life & trouble free operating
- Hot roll-formed, alloy steel beam is made strong and reliable
- Beam holes accommodate attachment of clevis pins, chains, bolts, ropes, etc.
- Hollow, special high tensile steel handle locks against beam for convenient storage
- Extra large 38-1/2 sq. in. base is heavily ribbed for strength and load stability

*Maximum capacity reached within 12-in. of base. Capacity decreases as distance from base increases.

Maasdam's 8,000 lb. Capacity Jacks, like all our pullers and products, are the best available. Built with a designed "Safety-Link," the Maasdam Jackall® is the "Jack with More"! Larger base for greater stability. "Safety Link" mechanism that prevents abuse, misuse and makes operations safer. When safety and dependability matter most, continue to rely on Maasdam®.



JACKALL ACCESSORIES



MODEL #: 1333 ▼

- » Jack Maintenance Kit
- » Weight: 1.0 lbs.



MODEL #: 1313 ▼

- » Jack Rack
- » Weight: 2.7 lbs.



MODEL #: 1323 ▼

- » Jack Quick Clamp
- » Weight: 1.6 lbs.



MODEL #: 1390 ▼

- » Jack Adapter
- » Weight: 1.0 lbs.

LOAD BINDERS

MINI BIND'R FEATURES:

- Forged steel mini binder, for use with cable, chain or rope
- Swivel hook
- 7 inch handle



MINI TIGHTENER BIND'R 175#

MODEL #: 48979M ▼

Limited Quantity - While Supplies Last

- » Weight: 1.1 lbs.
- » Min-Max Chain Size: 1/4-in.
- » Take Up: 3.5-in.
- » Handle Length: 7-in.
- » WLL: 175 lbs.
- » Proof Load: 350 lbs.
- » Ultimate Strength: 525 lbs.

MINI TIGHTENER BIND'R 250#

MODEL #: 48919M ▼

Limited Quantity - While Supplies Last

- » Weight: 1.1 lbs.
- » Min-Max Chain Size: 1/4-in.
- » Take Up: 3.5-in.
- » Handle Length: 7-in.
- » WLL: 250 lbs.
- » Proof Load: 500 lbs.
- » Ultimate Strength: 750 lbs.

MINI TIGHTENER BIND'R 375#

MODEL #: 48949M ▼

Limited Quantity - While Supplies Last

- » Weight: 1.25 lbs.
- » Min-Max Chain Size: 1/4-in.
- » Take Up: 3.5-in.
- » Handle Length: 7-in.
- » WLL: 375 lbs.
- » Proof Load: 750 lbs.
- » Ultimate Strength: 1,500 lbs.

PRO LOAD BIND'R FEATURES:

- Forged steel, quenched and tempered
- Ball and socket swivel joints at hook assemblies permit a straight line pull
- Binder toggles away from the load
- Extra heavy construction at leverage points to prevent spreading

1/4-IN. MALLEABLE PRO LOAD BINDER ▼

MODEL #: 48304M

Limited Quantity - While Supplies Last

- » Weight: 2.75 lbs.
- » Min-Max Chain Size: 1/4-in.
- » Take Up: 4-in.
- » Handle Length: 11-in.
- » WLL: 2,600 lbs.
- » Proof Load: 5,200 lbs.
- » Ultimate Strength: 9,200 lbs.



3/8-IN. MALLEABLE PRO LOAD BINDER ▼

MODEL #: 48305M

Limited Quantity - While Supplies Last

- » Weight: 6.55 lbs.
- » Min-Max Chain Size: 5/16-in. to 3/8-in.
- » Take Up: 4.5-in.
- » Handle Length: 16-in.
- » WLL: 5,400 lbs.
- » Proof Load: 10,800 lbs.
- » Ultimate Strength: 19,000 lbs.



TRANSPORT BIND'R FEATURES:

- Forged steel, quenched and tempered
- Ball and socket swivel joints at hook assemblies permit a straight line pull
- Binder toggles away from the load
- Extra heavy construction at leverage points to prevent spreading

3/8-IN. TRANSPORT BINDER MODEL #: 48311M ▼

Limited Quantity - While Supplies Last

- » Weight: 7.45 lbs.
- » Min-Max Chain Size: 1/2-in. to 5/8-in.
- » Take Up: 4.75-in.
- » Handle Length: 21-in.
- » WLL: 5,400 lbs.
- » Proof Load: 10,800 lbs.
- » Ultimate Strength: 19,000 lbs.



MANUAL CHAIN HOISTS

MANUAL CHAIN HOIST FEATURES:

- Economical hand chain hoist designed for years of trouble free service
- Steel construction with powder coating
- Lightweight, compact design for tight applications
- Needle bearing for smooth operations
- Completely enclosed brake system for precise load spotting
- Conforms to ANSI/ASME B30.21-1999

48500 1/2 TON CAPACITY ▼

Limited Quantity - While Supplies Last

- » Weight: 22.0 lbs.
- » Lift: 10 ft.
- » Hook size: 1-1/8-in.
- » Housing dimensions: 5.75-in. x 5-in. x 6.25-in.
- » Housing and Hook length: 10.5-in.



48510 1 TON CAPACITY ▼

Limited Quantity - While Supplies Last

- » Weight: 22.75 lbs.
- » Lift: 10 ft.
- » Hook size: 1-1/8-in.
- » Housing dimensions: 5.75-in. x 5-in. x 6.25-in.
- » Housing and Hook length: 10.5-in.

LEVER HOISTS

LEVER CHAIN HOIST FEATURES:

- Automatic brake system holds load in any position
- Freewheeling feature without load for quick load attachment
- All steel construction with durable powder-coat finish
- Drop forged hooks with heavy-duty safety latches swivel 360° for easy rigging
- Conforms to ANSI/ASME B30.21-1999

48600 3/4 TON CAPACITY ▼

Limited Quantity - While Supplies Last

- » Weight: 15.25 lbs.
- » Lift: 5 ft.
- » Hook size: 1-1/4-in.
- » Housing dimensions: 5-in. x 3.75-in. x 4.75-in.
- » Handle length: 12-in.



48610 1-1/2 TON CAPACITY ▼

Limited Quantity - While Supplies Last

- » Weight: 26.5 lbs.
- » Lift: 5 ft.
- » Hook size: 1-3/8-in.
- » Housing dimensions: 6-in. x 4.5-in. x 5.25-in.
- » Handle length: 16.75-in.

TROLLEY JACKS

MPL4136 ▼
2 TON CAPACITY
TROLLEY JACK



- » Maximum Load Capacity: 2 Tons (4000 lbs.)
- » Lifting Range: 3 in. to 13 in.
- » Saddle Dimensions: 1.875 in. diameter
- » Size: 17-1/2 in. x 7-3/4 in. x 5-1/2 in.
- » Weight: 18.3 lbs.

FEATURES:

- Small frame for easy maneuverability and lightweight design
- Removable pump handle for easy storage and ease of lowering jack
- Swivel casters for maneuvering and smooth positioning
- Swiveling saddle to adjust placement for stability
- Carrying handle for easy portability
- Meets ANSI/ASME standard requirements

MPL1449-HD 3 TON CAPACITY ▼
COMMERCIAL GRADE
SUV/EQUIPMENT JACK
(FOOT PUMP WITH SLEEVE)



- » Maximum Load Capacity: 3 Tons (6000 lbs.)
- » Lifting Range: 7.5 in. to 21 in.
- » Saddle Dimensions: 2.28 in. diameter
- » Size: 25 in. x 10 in. x 7-1/2 in.
- » Weight: 45 lbs.

FEATURES:

- 360° swivel saddle for solid load contact, adjustable saddle height
- Rust resistant finish for long life
- Heavy gauge steel frame provides strength and durability
- Ball-bearing swivel casters for easy jack positioning
- Handle with extra large grip for added comfort
- Meets ANSI/ASME standard requirements

JACK STANDS

MPL4117 ▼
2 TON JACK STAND

- » Maximum Load Capacity: 2 Tons (4,000 lbs.)
- » Lifting Range: 10.5-in. to 17-in.
- » Base Dimensions: 7-in. x 7.5-in.
- » Weight: 11 lbs.



FEATURES:

- Heavy-duty steel base with anti-sink feet
- Use with SUV, light truck and automobiles
- Iron saddle
- Extended reach
- Meets ANSI/ASME standard requirements

MPL4124-HD ▼
3 TON JACK STAND

- » Maximum Load Capacity: 3 Tons (6,000 lbs.)
- » Lifting Range: 12-in. to 17.5-in.
- » Base Dimensions: 7.5-in. x 8.25-in.
- » Weight: 12 lbs. (6 lbs. each)



FEATURES:

- Heavy-duty steel base with anti-sink feet
- Use with SUV, light truck and automobiles
- Iron saddle
- Extended reach
- Meets ANSI/ASME standard requirements

MAASDAM
POW'R-LIFT™

BOTTLE JACKS

MPL2B ▼

- » Maximum Load Capacity: 2 Tons (4,000 lbs.)
- » Lifting Range: 7-1/2-in. to 13-9/16-in.
- » Saddle Dimensions: 3/4-in. diameter
- » Weight: 6.5 lbs.

FEATURES:

- Adjustable load saddle
- Meets ANSI standard requirements



MPL2B ▼

- » Maximum Load Capacity: 2 Tons (4,000 lbs.)
- » Lifting Range: 7-1/2-in. to 13-9/16-in.
- » Saddle Dimensions: 3/4-in. diameter
- » Weight: 6.5 lbs.

FEATURES:

- Adjustable load saddle
- Meets ANSI standard requirements



MPL6B ▼

- » Maximum Load Capacity: 6 Tons (12,000 lbs.)
- » Lifting Range: 8-1/2-in. to 16-1/4-in.
- » Saddle Dimensions: 1-1/4-in. diameter
- » Weight: 7.9 lbs.

FEATURES:

- Adjustable load saddle
- Meets ANSI standard requirements



MPL8B ▼

- » Maximum Load Capacity: 8 Tons (16,000 lbs.)
- » Lifting Range: 8-1/2-in. to 17-in.
- » Saddle Dimensions: 1-3/8-in. diameter
- » Weight: 13.5 lbs.

FEATURES:

- Adjustable load saddle
- Meets ANSI standard requirements
- Carrying handle



MPL12B ▼

- » Maximum Load Capacity: 12 Tons (24,000 lbs.)
- » Lifting Range: 9-1/2-in. to 18-7/16-in.
- » Saddle Dimensions: 1-5/8-in. diameter
- » Weight: 13.1 lbs.

FEATURES:

- Adjustable load saddle
- Meets ANSI standard requirements
- Carrying handle



MPL20B ▼

- » Maximum Load Capacity: 20 Tons (40,000 lbs.)
- » Lifting Range: 9-1/2-in. to 17-in.
- » Saddle Dimensions: 1-7/8-in. diameter
- » Weight: 19.2 lbs.

FEATURES:

- Adjustable load saddle
- Meets ANSI standard requirements
- Carrying handle





Pull'R Holding Company, LLC
415 East State Parkway, Schaumburg, IL 60173
888-797-7855

WWW.MAASDAM.COM