# Safety Data Sheet ULTRAFLEX 2 GRAY

Safety Data Sheet dated: 06/11/2021 - version 1

Date of first edition: 06/11/2021

# **MAPEI**

# 1. Identification

#### **Product identifier**

Mixture identification:

Trade name: ULTRAFLEX 2 GRAY

Other means of identification Trade code: 9029058

**Recommended use and restrictions on use** Recommended use: Polymer modified mortar

Restrictions on use: N.A. **Supplier's details** 

Company: MAPEI INC. (Canada)

2900 Francis-Hughes Avenue H7L 3J5 - Laval - QC - CAN

# **Emergency phone number**

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

# 2. Hazard identification







# Classification of the product

Skin Corr. 1A Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1 May cause an allergic skin reaction.

Carc. 1A May cause cancer if inhaled.

STOT SE 3 May cause respiratory irritation.

STOT RE 1 Causes damage to organs through prolonged or repeated exposure if inhaled.

# Label elements

# **Pictograms and Signal Words**



Danger

# Hazard statements:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H350 May cause cancer if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

# **Precautionary statements:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Print date 11/10/2022 Production Name ULTRAFLEX 2 GRAY Page n. 1 of 8

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a doctor.

P321 Specific treatment (see supplementary instructions on this label)
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

#### Other hazards

None

# Ingredient(s) with unknown acute toxicity

None

# 3. Composition/information on ingredients

#### **Substances**

N.A.

# Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

#### List of components

Concentra Name
tion (%
w/w)

50-75 % silica sand; quartz

CAS:14808-60-7 STOT RE 1, H372; Carc. 1A, H350

CAS:65997-15-1 STOT SE 3, H335; Eye Dam. 1,
portland, chemicals

CAS:65997-15-1 STOT SE 3, H317; Skin
Corr. 1A, H314

The actual concentration of the components listed above is withheld as a trade secret.

# 4. First-aid measures

# Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

# Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

# Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

#### 5. Fire-fighting measures

# Suitable and unsuitable extinguishing media

Print date 11/10/2022 Production Name ULTRAFLEX 2 GRAY Page n. 2 of 8

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

# Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke. Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

# Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

# Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

# 7. Handling and storage

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

# 8. Exposure controls/personal protection

# **Control parameters**

# List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour Note
silica sand; quartz	ACGIH			0,025				A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;

portland cement; cement, OSHA 15 portland, chemicals

Print date 11/10/2022 Production Name ULTRAFLEX 2 GRAY Page n. 3 of 8

OSHA

**ACGIH** 

Human Carcinogen; pulmonary function; respiratory

A4 - Not Classifiable as a

symptoms; asthma;

**ACGIH** 1 A4 - Not Classifiable as a Human

Carcinogen; pulmonary function; respiratory symptoms;asthma

MAK **AUSTRIA** 5 MAK SWITZERI AND 5

#### Appropriate engineering controls

N.A.

# Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

# 9. Physical and chemical properties

#### Information on basic physical and chemical properties

Physical state: Solid

Appearance and colour: powder Grey

Odour: cement like

Odour threshold: No data available

pH: No data available

pH (water dispersion, 10%): 11.50

Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: No data available Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 2.15 g/cm3 Solubility in water: Soluble Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

#### Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

Print date 11/10/2022 Production Name **ULTRAFLEX 2 GRAY** 4 of 8 Page n.

#### 10. Stability and reactivity

#### Reactivity

Stable under normal conditions

# **Chemical stability**

Data not available.

# Possibility of hazardous reactions

None.

#### Conditions to avoid

Stable under normal conditions.

#### **Incompatible materials**

None in particular.

#### Hazardous decomposition products

None.

#### 11. Toxicological information

# Information on toxicological effects

#### Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

#### Toxicological information on main components of the mixture:

silica sand; quartz

a) acute toxicity

LD50 Oral Rat = 500 mg/kg

# If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

- i) STOT-repeated exposure
- j) aspiration hazard

# Substance(s) listed on the IARC Monographs:

silica sand; quartz

Group 1

# Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

# Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

# Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

# 12. Ecological information

#### **Ecotoxicity**

Adopt good working practices, so that the product is not released into the environment.

# List of components with eco-toxicological properties

Component Ident. Numb. Ecotox Infos

silica sand; quartz CAS: 14808-60- a) Aquatic acute toxicity: LC50 carp > 10000,00000 mg/L 72h

7

# Persistence and degradability

N.A.

Print date 11/10/2022 Production Name ULTRAFLEX 2 GRAY Page n. 5 of 8

#### **Bioaccumulative potential**

NΑ

#### Mobility in soil

N.A.

#### Other adverse effects

N.A.

# 13. Disposal considerations

# Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Any disposal practice must be in compliance with local, state and federal laws and regulations (contact local or state environmental agency for specific rules). Do not dump into sewers, any body of water or onto the ground.

#### Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

# Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

#### 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

# **UN** number

TDG-UN number: N.A. ADR-UN number: N.A. DOT-UN Number: N.A. IATA-Un number: N.A. IMDG-Un number: N.A.

# **UN** proper shipping name

TDG-Shipping Name: N.A.
ADR-Shipping Name: N.A.
DOT-Proper Shipping Name: N.A.
IATA-Technical name: N.A.
IMDG-Technical name: N.A.

# Transport hazard class(es)

TDG-Class: N.A.
ADR-Class: N.A.
DOT-Hazard Class: N.A.
IATA-Class: N.A.

IMDG-Class: N.A.

#### **Packing group**

TDG-Packing Group: N.A. ADR-Packing Group: N.A. DOT Packing Group: N.A. IATA-Packing group: N.A. IMDG-Packing group: N.A.

# **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: N.A.

# Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

# Special precautions in connection with transport or conveyance

Print date 11/10/2022 Production Name ULTRAFLEX 2 GRAY Page n. 6 of 8

```
TDG:
```

TDG Special provisions: N/A Department of Transportation (DOT):

N.A

Road and Rail ( ADR-RID ):

N.A.

Air (IATA):

N.A.

Sea ( IMDG ):

N.A.

# 15. Regulatory information

# Canada - Federal regulations

#### **DSL - Domestic Substances List**

**DSL Inventory:** 

All the substances are listed in the DSL.

#### **NDSL - Non Domestic Substances List**

**NDSL Inventory:** 

No substances listed

#### NPRI - National Pollutant Release Inventory

**Substances listed in NPRI:** 

No substances listed

# **USA - Federal regulations**

#### **TSCA - Toxic Substances Control Act**

**TSCA** inventory:

All the components are listed on the TSCA inventory

#### **TSCA listed substances:**

silica sand; quartz

is listed in TSCA Section 8b

portland cement; cement,

is listed in TSCA Section 8b

portland, chemicals

# **SARA - Superfund Amendments and Reauthorization Act**

# **Section 302 - Extremely Hazardous Substances:**

No substances listed

# Section 304 - Hazardous substances:

No substances listed

# Section 313 - Toxic chemical list:

No substances listed

# CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

# Substance(s) listed under CERCLA:

No substances listed

#### CAA - Clean Air Act

#### **CAA listed substances:**

No substances listed

# **CWA - Clean Water Act**

# **CWA listed substances:**

No substances listed

# **USA - State specific regulations**

# **California Proposition 65**

# Substance(s) listed under California Proposition 65:

silica sand; quartz

Listed as carcinogen

# Massachusetts Right to know

# Substance(s) listed under Massachusetts Right to know:

silica sand; quartz

portland cement; cement, portland, chemicals

# Pennsylvania Right to know

# Substance(s) listed under Pennsylvania Right to know:

Print date 11/10/2022 Production Name ULTRAFLEX 2 GRAY Page n. 7 of 8

silica sand; quartz

portland cement; cement, portland, chemicals

#### New Jersey Right to know

# Substance(s) listed under New Jersey Right to know:

silica sand; quartz

portland cement; cement, portland, chemicals

#### 16. Other information

Safety Data Sheet dated: 6/11/2021 - version 1

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350	May cause cancer.
H350	May cause cancer if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.

#### Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

 ${\sf GefStoffVO:}\ \ {\sf Ordinance}\ \ {\sf on}\ \ {\sf Hazardous}\ \ {\sf Substances},\ {\sf Germany}.$ 

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Print date 11/10/2022 Production Name ULTRAFLEX 2 GRAY Page n. 8 of 8