

# Cold Water Gasoline Direct Drive



The handy ChoreMaster® Series gasoline pressure washer is completely portable and will reach as far as your garden hose will take you. Use without the need of an electrical connection, this model is perfect for cleaning decks, driveways, and siding.

To see more online, scan here or go to [www.mitm.com](http://www.mitm.com):



**Pump**

- Aluminum manifold (brass manifold on CV-3000-OMSC)
- Thermal relief valve
- In-line water strainer
- Built-in low pressure detergent injection

**Frame**

- Removable large 1¼-inch powder coated steel tube handle
- Contoured-designed base plate with reinforced engine platform
- Large 12-inch semi-pneumatic tires

**Unit Includes:**

- 30-foot x ¼-inch nylon-braided pressure hose
- Professional-grade trigger gun



CV-2600-OMMC

*Limited Warranties:*

**1 Year**  
Honda Engine Pump

**1 Year**  
Mi-T-M Engine **3 Year**  
Subaru Engine

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CV-2600-OMHC <sup>^</sup>	2600	2.2	160cc Honda OHC	AR, axial	Preset pressure	15°, 25° & detergent nozzle	Two-piece, 36-in.	26x18x38in.	65 lb.	54 lb.
CV-2600-OMMC <sup>^</sup>	2600	2.2	170cc Mi-T-M OHV	AR, axial	Preset pressure	15°, 25° & detergent nozzle	Two-piece, 36-in.	26x18x38in.	65 lb.	54 lb.
CV-2600-OMSC <sup>+</sup>	2600	2.2	190cc Subaru OHC	AR, axial	Preset pressure	15°, 25° & detergent nozzle	Two-piece, 36-in.	26x18x38in.	65 lb.	54 lb.
CV-3000-1MHC <sup>^</sup>	3000	2.3	187cc Honda OHC	AR, axial	Preset pressure	15°, 25° & detergent nozzle	Two-piece, 36-in.	26x18x38in.	65 lb.	54 lb.
CV-3000-OMSC <sup>+</sup>	3000	2.4	190cc Subaru OHC	AR, axial	Preset pressure	15°, 25° & detergent nozzle	Two-piece, 36-in.	26x18x38in.	65 lb.	54 lb.

<sup>^</sup>Carb compliant in all 50 states. Can be sold in California.

<sup>+</sup>EPA compliant in 49 states. Cannot be sold in California.