



Mobil 1 10W30

Mobil Passenger Vehicle Lube , United States

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1 10W-30 is an advanced full synthetic engine oil designed to keep engines running like new by providing exceptional cleaning power, wear protection and overall performance. Mobil 1 10W-30 meets or exceeds the requirements of the latest industry standards required by modern gasoline engines. Mobil 1 technology comes as standard equipment in many different vehicles, including select high-performance vehicles

Features and Benefits

Mobil 1 10W-30 is made with a proprietary blend of ultra high performance synthetic basestocks fortified with a precisely balanced additive component system. This oil is uniquely designed to help provide unsurpassed levels of performance, cleaning power and engine protection, while meeting the demanding ILSAC GF-5 performance standards. Key features and potential benefits include:

Features	Advantages and Potential Benefits
Advanced Full synthetic formula	Helps prevent deposits and sludge build-up to enable long engine life Excellent overall lubrication and wear protection performance for many driving styles
Outstanding thermal and oxidation stability	Outstanding performance during the maximum oil change interval recommended in a vehicle's owners manual
Enhanced frictional properties	Aids fuel economy
Excellent low temperature capabilities	Quick cold weather starting for ultra fast protection Helps to extend engine life

Applications

Mobil 1 10W-30 is recommended for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline and diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

- 10W-30 is the recommended viscosity grade for a variety of SUV, light van and truck engines, as well as a number of older model passenger cars.
- Mobil 1 10W-30 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Specifications and Approvals

This product is recommended for use in applications requiring:
APICF
GM4718M
GM6094M

This product meets or exceeds the requirements of:

This product meets or exceeds the requirements of:

APISN

APISM

APISL

APISJ

ILSACGF-5

ACEAA5/B5-16

APISN PLUS

APISN PLUS RESOURCE CONSERVING

Properties and Specifications

Property	
Grade	SAE 10W-30
Ash, Sulfated, mass%, ASTM D874	0.8
Density @ 15.6 C, g/ml, ASTM D4052	0.859
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.1
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	63.2
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	146

Health and safety

<http://www.msds.exxonmobil.com/psims/psims.aspx> Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2019

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit

www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

© Copyright 2003-2019 Exxon Mobil Corporation. All
Rights Reserved