



## TECHNICAL SPECIFICATIONS

## SEWER AND DRAIN REDUCER COUPLING

MEETS ASTM STANDARDS:
PVC—ASTM D-3034, D-2729
STYRENE—D-2852
MOLDED IN THE USA
MADE OF PVC TYPE I MATERIAL
FITS THE FOLLOWING PIPES:
SDR-35, SDR-26, TRIPLE WALL, & ASTM D-2729 PIPE
HUB X HUB CONNECTION









| MATERIAL | PART<br>NUMBER | A<br>(INCHES) | B<br>INSIDE LARGER<br>DIAMETER<br>(INCHES) | C<br>INSIDE SMALLER<br>DIAMETER<br>(INCHES) | CONNECTION      | WEIGHT (LBS) |
|----------|----------------|---------------|--|---|-----------------|--------------|
| PVC      | 4P07           | 3.60          | 4.23                                       | 3.27  | 3" HUB X 4" HUB | 0.35         |
|          | 6P07           | 6.12          | 6.31                                       | 4.25  | 4" HUB X 6" HUB | 1.0          |
|          | 8P07           | 8.30          | 8.40                                       | 6.30  | 8" HUB X 6" HUB | 2.20         |
| STYRENE  | 407            | 3.60          | 4.23                                       | 3.27  | 3" HUB X 4" HUB | 0.20         |
|          | 607            | 6.12          | 6.31                                       | 4.25  | 4" HUB X 6" HUB | 0.80         |

NOTE: NOT FOR USE IN PRESSURIZED WATER SYSTEMS. 5 P.S.I. MAXIMUM DOES NOT FIT SCHEDULE 40 PIPE



