Incredible 5.0 525 Waterproof Floating Floor







Size

7" x 48" nominal (18 cm x 122 cm) 5.0 mm thick

Wear Layer

12 mil / UV-Cured Urethane

Edge Treatment

Four-Sided Microbevel

Installation

Angle-Angle Click Floating Floor (on, above or below grade)

Attached Cushion

For superior sound abatement and easier installation

Coordinating Moldings

See nextfloor.net for more details.

Packaging

12 pieces per carton (42 lbs) 28.4 SF per carton 55 cartons per pallet 18 pallets per container

Testing

Critical Radiant Flux

Surface Flammability Coefficient of Friction Static Load Limit Sound Transmission Class (STC) Impact Isulation Class (IIC) High Frequency Impact Isulation Class(HIIC) ASTM E3222 88 Floor Score Certified Phthalate Free 100% Virgin PVC

Warranties

Lifetime Waterproof Lifetime Residential Wear 10-Year Commercial Wear

*For moderate traffic areas without rolling loads, heavy fixtures or ramps. See full warranty text at nextfloor.net

ASTM E648 Class I

DOC FF 1-70 Passed

Passes>0.6

64

exceeds 3000 lbs

ASTM 2047

ASTM F970

ASTM E492

ASTM E989 71

Sample SKUs

Handle Boards HB525NF-B 10 per carton (126 lbs)

Strap Sets SS525NF-B 5 per carton (37.5 lbs)

Step Up Display 8CARDS525NF-1B (203, 204, 211, 208) 8CARDS525NF-2B (212, 051, 002, 193)

FIXT525NF

Packaged in 3 cartons (165 lbs)



