Datey®

SAFETY DATA SHEET

1. Identification

Product identifier Oatey Instant Solder

Other means of identification

SDS number 1607E

Synonyms Part Numbers: 53019, 53022

Recommended use Joining Copper Pipes. Joining Copper Tubing.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name Oatey Co.

Address 4700 West 160th St.

Cleveland, OH 44135

Telephone 216-267-7100 info@oatey.com

Transport Emergency Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

Emergency First Aid 1-877-740-5015
Contact person MSDS Coordinator

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

Serious eye damage/eye irritation Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage.

Precautionary statement

Prevention Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face

protection. Do not breathe dusts or mists.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Tin	7440-31-5	40-70
Zinc chloride	7646-85-7	10-30
Water	7732-18-5	7-13

Oatey Instant Solder SDS US

922644 Version #: 02 Revision date: 17-December-2014 Issue date: 23-October-2014

Copper	7440-50-8	1-5
Bismuth	7440-69-9	0.5-1.5
Propylene glycol	57-55-6	0.1-1
Other components below reportable levels		0.4

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Skin contact If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Take off immediately all contaminated clothing. Wash off with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

present and easy to do. Continue rinsing. Call a physician or poison control center immediately. Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs,

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

Ingestion

keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Diarrhea. Nausea, vomiting. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Dry sand. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions 7. Handling and storage

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Oatey Instant Solder SDS US

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Tin (CAS 7440-31-5)	PEL	2 mg/m3	
Zinc chloride (CAS 7646-85-7)	PEL	1 mg/m3	Fume.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.
,	TWA	1 mg/m3	Fume.
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
Tin (CAS 7440-31-5)	TWA	2 mg/m3	
Zinc chloride (CAS 7646-85-7)	STEL	2 mg/m3	Fume.
,	TWA	1 mg/m3	Fume.
US. Workplace Environmental Ex	xposure Level (WEEL) Guides		
Components	Туре	Value	Form

57-55-6) **Biological limit values**

Propylene glycol (CAS

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

10 mg/m3

Aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

TWA

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Other

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Paste. **Appearance** Physical state Solid. Solid. **Form** Color Gray. Chemical. Odor **Odor threshold** Not available. рH

Not available. Melting point/freezing point

Oatey Instant Solder SDS US Initial boiling point and boiling

range

Not available.

Not available. Flash point **Evaporation rate** Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Vapor density > 1 Relative density 3.5

Solubility(ies)

Vapor pressure

30% soluble Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. 30000 cP Viscosity

Other information

VOC (Weight %) 28 g/l 2% by weight

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Acids. Chlorine. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Causes severe skin burns. Skin contact Eve contact Causes serious eye damage. Causes digestive tract burns. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Diarrhea. Nausea, vomiting. Causes serious eye

damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Copper (CAS 7440-50-8)		
Acute		
Inhalation LC50	Rat	> 2.77 mg/l, 4 hours
Oral		<i>3</i> /
LD50	Rat	481 mg/kg

SDS US Oatey Instant Solder

922644 Version #: 02 Revision date: 17-December-2014 Issue date: 23-October-2014

Species Test Results Components

Propylene glycol (CAS 57-55-6)

Acute Oral

LD50 Rat 30 g/kg

* Estimates for product may be based on additional component data not shown. Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Propylene glycol (CAS 57-55-6) -0.92

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

Oatey Instant Solder SDS US

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Copper (CAS 7440-50-8)

Zinc chloride (CAS 7646-85-7)

LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Zinc chloride	7646-85-7	10-30	
Copper	7440-50-8	1-5	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Copper (CAS 7440-50-8)

Tin (CAS 7440-31-5)

Zinc chloride (CAS 7646-85-7)

US. New Jersey Worker and Community Right-to-Know Act

Copper (CAS 7440-50-8)

Propylene glycol (CAS 57-55-6)

Tin (CAS 7440-31-5)

Zinc chloride (CAS 7646-85-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Copper (CAS 7440-50-8)

Propylene glycol (CAS 57-55-6)

Tin (CAS 7440-31-5)

Zinc chloride (CAS 7646-85-7)

US. Rhode Island RTK

Copper (CAS 7440-50-8)

Zinc chloride (CAS 7646-85-7)

Oatey Instant Solder SDS US

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 23-October-2014
Revision date 17-December-2014

Version # 02

HMIS® ratings Health: 3

Flammability: 0 Physical hazard: 0

Disclaimer Oatey Co. cannot anticipate all conditions under which this information and its product, or the

products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Oatey Instant Solder SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).